View NSN Online: https://aerobasegroup.de/nsn/6630-01-210-8162

DEXSIL CHEMICAL CORP -- CLOR-N-OIL 500 PCB SCREENING KIT, AMPULE 1 -- 6630-01-210-8162

Product ID:CLOR-N-OIL 500 PCB SCREENING KIT, AMPULE 1 MSDS Date:03/14/1995 FSC:6630 NIIN:01-210-8162 MSDS Number: BXTJN === Responsible Party === Company Name: DEXSIL CHEMICAL CORP Address:1 HAMDEN PARK DRIVE **City:HAMDEN** State:CT ZIP:06517 Country:US Info Phone Num:203-288-3509 Em ergency Phone Num:203-288-3509/800-424-9300(CHEMTREC) CAGE:65297 === Contractor Identification === Company Name: DEXSIL CORP Address:1 HAMDEN PARK DR Box:City:HAMDEN State:CT ZIP:06514-3150 Country:US Phone:203-288-3509 CAGE:65297 

Ingred Name:SODIUM (CERCLA) CAS:7440-23-5 RTECS #:VY0686000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mix

AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SEE PHYSICIAN. SKIN:WASH WITH P LENTY OF SOAP & WATER. ORAL:SEEK IMMEDIATE MEDICAL ATTENTION.

Flash Point:>212F,>100C Extinguishing Media:DRY

CHEMICAL, FOAM, CARBON DIOXIDE. AVOID WATER ON A SODIUM FIRE.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:SODIUM OXIDE FUMES MAY BE FORMED.

Spill Release Procedures: AVOID CONTACT WITH SKIN. COVER SPILL WITH DRY SODA ASH. CAREFULLY TRANSFER TO A CONTAINER FOR LATER DISPOSAL. STORE IN WELL VENTILATED AREA AWAY FROM MOISTURE Neutralizing Agent: WEAK ACID

Handling and Storage Precautions:STORE IN COOL AND DRY PLACE. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. LAUNDER BEFORE REUSE. KEEP OUT OF REACH OF CHILDREN. ====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. Ventilation:ADEQUATE Protective Gloves: RUBBER Eye Protection:SAFETY GLASSES/GOGGLES Other Protective Equipment: SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY. WEAR APPROPRIATE PROTECTIVE CLOTHING FOR RISK OF EXPOSURE. Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health **KEY1:R2. THIS** PRODUCT IS A KIT CONSISTING OF SIX PARTS. AMPULE 1 HAS PNI B; AMPULE 2 HAS PNI C, AMPULE 3 HAS PNI D, AMPULE 4 HAS PNI E, AMPULE 5 HAS PNI F, AQUEOUS SOLUTION HAS PNI G, SAME NSN. FORMUL A CHAGED. FOR PREVIOUS FORMULATION, SEEPNI A. THIS IS FOR GRAY AMPULE. HCC:F3 NRC/State Lic Num:NOT RELEVANT Spec Gravity:0.86 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference: NOT RELEVANT Solubility in Water:REACTS Ap pearance and Odor: GRAY SOLID - ODORLESS Stability Indicator/Materials to Avoid:YES OXIDIZERS, ACIDS, WATER, ALCOHOLS, AMINES Stability Condition to Avoid:MOISTURE Hazardous Decomposition Products:SODIUM OXIDE Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the

## compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.