

OPTIMA BATTERIES INC -- SEALED LEAD ACID BATTERY,800 S -- 6140-01-378-8232

=====  
Product Identification  
=====

Product ID:SEALED LEAD ACID BATTERY,800 S

MSDS Date:12/13/1996

FSC:6140

NIIN:01-378-8232

MSDS Number: BXVSK

=== Responsible Party ===

Company Name:OPTIMA BATTERIES INC

Address:5 E MISSISSIPPI AVE

City:DENVER

State:CO

ZIP:80210

Country:US

Info Phone Num:303-744-5360/340-7400

Emergency Phon

e Num:303-744-5360/800-424-9300(CHEMTREC)

CAGE:0UJ55

=== Contractor Identification ===

Company Name:BATTERY OUTLET OF HAMPTON INC

Address:2815 GEORGE WASHINGTON HWY

Box:City:TABB

State:VA

ZIP:23602

Country:US

Phone:804-867-8280

CAGE:0FTM0

Company Name:NORTHERN AUTOMOTIVE AUTOWORKS DIV

Box:UNKNOW

CAGE:0PLX0

Company Name:OPTIMA BATTERIES INC

Address:17500 E 22ND AVENUE

Box:City:AURORA

State:CO

ZIP:80011

Country:US

Phone:303-448-8899 OR 800-292-4359

CAGE:0UJ55

Company Name:STANDARD BATTERIES INC

Ad

dress:5200 4TH AVE S.  
Box:81103  
City:SEATTLE  
State:WA  
ZIP:98108-2218  
Country:US  
CAGE:8F843

=====  
===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA 313) (CERCLA)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 32 - 42%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:SEE 1910.1025  
ACGIH TLV:0.05MG/M3, A3; 9596  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:LEADY LEAD MONOXIDE  
CAS:68411-78-9  
Fraction by Wt: 30 - 36%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:LEAD OXIDE, (RED LEAD OXIDE)/LEAD TETRAOXIDE  
CAS:1314-41-6  
RTECS #:OG5425000  
Fraction by Wt: 1 - 3%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:SEE 1910.1025  
ACGIH TLV:0.15 MG/M3

Ingred Name:SULFURIC ACID (SARA 302/313) (CERCLA)  
CAS:7664-93-9  
RTECS #:WS5600000  
Fraction by Wt: 17 - 25%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3/3 STEL; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:POLYPROPYLENE (CASE MATERIAL)  
CAS:9003-07-0  
RTECS #:TR5000000  
Fraction by Wt: 2

- 6%

Other REC Limits:NONE RECOMMENDED

Ingred Name:FIBERGLASS (FIBROUS GLASS)/SEPARATOR

CAS:65997-17-3

Fraction by Wt: 1 - 4%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 RESP DUST

ACGIH TLV:10 MG/M3 (