

3M GENERAL OFFICES -- CATALOG 6065 SPRAY-MOUNT ARTIST ADHESIVE

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 00-171-1535
MSDS Date: 09/15/1994
MSDS Num: BXXJP
Product ID: CATALOG 6065 SPRAY-MOUNT ARTIST ADHESIVE
MFN: 03
Responsible Party
Cage: 1BY21
Name: 3M GENERAL OFFICES
Address: 3M CENTER
City: ST PAUL MN
55144-1000
Info Phone Number: 612-733-1110
Emergency Phone Number: 612-733-1110
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 76381
Name: MINNESOTA MINING AND MFG CO, DBA 3M
Address: 3M CENTER BLDG 224-5S-04
City: SAINT PAUL MN 55144-1000
Phone: 866-556 5712 / 612-733-1110
Cage: 1BY21
Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV
Address: 3M CTR
City:
SAINT PAUL MN 55144-1000
Phone: 612-737-4114

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ADHESIVE
Specification Number: UNKNOWN
Unit of Issue: PT
UI Container Qty: 0
Type of Container: CAN,AEROSOL

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYES:MOD IRRIT: SIGNS/SYMPS CAN INCL REDNESS, SWELL, PAIN, TEARING &; HAZY VISION. SKIN:MILD IRRIT (AFTER PRLNG/RPTD CNTCT): SIGNS/SYMPS CAN INCL REDNESS, SWELL &; ITCH

. INHAL: INTENTIONAL CONC &;

INHAL MAY BE HARMFUL/FATAL. CNS DEPRESS: SIGNS/SYMPS CAN INCL HDCH, DIZZ, DROW, INCOORDINATION, SLOWED RXN (EFTS OF OVEREXP)

Explanation Of Carcinogenicity: NOT RELEVANT

Signs And Symptions Of Overexposure: HLTH HAZ:TIME, SLURRED SPEECH, GIDD &; UNCON. IRRIT (UPPER RESP): SIGNS/SYMPS CAN INCL SORENESS OF NOSE &; THROAT, COUGH &; SNEEZING. INGEST: NOT LIKELY ROUTE OF EXPOS. WHILE FOLLOWING EFT IS ASSOC W/ONE OR MORE INGREDIENTS OF PROD &; IS REQD TO BE

INCL ON MSDS BY OSHA, IT IS NOT EXPECTED EFT DURING FORESEEABLE USE OF (SUPDAT)

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: IMMEDIATELY FLUSH EYES W/LG AMTS OF WATER FOR AT LEAST 15 MIN. GET IMMEDIATE MED ATTN. SKIN: FLUSH SKIN W/LG AMTS OF WATER. IF IRRIT PERSISTS, GET MED ATTN. INHAL: REMOVE TO FRESH AIR. IF NOT BRTHG, GIVE ARTF RESP. IF BRTHG IS DFCLT, GET IMMEDIATE MED ATTN. INGEST: DO NOT INDUCE VOMITING. DRINK TWO GLASSES OF WATER. CALL MD.

==

=====
Handling and Disposal
=====

Spill Release Procedures: REFER TO OTHER SECTIONS OF MSDS FOR INFO REGARDING PHYSICAL &; HLTH HAZS, RESP PROT, VENT &; PERSONAL PROT EQUIP. CALL 612-733-1110 OR 612-733-6100 FOR 24-HR SPILL ASSISTANCE. VENT AREA. EXTING ALL IGNI T SOURCES. COVER W/ABSORB MATL. COLLECT

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCIN IN PE

MITTED HAZ WASTE INCIN IN PRESENCE OF
COMBUST MATL. FACILITY MUST BE CAPABLE OF HNDLG AEROSOL CANS. DISPOSE OF
EMPTY CANS IN SANITARY LANDFILL. DISP OF WASTE PROD IN FACILITY PERMITTED TO
ACCEPT CHEM WASTE. SINCE REGS VARY,

Handling And Storage Precautions: STORE AT TEMPERATURES BELOW 120F (49C). KEEP
OUT OF REACH OF CHILDREN.

Other Precautions: AEROSOL CNTNR CONTAINS FLAMMABLE GAS UNDER PRESS. KEEP AWAY
FROM HEAT, SPARKS, OPEN FLAME & OTHER SOURCES OF IGNIT. EXTREMELY FLAMM
L

IQ & VAP. DO NOT PIERCE OR BURN CONTAINER, EVEN AFTER USE. AVOID S
TATIC DISCHARGE.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: -50F, -46C

Upper Limits: FLAMM GAS

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP(FP
N) INCL BUNKER COAT & PANTS, BANDS AROUND
ARMS, WAIST & LEGS, FACE

MASK & PROT COVERING FOR EXPOS AREAS OF HEAD.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY
BUILD PRESSURE & EXPLODE. VAPORS MAY TRAVEL LONG DISTANCES ALONG
GROUND/FLOOR TO IGNITION SOURCE & FLASH BACK.

=====
Control Measures
=====

Respiratory Protection: AVOID PRLNG BRTHG OF VAPS, MISTS/SPRAY. SELECT ONE OF
FOLLOW

ING NIOSH/MSHA APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF
CONTAMINANTS & IN ACCORDANCE WITH OSHA REGULATIONS: HALF-MASK ORGANIC
VAPOR RESPIRATOR.

Ventilation: USE IN WELL-VENT AREA. PROVIDE SUFFICIENT VENT TO MAINTAIN
EMISSIONS BELOW RECOM EXPOS LIMS. IF EXHST VENT IS

Protective Gloves: POLYETHYLENE/ETHYLENE VINYL

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: EYEWASH FOUNTAIN & DELUGE SHOWER MEETING ANSI
DESIGN CRITERIA (FP N).

W

ork Hygienic Practices: DO NOT INGEST. AVOID SKIN & EYE CONTACT.
Supplemental Safety and Health: USERS OF "L" VERSION SHOULD CONSULT "LR"
VERSION FOR ADDNL INFO (FP N). BP: COMPRESSED GAS. VP: COMPRESSED GAS. EFTS
OF OVEREXP: PROD. INGEST MAY CAUSE IRRIT OF GI TISS: SIGNS/SYMPS CAN INCL
PAIN, VOMITING, ABDOM TENDERNESS, NAUS, BLOOD IN VOMITUS & IN FECES.

=====
Physical/Chemical Properties
=====

=====
B.P. Text: SUPDAT
Vapor Pres: SUPDAT
Vapor Density: 2.97
Spec Gravity: 0.640 (H*2O=1)
Evaporation Rate & Reference: 1.90 (H*2O=1)
Solubility in Water: NIL
Appearance and Odor: LIQUID IN AEROSOL, CLEAR; SWEET/FRUITY ODOR.
Percent Volatiles by Volume: 90
=====

Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: HEAT.
Materials To Avoid: NONE SPECIFIED BY MANU
FACTURER.
Hazardous Decomposition Products: CARBON MONOXIDE & CARBON DIOXIDE. TOXIC
VAPORS, GASES OR PARTICULATES.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT
=====

Toxicological Information
=====

Ecological Information
=====

=====
MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

HAZCOM Label
=====

=====

Product ID: CATALOG 6065 SPRAY-MOUNT ARTIST ADHESIVE

Cage: 1BY21

Company Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV

Street: 3M CTR

City: SAINT PAUL MN

Zipcode: 55144-1000

Health Emergency Phone: 612-733-1110

Label Required IND: Y

Date Of Label Review: 06/15/1995

Status Code: C

Label Date: 06/15/1995

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: M

oderate

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: FLAMMABLE. COMPRESSED GAS. ACUTE: EYES: MODERATE IRRITATION WITH REDNESS, SWELLING, PAIN, TEARING AND HAZY VISION. SKIN: MILD IRRITATION WITH REDNESS, SWELLING AND ITCHING. INHALATION: INTENTIONAL CONCENTRATION & INHALATION MAY BE HARMFUL OR FATAL. CENTRAL NERVOUS SYSTEM DEPRESSION WITH HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS AND UNCONSCIOUS NESS. UP

PER

RESPIRATORY IRRITATION WITH SORNESS OF NOSE AND THROAT, COUGHING AND SNEEZING. CHRONIC: NONE LISTED BY MANUFACTURER.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similari

ty to a corresponding Department
of Defense or other government situation.