

PIONEER/ECLIPSE CORP. -- ILLUMINATE (#206) -- 7930-01-380-8401

=====
Product Identification
=====

Product ID:ILLUMINATE (#206)

MSDS Date:03/15/1995

FSC:7930

NIIN:01-380-8401

MSDS Number: BYCDW

=== Responsible Party ===

Company Name:PIONEER/ECLIPSE CORP.

City:SPARTA

State:NC

ZIP:28675

Country:US

Info Phone Num:910-372-8080

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:JAMES B. MC CORM

ICK

CAGE:ONLMO

=== Contractor Identification ===

Company Name:CLEANING SOLUTIONS, INC.

Box:UNKNOW

CAGE:0NY12

Company Name:PIONEER ECLIPSE CORPORATION

Address:CHEMICAL DIVISION

Box:City:SPARTA

State:NC

ZIP:28675

Country:US

Phone:919-372-8080

CAGE:0NLM0

Company Name:PIONEER/ECLIPSE CORP.

Address:ECLIPSE RD. & HWY. 21 S.

Box:1089

City:SPARTA

State:NC

ZIP:28675

Phone:(919) 372-8080

CAGE:ONLMO

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHANOL, 2-(2-METHOXYETHO

XY) (SARA III) (LD50: 9.2 G/KG

MALE RAT, ORAL)

CAS:111-90-0

RTECS #:KK8750000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: SLIGHTLY IRRITATING. SKIN:

IRRITATING UPON REPEATED/PROLONGED CONTACT. INHALATION: VAPOR/MIST
CAN CAUSE HEADACHE, NAUSEA, IRRITATION OF
EYES, NOSE & LUNGS.

INGESTION: IRRITATION TO MOUTH, ESOPHAGUS & STOMACH.

Explanation of Carcinogenicity:NONCARCINOGENIC

Effects of Overexposure:PROLONGED/REPEATED CONTACT CAN CAUSE DRYING,
DEFATTING & DERMATITIS TO SKIN.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNT WATER AT LEAST 15 MINUTES. SEE
PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREAS W/SOAP
& WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: DRINK

SEVERAL

GLASSES WATER AND INDUCE VOMITING. SEEK MEDICAL ATTN.

=====
===== Fire Fighting Measures =====

Flash Point:NONCOMBUSTIBLE

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NA

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:MATERIALS CAN SPLATTER ABOVE 212F.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SM: ABSORB ON INERT MATERIAL (SAND/EARTH)

DISPOSE IN ACCORDANCE FED./STATE/LOCAL REG

. LG: KEEP SPECTATORS AWAY. FLOORS MAY BE SLIPPERY. DIKE/CONTAIN SPILL W/INERT MATERIAL (SAND/EARTH). TRANSFER LIQUID/SOLID DIKING MATERIAL TO SEPARATE CONTAINERS*

Neutralizing Agent: NK *FOR DISPOSAL. KEEP SPILLS/CLEANING RUN-OFF OUT OF SEWERS/OPEN BODIES WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORAGE TEMP. MAX. 140F, MIN. 34F.
Other Precautions: KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.
KEEP CONTAINER SEALED WHEN NOT IN USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE REQUIRED WHEN PERMISSIBLE AIRBORNE CONCENTRATIONS NOT EXCEEDED. IN EMERGENCY, USE APPROVED POSITIVE PRESSURE SCBA.
Ventilation: MECHANICAL LOCAL EXHAUST AT POINT OF CONTAMINATION RELEASE.
Eye Protection: CHEMICAL SPLASH GOGGLES
Other Protective Equipment: AS REQUIRED BY EMPLOYER CODE.
Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 212F, 100C
Melt/Freeze Pt: M.P/F.P Text: 32.0F, 0.0C
Vapor Pres: NOT EST.
Vapor Density: