

ALLIED ENTERPRISES, INC. -- FORMULA 1309 WATER-BASED STAINLESS STEEL CLEANER & POLISH -- 7930-01-398-1010

===== Product Identification =====

Product ID:FORMULA 1309 WATER-BASED STAINLESS STEEL CLEANER & POLISH

MSDS Date:04/28/1994

FSC:7930

NIIN:01-398-1010

MSDS Number: BYCXV

=== Responsible Party ===

Company Name:ALLIED ENTERPRISES, INC.

Address:814 W. 45TH STREET

Box:6159

City:NORFOLK

State:VA

ZI

P:23508-2008

Country:US

Info Phone Num:804-489-8282

Emergency Phone Num:800-535-5053

CAGE:58396

=== Contractor Identification ===

Company Name:ALLIED ENTERPRISES, INC.

Address:814 W. 45TH STREET

Box:6159

City:NORFOLK

State:VA

ZIP:23508-2008

Country:US

Phone:757-489-8282

CAGE:58396

===== Composition/Information on Ingredients =====

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 5-20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ing

red Name: BUTANE
CAS: 106-97-8
RTECS #: EJ4200000
Fraction by Wt: 5-20%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 800 PPM
ACGIH TLV: 800 PPM

Ingred Name: PETROLEUM DISTILLATES
CAS: 64742-48-9
Fraction by Wt: 1-5%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CA
USE TRANSIENT PAIN.

=====
First Aid Measures
=====

First Aid: QUICKLY FOLLOW DIRECTIONS BELOW: GET QUICK MEDICAL ATTN. IF
ANY ILL AFFECTS CONTINUE OR DEVELOP LATER. EYES: FLUSH W/PLENTY
WATER. REMOVE CONTACT LENSES. THEN HOLD EYES OPEN & CONTINUE
FLUSHING THOROUGHLY.

=====
Fire Fighting Measures
=====

Flash Point: 47.0F, 8.3C
Lower Limits: 1.0
Upper Limits: 7.0
Extinguishing Media: FOAM, DRY CHEMICAL, CO2.
Fire Fighting Procedures: KEEP CONTAINERS COOL. USE SHIELDING TO PROTECT
PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINERS.
Unusual Fire/Explosion Hazard: AT ELEVATED TEMPERATURES (OVER 120F)
CONTAINERS MAY VENT, RUPTURE OR BURST.

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE SOURCES OF FLAME, SPARK OR HEAT.
PROVIDE ADEQUATE VENTILATION. WIPE SPILLS THEN WASH W/CLEANER TO
REMOVE FINAL TRACES. FLOORS MAY BE SLIPPERY. USE CAUTION

TION TO AVOID
FALLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:CAUTION: CONTENTS UNDER PRESSURE. KEEP
OUT OF REACH OF CHILDREN. DO NOT STORE WHERE TEMPERATURES MAY
EXCEED 120F.

Other Precautions:READ ENTIRE LABEL BEFORE USING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED.

Ventilation:ADEQUATE MECHANICAL (GENERAL)

Protective Gloves:NONE REQUIRED

Eye Protection:SAF

ETY GLASSES

Other Protective Equipment:NONE

Work Hygienic Practices:ALWAYS FOLLOW SAFE WORK PRACTICES.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:18

Vapor Density: