

MINNESOTA MINING & MFG CO ELECTRICAL PRODUCTS,(3M) -- 00-54007-14853-1 SCOTCHKOTE
BRAND ELECTRICAL COATING -- 5970-00-962-3335

===== Product Identification =====

Product ID:00-54007-14853-1 SCOTCHKOTE BRAND ELECTRICAL COATING

MSDS Date:02/22/1995

FSC:5970

NIIN:00-962-3335

MSDS Number: BYFLM

=== Responsible Party ===

Company Name:MINNESOTA MINING & MFG CO ELECTRICAL PRODUCTS,(3M)

Address:3M AUSTIN

CTR

Box:2963

City:AUSTIN

State:TX

ZIP:78769-2963

Country:US

Info Phone Num:512-984-5670

Emergency Phone Num:512-984-5670

CAGE:75037

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO ELECTRICAL PRODUCTS DIV

Address:3M AUSTIN CTR

Box:City:AUSTIN

State:TX

ZIP:78769-2963

Country:US

Phone:512-984-1800

CAGE:75037

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA 313) (CERCLA)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 40-45%

O

ther REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:750PPM/1000STEL;9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 12-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 12-15%
Other REC Limits:NONE RECOMMENDE
D
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACRYLONITRILE BUTADIENE POLYMER
CAS:9003-18-3
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PHENOL FORMALDEHYDE RESIN
Fraction by Wt: 3-7%
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLYCEROL ESTERS OF ROSIN ACIDS (MFR GAVE CAS# OF 8050-31-3
WHICH IS INVALID PER BASE 10 CHECK).
Fraction by Wt: 3-7%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SALICYLIC ACID
CA

S:69-72-7
RTECS #:VO0525000
Fraction by Wt: 1-2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC OXIDE (SARA 313) (CERCLA)
CAS:1314-13-2
RTECS #:ZH4810000
Fraction by Wt: 1-2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Name:ANTIOXIDANT (BENZENAMINE, N-PHENYL-,)
CAS:68411-46-1
Fraction by Wt: 0.1-1.0%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Sk
in:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE CNS DERESSION IF
INHALED, ABSORBED THROUGH SKIN OR INGESTED. MAY CAUSE RESPIRATORY
IRRITATION IF INHALED. CONTACT MAY CAUSE IRRITATION OF SKIN & EYES.
INGESTION MAY CAUSE GI TRACT IRR ITATION. CHRONIC: PROLONGED OR
RPEATED EXPOSURE MAY CAUSE KIDNEY & LIVER EFEFCTS, CARDICA
SENSITIZATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF
0.1%

OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:INHALED/SKIN ABSORPTION/INGESTED-DIZZINESS,
HEADACHE, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED
SPEECH. INHALED-SORE THROAT/NOSE, COUGHING, SNEEZING. SKIN-REDNESS,
ITCHING, SWELLING. E YES-REDNESS, SWELLING, PAIN, TEARING, HAZY
VISION. INGESTED- PAIN, VOMITING, ABDOMINAL TENDERNESS, NAUSEA,
BLOOD IN VOMI

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACT
URER.

===== First Aid Measures =====

First Aid:IN ALL CASES GET IMMEDIATE MEDICAL ATTENTION.
EYES-IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. SKIN-REMOVE
CONTAMINATED CLOTHES. FLUSH WITH LOTS OF WATER. INHALED-REMOVE TO
FRESH AIR. ADMINISTER OXYG EN OR ARTIFICIAL RESPIRATION AS
NEEDED.INGESTED-DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE 1-2
GLASSES WATER.

===== Fire Fighting Measures =====

Flash Point

Method:CC

Flash Point:0F,-18C

Lower Limits:2.15

Upper Limits:13.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:VAPOR MAY TRAVEL LONG DISTANCE ALONG THE GROUND OR FLOOR TO AN IGNITION SOURCE AND FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. E

LIMINATE ALL SOURCES OF

IGNITION. CONTAIN SPILL. COVER WITH INORGANIC ABSORBENT MATERIAL. COLLECT SPILLED MATERIAL. CLEAN UP RESIDUE. PLACE IN AN APPROVED METAL CONTAINER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED PLACE AWAY FROM SOURCES OF IGNITION AND INCOMPATIBLE MATERIALS. CONTENTS MAY BE UNDER PRESSURE.

Other Precautions:KE

EP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM

CHILDREN. GROUND CONTAINERS SECURELY WHEN TRANSFERRING CONTENTS. WEAR LOW STATIC OR PROPERLY GROUNDING SHOES. NO SMOKING WHEN HANDLING THIS MATERIAL. VAPOR S MAY IGNITE EXPLOSIVELY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR OR AN AIR- SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED . USE IN ACCORDANCE

WITH 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE EXPLOSION-PROOF MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:BUTYL RUBBER.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:APRON, COVERALLS. DLA-HMIS: EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CL

OTHERS BEFORE REUSE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:134F,57C
Vapor Pres:229
Vapor Density:2.00
Spec Gravity:0.88
Viscosity:325 CPS
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWN LIQUID; SOLVENT ODOR.
Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE,
OXIDES OF NITROGEN, HYDROCARBONS, AMINE COMPOUNDS.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS. EPA/RCRA HAZARDOUS WASTE NUMBER
D001 (IGNITABLE) MAY APPLY TO UNUSED/UNCONTAMINATED PRODUCT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.