

DEXTER ADHESIVES & STRUCTURAL -- AS9216000 EA 9320NA SYSTEM PART A

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 01-043-5423
MSDS Date: 06/01/1995
MSDS Num: BYNZT
Product ID: AS9216000 EA 9320NA SYSTEM PART A
MFN: 05
Responsible Party
Cage: 33564
Name: DEXTER ADHESIVES & STRUCTURAL MATERIALS
Address: 2850 WILL
OW PASS RD
Box: 312
City: PITTSBURGH CA 94565-3299
Info Phone Number: 510-458-8000 EXT-262/EXT-263
Emergency Phone Number: 510-458-8000 EXT-262/EXT-263
Proprietary Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 33564
Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address: 2850 WILLOW PASS ROAD
Box: 312
City: BAY POINT CA 94565-3299

=====
Contractor Summary
=====

Cage: 33564
Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address: 2850 WILLOW PASS ROAD
Box: 312
City: BAY POINT CA 94565-3299
Phone: 202-483-7616

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ADHESIVE
Unit of Issue: KT
UI Container Qty: 0
=====

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data
=====

LD50 LC50 Mixture: ORAL LD50(RAT): 11,400 MG/KG (SEE SUPP)

Route Of Entry Inds - Inhalation: NO

Skin: NO

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: MAY CA

USE SKIN & EYE IRRITATION. REPEATED/PROLONGED

SKIN CONTACT W/UNCURED ADHESIVE MAY RESULT IN ALLERGIC SENSITIZATION.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: IRRITATION & RASH.

Medical Cond Aggravated By Exposure: SKIN SENSITIZATION.

First Aid: EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH THOROUGHLY W/SOAP &

WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK PLENTY OF WATER.

OBTAIN MEDICAL ATTENTION IN ALL CASES.
=====

Handling and Disposal
=====

Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES & SAFETY GLASSES. PICK UP/SHOVEL INTO DOT APPROVED WASTE CONTAINERS.

Waste Disposal Methods: INCINERATION IN AN EPA-APPROVED WASTE INCINCERATOR IS A PREFERRED DISPOSAL PRACTICE. DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Handling And Storage Precautions: REFRIGERATED STORAGE IS RECOMMENDED TO MAINTAIN PRODUCT

QUALITY. MAY BE STORED AT ROOM TEMP OF 77F FOR UP TO 12 MONTHS.

Other Precautions: FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WHICH MAY CAUSE AN EXOTHERM. EXOTHERM HAS POTENTIAL FOR RELEASE OF TOXIC GASES. AVOID CONTACT.
=====

Fire and Explosion Hazard Information
=====

Extinguishing Media: DRY CHEMICAL, HALON FIRE EXTINGUISHER, WATER SPRAY, FOAM, FOG.

Fire Fighting

Procedures: WEAR A SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING/TURN-OUT GEAR. CARTRIDGE RESPIRATORS DON'T PROVIDE ADEQUATE PROTECTION/EXOTHERM MITIGATION.

Unusual Fire/Explosion Hazard: MAY LIBERATE LARGE QUANTITIES OF DENSE FOUL-SMELLING SMOKE WHICH MAY CONTAIN UNIDENTIFIED TOXIC GASES.

=====
Control Measures
=====

Respiratory Protection: UNNECESSARY W/ADEQUATE EXHAUST VENTILATION.

Ventilation: LOCAL EXHAUST AT POINT OF USE.

Protective Gloves: BUTYL/NITRILE RUBBER/POLYVINYL CHLORIDE

Eye Protection: SAFETY GLASSES

Other Protective Equipment: EYEWASH & SAFETY SHOWER

Work Hygienic Practices: WASH AFTER HANDLING.

Supplemental Safety and Health: ORAL LD50 INFORMATION IS FOR BISPHENOL A/EPICHLOROXYDRIN EPOXY RESIN. ACCORDING TO DEXTER AEROSPACE, THE SILICA CAS NUMBER 112945-52-5 HAS BEEN GIVE TO DEXTER BY THE SUPPLIER, BUT THE MATERIAL IS TSCA LISTED AS 763

1-86-9.

=====
Physical/Chemical Properties
=====

Vapor Pres: 0

Vapor Density: >1

Spec Gravity: >1

VOC Grams/Liter: 10

Solubility in Water: NEGLIGIBLE

Appearance and Odor: OPAGUE-AMBER COLORED PASTE.

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: MIXING RESIN & CURING AGENT IN BATCHES >1/2 LB

TOTAL, HEATING MIXED ADHESIVE >75F UNLESS CURING SURFACES TO BE BONDED.

Materials To Avoid: STRONG OXIDIZING AGENTS, STRONG LEWIS/MINERAL ACIDS.

Hazardous Decomposition Products: CO, NITROGEN OXIDES, ALDEHYDES, ACIDS & UNDETERMINED ORGANICS.

Hazardous Polymerization Indicator: YES

Conditions To Avoid Polymerization: MIXING RESIN & CURING AGENT IN BATCHES >1/2

LB TOTAL, HEATING MIXED ADHESIVE >75F UNLESS CURING SURFACES TO BE BONDED.

=====

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

Other Information: VOLATILE ORGANIC CONTENT: < 10 G/L.
=====

=====
HAZCOM Label
=====

Product ID: AS9216000 EA 9320NA SYSTEM PART A

Cage: 33564

Company Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Street: 2850 WILLOW PASS ROAD

P

O Box: 312

City: BAY POINT CA

Zipcode: 94565-3299

Health Emergency Phone: 510-458-8000 EXT-262/EXT-263

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: MAY CAUSE SKIN & EYE IRRITATION. REPEATED/PROLONGED
SKIN CONTACT W/UNCURED ADHESIVE MAY RESULT IN ALLERGIC SENSITIZATION.

IRRITATION & RASH.
=====

Disclaimer (provided with this i

nformation by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any

person

utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.