

METCO INC, SUB OF THE PERKIN-ELMER CORP -- 210NS-1/12.5 LB -- 3439-01-391-8637

=====  
Product Identification  
=====

Product ID:210NS-1/12.5 LB

MSDS Date:06/24/1992

FSC:3439

NIIN:01-391-8637

MSDS Number: BYRXS

=== Responsible Party ===

Company Name:METCO INC, SUB OF THE PERKIN-ELMER CORP

Address:1101 PROSPECT AVENUE

Box:1006

City:WESTBURY

State:NY

ZIP:11590-0201

Country:US

Info Phone Num:516-334-1300

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:39918

=== Contractor Identification ===

Company Name:METCO INC, SUB OF THE PERKIN-ELMER CORP

Address:1101 PROSPECT AVENUE

Box:City:WESTBURY

State:NY

ZIP:11590-2724

Country:US

Phone:516-334-1300

CAGE:39918

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ZIRCONIUM

CAS:7440-67-7

RTECS #:ZH7070000

Fraction by Wt: 76%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9495

Ingred Name:MAGNES

IUM OXIDE

CAS:1309-48-4

RTECS #:OM3850000

Fraction by Wt: 22%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 PARTICULATE

ACGIH TLV:10 MG/M3; FUME; 9495

Ingred Name:HAFNIUM OXIDE

CAS:12055-23-1

Fraction by Wt: 1.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.5 MG/M3 (HF)

ACGIH TLV:0.5 MG/M3 (HF)

Ingred Name:CALCIUM OXIDE

CAS:1305-78-8

RTECS #:EW3100000

Fraction by Wt: 0.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:2 MG/M3; 9495

=====  
Hazards Identifica  
tion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION MAY CAUSE "METAL FUMES  
FEVER", RESPIRATORY IRRITATION. SKIN AND EYE CONTACT MAY CAUSE  
IRRITATION; DERMATITIS. INGESTION-NO DATA GIVEN. TARGET ORGANS:  
RESPIRATORY SYSTEM, SKIN, EYES.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%  
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTE  
D CARCINOGEN.

Effects of Overexposure:INHALED-IRRITATION. SKIN-IRRITATION.  
EYES-IRRITATION.

Medical Cond Aggravated by Exposure:CONSULT A PHYSICIAN.

=====  
First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER. CONSULT A PHYSICIAN IF IRRITATION  
PERSISTS. SKIN-WASH WITH SOAP & WATER. INHALED-REMOVE TO FRESH AIR.  
SEE PHYSICIAN IF IRRITATION OR RESPIRATORY DISTRESS PERSISTS.  
INGESTED-CONS ULT A PHYSICIAN.

=====  
Fire Fightin

g Measures =====

Flash Point:NONE

Extinguishing Media:USE CLASS D FIRE EXTINGUISHER.

Fire Fighting Procedures:TREAT AS METALLIC FIRE.

Unusual Fire/Explosion Hazard:FINE METAL DUSTS ARE FLAMMABLE AND MAY EXPLODE WHEN EXPOSED TO HEAT, FLAME, STRONG OXIDIZERS. HEATED ZIRCONIUM MAY REACT WITH WATER OR STEAM TO PRODUCE HYDROGEN

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM LOOSE POWDER ONLY WITH VACUUM EQUIPPED WITH HEPA FILTER. VACUUMS APPROPRIATE FOR METALLIC DUSTS SHOULD BE USED. WIPE AREA CLEAN. DO NOT USE WATER FOR CLEAN-UP OPERATIONS. DO NOT SWEEP. AVOID GENERATING AIRBORNE DUST.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS. STORE PRODUCT CONTAINERS IN A WELL-VENTILATED, DRY, CLEAN, COOL AREA. STORE TO MINIMIZE SPILLAGE & BREAKAGE.

Other

Precautions:AVOID INGESTION, INHALATION AND EXCESSIVE SKIN CONTACT. AVOID CONTACT OF POWDER WITH WATER AND OXIDIZERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A RESPIRATOR APPROVED BY NIOSH W/FILTER CARTRIDGES APPROVED FOR DUST/FUMES/MISTS SHOULD BE WORN AT ALL TIMES DURING THERMAL SPRAY PROCESS TO PROTECT OPERATOR FROM EXPOSURE TO DUST/FUMES.

Ventilation:PRODUCT SHOULD BE USED WITH APPROPRIATE LOCAL EXHAUST VENTILATION PROVIDED.

Protective Gloves:ALUMINIZED-PLASMA SPRAY;RUBB-OTHER.

Eye Protection:WELDERS GOGGLES W/LENSES.

Other Protective Equipment:WASH FACILITIES ARE RECOMMENDED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:3500F,1927C

Spec Gravity:1.8-2.1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:POWDER, NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, ACIDS, SULFUR.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:OZONE & NITRIC OXIDE ARE FORM BY  
PLASMA FLAME (SIMILAR TO WELDING FUMES). THIS ACTION IS INDEPENDENT  
OF METAL POWDER.

===== Disposal Considerations =====

Waste Disposal Methods:EMPTY PRODU

CT CONTAINERS, PRODUCT WASTE AND

CLEANING MEDIA SHOULD BE STORED AND DISPOSED OF ACCORDING TO LOCAL,  
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should

seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.