

MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV. -- EAL ARTIC 68 -- 9150-01-410-8972

=====
Product Identification
=====

Product ID:EAL ARTIC 68

MSDS Date:01/25/1995

FSC:9150

NIIN:01-410-8972

MSDS Number: BYRYC

=== Responsible Party ===

Company Name:MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV.

Address:RT 27 AND VINEYARD RD.

Box:250

City:EDISON

State:NJ

ZIP:08818-0250

Country:US

Info Phone Num:800-662-4525

Emergency Phone Num:609-737-4411 OR 800-424-9300

Preparer's Name:PRODUCTS & TECHNOLOGY DEP

CAGE:77988

=== Contractor Identification ===

Company Name:MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV.

Address:RT 27 AND VINEYARD RD.

Box:250

City:EDISON

State:NJ

ZIP:08818-0250

Country:US

Phone:609-737-4411 OR 800-424-9300

CAGE:77988

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

=====
Composition/Information on I

Ingredients =====

Ingredient Name: MANUFACTURER LISTS NOTHING UNDER "INGREDIENTS" IMPLYING THAT THERE ARE NO HAZARDOUS INGREDIENTS PER HAZ COM STANDARD.

Fraction by Wt: 100%

Other REC Limits: NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture: ORAL LD50 (RAT) IS >2000 MG/KG

Routes of Entry: Inhalation: NO Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: NO SIGNIFICANT EFFECTS EXPECTED.

Explanation of Carcinogenicity: NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure: NONE SPECIFIED BY MANUFACTURER.

Medical Condition Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid: EYES-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION OCCURS. SKIN-WASH WITH MILD SOAP & WATER.

INHALED-REMOVE TO FRESH AIR.

INHALED-ADMINISTER OXYGEN OR ARTIFICIAL

RESPIRATION AS NEEDED. GET MEDICAL ATTENTION IF ANY SYMPTOMS

OCCUR. INGESTED-IF UNCOMFORTABLE, SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method: PMCC

Flash Point: 450F, 232C

Extinguishing Media: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion

Hazard: NONE.

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB ON FIRE RETARDANT MATERIAL. SHOVEL UP AND PLACE IN A CONTAINER FOR LATER DISPOSAL. PREVENT SPILLS FROM ENTERING STORM DRAINS OR DRAINS AND CONTACT WITH SOIL. IF ENTERS WATERWAYS/DRAINS, NOTIFY NATIONAL RESPONSE CENTER AT 800-424-8802.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling

and Storage Precautions:DO NOT STORE IN OPEN OR UNLABELED CONTAINERS. STORE AWAY FROM STRONG OXIDIZING AGENTS OR COMBUSTIBLE MATERIAL.

Other Precautions:THIS MATERIAL IS NOT INTENDED FOR USE IN AIR COMPRESSORS FOR BREATHING APPLICATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE IN A WELL VENTILATED AREA.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Ot

her Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:USE GOOD PERSONAL HYGIENE PRACTICES.

Supplemental Safety and Health

MSDS PRESENTED BY CAGE 0T5C6 FOR CONTRACT NUMBER SP0451-96-MP656.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Melt/Freeze Pt:M.P/F.P Text:-38F,-39C

Vapor Pres: