View NSN Online: https://aerobasegroup.de/nsn/6850-01-416-6363

Product ID:SAFETY STRIP 1000 MSDS Date:02/23/1988 FSC:6850 NIIN:01-416-6363 MSDS Number: BYRYJ === Responsible Party === Company Name: BRULIN AND CO INC Address: 2920 DR ANDREW J BROWN AVE Box:270 **City:INDIANAPOLIS** State:IN ZIP:46205-0270 Country:US Info Phone Num:317-923-3211 OR 800-428-7149 **Emergency Phon** e Num:317-923-3211 CAGE:94058 === Contractor Identification === Company Name: BRULIN AND CO INC Address:2920 DR ANDREW J BROWN AVE Box:270 **City:INDIANAPOLIS** State:IN ZIP:46205-0270 Country:US Phone:317-923-3211 CAGE:94058

Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 15% Other REC Limits:NONE RECOMMENDED OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9495

Ingred Name: ETHANOL, 2-BUTOXY-; (ETHYLENE GLYCOL

MONOBUTYL ETHER). VP: 0.6 @ 68F. VAP DENS: 4.0 CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 10-30% OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: (ACUTE & CHRONIC): DIRECT CNTCT MAY CAUSE MODERATE EYE IRRIT. EXCESS INHAL MAY CAUSE RESP IRRIT. MODERATELY TOX IF INGESTED. PRLN **GD/RPTD SKIN CONTACT MAY CAUSE IRRIT. 2-BUTOXYETHANOL IS READILY ABSORBE D THRU SKIN. CHRONIC** EXPOSURE TO 2-BUTYOXYETHANOL MAY CAUSE BLOOD EFFECTS & INJURY TO LIVER & KIDNEY.(EFTS OF OVEREXP) Explanation of Carcinogenicity: THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP, IARC OR OSHA. Effects of Overexposure: HLTH HAZ: CHRONIC SKIN EXPOS MAY CAUSE DERM. ANIMAL STUDIES HAVE CLEARLY DEMONSTRATED DOSE-RELATED ADVERSE EFTS ON THE CNS, THE HEMATOPOI ETIC TISSUE, THE BLOOD, THE KIDNEYS, & THE LIVER ASSOC W/ THE AD MINISTRATION OF ETHYLENE GLYCOL MONOBUTYL ETHER. (EXTRACTED FROM DHHS (NIOSH) PUB NO. 90-118). (SUPP DATA) Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:INHAL:REMOVE TO FRESH AIR. ADMINISTER O2 IF BRTHG IS DIFFICULT. GET MED ATTN. EYE: FLUSH W/LRG AMTS OF WATER FOR @ LST 15 MIN LIFTING UPPER & LOWER LIDS OCCASNLY. GET MED ATTN. SKIN: WASH

W/MILD SOAP & WATER. REMOVE CONTAM CLTHG & LAUNDER BEFORE REUSE. INGEST: GIVE TWO GLASSES OF WATER & INDUCE VOMIT IMMED BY STICKING FINGER DOWN THROAT. CALL A MD. NEVER GIVE ANYTHING BY MOUTH TO UNCON PERSON.

Flash Point Method:PMCC Flash Point:>200F,>93C Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICALS. Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUI

| PMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER  |
|--|
| FOG.<br>Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR<br>NEAR DRUM, EVEN EMPTY.   |
| ======================================   |
| Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE THE<br>AREA WELL. ABSORB ON SOLID ABSORBENT AND SHOVEL INTO CNTNRS. FLUSH<br>RESIDUES WITH WATER.<br>Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.   |
| ======================================   |
| Handling and Storage Precautions:STORE BETWEEN 40 AND 120F.<br>Other Precautions:NONE SPECIFIED BY MANUFACTURER.   |
| ======================================   |
| Respiratory Protection:IF TLV IS EXCEEDED, USE A NIOSH/MSHA APPROVED<br>RESP. CONTACT YOUR LOCAL SAFETY EQUIPMENT SUPPLIER FOR<br>RECOMMENDATIONS.<br>Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL<br>EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.<br>Protective Gloves:BUTYL RUBBER<br>Even Prot |
| Eye Prot<br>ection:CHEMICAL WORKERS GOGGLES .<br>Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.<br>Work Hygienic Practices:AVOID BREATHING SPRAY MISTS. WASH HANDS AFTER<br>HANDLING.  |
| Supplemental Safety and Health<br>COPIED FROM 8010-00-N01-6111,AS DIRECTED BY T.MCCARLEY.EFTS OF OVEREXP:<br>SIGNS & SYMPS: EYE CONTACT MAY CAUSE REDNESS, TEARING. SKIN<br>IRRITATION MAY BE SEEN AS REDNESS. EXCESSIVE INHALATION MAY CAUSE<br>HE ADACHE, NAUSEA, DIZZINESS. INGESTION MAYCAUSE GASTROINTESTINAL<br>IRRITA |
| TION, NAUSEA, VOMITING, DIARRHEA.  |
| ======================================   |
|  |

Boiling Pt:>100.C, 212.F Melt/Freeze Pt: