

EASTMAN KODAK COMPANY -- 102 3209 DURAFLO RT DEVELOPER (WORKING SOLUTION) --  
6750-01-319-6473

===== Product Identification =====

Product ID:102 3209 DURAFLO RT DEVELOPER (WORKING SOLUTION)

MSDS Date:11/15/1995

FSC:6750

NIIN:01-319-6473

MSDS Number: BYSFB

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num

:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information

on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 80 - 85%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA)  
CAS:7631-90-5  
RTECS #:VZ2000000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9495  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:POTASSIUM SULFITE  
CAS:10117-38-1  
RTECS #:WT3530000  
Fraction by Wt: 1 - 5%  
Othe  
r REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE  
CAS:7757-83-7  
RTECS #:WE2150000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM CARBONATE  
CAS:584-08-7  
RTECS #:TS7750000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE BIS(SODIUM BISULFITE)  
CAS:7420-89-5  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CARBONATE  
CAS:497-19-8  
RTECS #:VZ4050000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOM

MENDED

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)  
CAS:1310-58-3  
RTECS #:TT2100000  
Fraction by Wt: 100C  
Vapor Pres:18 @ 68F  
Vapor Density:0.6  
Spec Gravity:1.115  
pH:9.4  
Solubility in Water:COMPLETE  
Appearance and Odor:COLORLESS LIQUID, ODORLESS  
Percent Volatiles by Volume:80- 85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXID  
E,  
SULFUR DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT  
TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT  
OF WATER IF PERMITTED.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warran  
ts this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.