

GRIGGS PAINT -- TPD-24607,#24516 NON-FLAMING -- 8010-01-344-5098

=====
Product Identification
=====

Product ID:TPD-24607,#24516 NON-FLAMING

MSDS Date:01/01/1994

FSC:8010

NIIN:01-344-5098

MSDS Number: BYSFD

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S. 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:602-243-3293

Preparer's

Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====
Composition/Information on Ingredients
=====

Ingred Name:AROMATIC PETROLEUM DISTILLATES

CAS:64742-95-6

RTECS #:WF3400000

Fraction by Wt: 5%

Other REC Limits:ABOVE

VALUES MFR'S
OSHA PEL:100 PPM
ACGIH TLV:300 PPM

Ingred Name:ALIPHATIC HYDROCARBONS (STODDARD TYPE) (SARA 313)CERCLA)
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 4%
Other REC Limits:100 PPM 9MFR)
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9495

Ingred Name:VOLATILE ORGANIC CONTENT, V.O.C.= 342 G/L (2.85 LB/GL)
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry:

Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: IRRITATION. SKIN:

PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION,
DERMATITIS. INHALATION: MAY CAUSE CNS DEPRESSION, DROWSINESS,
DIZZINESS, FATIGUE, COMA. INGESTION: MAY CAUSE GAS TROINTESTINAL
DISTURBANCES. CHRONIC:DERMATITIS, CNS DEPRESSION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATIO
N, DERMATITIS.

INHALATION: RESPIRATORY SYSTEM IRRITATION, CNS DEPRESSION, NAUSEA,
VOMITING, LUNG CHANGES, COUGH. INGESTION: GI TRACT DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING
DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN, CENTRAL NERVOUS
SYSTEM, LIVER, AND KIDNEYS.

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL
ATTENTION. SKIN: REMOVE CONTAMINATED C

LOTHING. WASH AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. SUPPORT BREATHING. IF ADVERSE SYMPTOMS DEVELOP, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:100F,38C
Lower Limits:1.0%
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE USED TO COOL CONTAINERS. IF WATER USED, FOG NOZZLES PREFERRED.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT ABSORBENT MATERIAL. FLUSH AREA WITH WATER. VENTILATE AREA UNTIL AREA HAS BEEN DECLARED SAFE.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING VAPORS AND SPRAY MISTS.
Other Precautions:AVOID EYE AND SKIN CONTACT. MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANKS, OR PIPES WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW TLV/PEL, USE MSHA/NIOSH APPROVED UNITS. IF EXPOSURE IS WITHIN OSHA PROTECTION FACTOR, AIR PURIFYING OVER/FILTER UNITS ARE OK FOR USE.
Ventilation:PROVIDE ADEQUATE LOCAL AND MECHANICAL EXHAUST VENTILATION.
Protective Gloves:RUBBER GLOVES RECOMMENDED.
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

OGGLES

Other Protective Equipment:PROVIDE EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:320 TO 334F

Vapor Density:>1

Spec Gravity:1.7

Evaporation Rate & Reference:SLOWER THAN ETHER.

Solubility in Water:ESSENTIALLY NIL

Appearance and Odor:

VISCOUS LIQUID. TYPICAL PAINT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:FLAMES, SPARKS, SMOKING, AND HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE AS AN IGNITABLE HAZARDOUS WASTE

IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. PRODUCT IS
US EPA DEFINED IGNITABLE HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.