

CONVOY OIL CORP -- LUBRICANT,MOLYBDENUM DISULFIDE,SILICONE -- 9150-00-543-7220

=====
Product Identification
=====

Product ID:LUBRICANT,MOLYBDENUM DISULFIDE,SILICONE

MSDS Date:04/21/1992

FSC:9150

NIIN:00-543-7220

MSDS Number: BYTKQ

=== Responsible Party ===

Company Name:CONVOY OIL CORP

Address:1412 N FRONT STREET

City:PHILADELPHIA

State:PA

ZIP:19122-3902

Country:US

Info Phone Num:215-739-5281

Emer

gency Phone Num:215-739-5281

CAGE:6A438

=== Contractor Identification ===

Company Name:CONVOY OIL CORP

Address:1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

=====
Composition/Information on Ingredients
=====

Ingred Name:PHENYLMETHYLSILOXANE; (SILICONE)

CAS:63148-52-7

Fraction by Wt: 40-70%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 30-60%

Othe

r REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG MO/M3

ACGIH TLV:5 MG MO/M3

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>400F,>204C ING1

Extinguishing Media:USE WATER FOG,FOAM,DRY CHEM OR CO2.DO NOT USE DIRECT STREAM OF WATER.PROD WILL FLOAT & CAN BE REIGN ON SURFACE OF WATER.

Fire Fighting Procedures:MATL WILL NOT BURN UNLESS PREHEATED.DO NOT ENTER CONFINED FIRE SPACE W/O FULL BUNKER GEAR(HELMET W/FCSHIELD,COATS,GLOVES,RUB

B BOOTS)INCLUDES +PRESS NIOSH(SUPPL)

Unusual Fire/Explosion Hazard:BASED ON INGRED 2 @TEMPS EXCEEDING 750F SULFUR OXIDES & HYDROGEN SULFIDE BOTH OF WHICH ARE TOXIC MAY BE RELEASED UPON COMBUST.DELAYED LUNG DMG(PULM EDEMA)(SUPP)

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F,>149C

Melt/Freeze Pt:M.P/F.P Text:NOT AVAILAB

Vapor Pres: