

TERRA INTERNATIONAL, INC. -- METHANOL -- 6810-00-275-6010

===== Product Identification =====

Product ID:METHANOL
MSDS Date:12/01/1994
FSC:6810
NIIN:00-275-6010
MSDS Number: BYVVK
=== Responsible Party ===
Company Name:TERRA INTERNATIONAL, INC.
Address:WOODWARD COMPLEX, 1000 TERRA DRIVE
City:WOODWARD
State:OK
ZIP:73801
Country:US
Info Phone Num:405-256-8651
Emergency Phone Num:405-256-8651
Chemtec
Ind/Phone:(800)424-9300
CAGE:TERRA
=== Contractor Identification ===
Company Name:HOC INDUSTRIES, INC
Address:3511 N. OHIO
Box:2609
City:WICHITA
State:KS
ZIP:67219
Country:US
Phone:316-838-4663
Contract Num:SP0450-99-M-C702
CAGE:0A9L8
Company Name:TERRA INTERNATIONAL, INC
Address:600 FORTH STREET
Box:6000
City:SIOUX CITY
State:IA
ZIP:51102-6000
Country:US
Phone:800-831-1002 EXT321
CAGE:TERRA

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ALCOHOL (METHA

NOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

= Wt:100.

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 200 PPM

ACGIH TLV:S,200PPM/250STEL; 95

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORL RAT) IS 5628 MG/KG (RTECS).

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS: LIVER. ACUTE: HUMAN

HEALTH EFFECTS OF OVEREXPOSURE BY INHALATION, INGESTION, OR SKIN OR EYE CONTACT MAY INCLUDE NONSPECIFIC DISCOMFORT; AND TEMPORARY NERVOUS SYSTEM DEPRESSION WITH ANESTHETIC EFFECTS. HIGHER EXPOSURES MAY LEAD TO ABNORMAL LIVER FUNCTION. INGESTION OF AS LITTLE AS 60 ML MAY CAUSE BLINDNESS OR FATALITY. SKIN PERMEATION CAN OCCUR IN AMOUNTS CAPABLE OF PRODUCING SYSTEMS TOXICITY.

Effects of Overexposure:HUMAN HEALTH EFFECTS OF OVEREXPOSURE BY INHALATION, INGESTION, OR SKIN OR EYE CONTACT MAY INCLUDE

NONSPECIFIC DISCOMFORT SUCH AS NAUSEA, OR WEAKNESS; AND TEMPORARY NERVOUS SYSTEM DEPRESSION WITH ANESTHETIC EFFECTS SUCH AS DIZZINESS, HEADACHE, CONFUSION, INCOORDINATION, AND LOSS OF CONSCIOUSNESS; OR BLINDNESS.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING DISEASES OF THE RETINA OR LIVER MAY HAVE INCREASED SUSCEPTIBILITY TO TOXICITY OF EXCESSIVE EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SEE PHYSICIAN. SKIN:WASH AFFECTED AREA WITH SOAP & WATER. IF IRRITATION PERSISTS, SEE DOCTOR. INHALED:REMOVE TO FRESH AIR. PROVIDE C PR/OXYGEN IF NEEDED. OBTAIN EMERGENCY MEDICAL HELP. ORAL:IF CONSCIOUS, IMMEDIATELY INDUCE VOMITING BY DRINKING WATER & PRESSING FINGER DOWN THROAT. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY.

=====
===== Fire Fighting Measures =====

====

Flash Point Method:TCC

Flash Point:=11.1C, 52.F

Autoignition Temp:=385.C, 725.F

Lower Limits:6.0%

Upper Limits:36%

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CO2. "ALCOHOL" FOAM.

Fire Fighting Procedures:EVACUATE AFFECTED AREA. STAY UPWIND AND AVOID SMOKE AND FUMES. USE WATER TO COOL CONTAINERS. IF SMOKE AND FUMES CANNOT BE AVOIDED, WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID. FLAME INVISIBLE IN DAYLIGHT. METHANOL-WATER MIXTURE

S WILL BURN UNLESS VERY DILUTE,

MIXTURES WITH 25% OR MORE METHANOL ARE OSHA CLASS I FLAMMABLE LIQUIDS. FOLLOW APPROPRIATE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) CODES.

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PERSONAL PROTECTION EQUIPMENT DURING CLEAN UP. DIKE LARGE SPILLS. FLUSH SPILL AREA WITH PLENTY OF WATER. DO NOT FLUSH TO SEWER. COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS ON REPORTING RELEASES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND FLAME. KEEP CONTAINERS TIGHTLY CLOSED. DO NOT STORE OR MIX WITH STRONG OXIDIZERS, CHROMIC ANHYDRIDE, LEAD PERCHLORIC, OR PERCHLORIC ACID. STORE IN ADEQUATELY VENTILATED AREA.

Other Precautions:BOND AND GROUND CONTAINERS WHEN TRANSFERRING LIQUID. AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. USE WITH ADEQUATE VENTILATION OR UNDER HOOD. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment:UNIFORM, PROTECTIVE SU

IT, EYEWASH STATION &
EMERGENCY SHOWER.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. MONITORING OF AIR IN WORKPLACE IS
RECOMMENDED.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:=64.7C, 148.3F

B.P. Text:AT 760 MM HG

Melt/Freeze Pt:=-97.7C, -143.8F

Vapor Pres:127 MMHG @ 77 DEG F

Vapor Density:1.1(AIR=1)

Spec Gravity:0.791 @ 68 DEG F

Evaporation Rate & Refer
ence:>1 (N-BUTYL ACETATE=1)

Solubility in Water:100 WT %

Appearance and Odor:LIQUID, COLORLESS OR CLEAR, FAINT ALCOHOLIC

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

DO NOT STORE OR MIX WITH STRONG OXIDIZERS, CHRONIC ANHYDRIDE, LEAD
PERCHLORATE, OR PERCHLORIC ACID (REACTS VIGOROUSLY).

Stability Condition to Avoid:NONE PROVIDED BY MFR.

Hazardous Decomposition Products:NONE PROVIDED BY MFR. (MFR STATED:
OCCURS FROM HEAT A

ND REACTION WITH ABOVE STATED MATERIALS)

===== Disposal Considerations =====

Waste Disposal Methods:CLEANED UP MATERIAL MAY BE AN RCRA HAZARDOUS
WASTE. THE RCRA HAZARDOUS WASTE NUMBER FOR METHANOL IS U154. COMPLY
WITH FEDERAL, STATE, AND LOCAL REGULATIONS ON DISPOSAL. IF APPROVED
INCINERATION, BIO-O XIDATION, SUBSURFACE INJECTION, OR A LICENSED
DISPOSAL CONTRACTOR MAY BE USED.

===== MSDS Transport Information =====

Transport Information:DOT/IMO PROPER SHIPPING NAME: METHANOL, UN1230.
HAZARD CLASS 3, SUBSIDIARY RISK: POISON.

=====
===== Regulatory Information =====

SARA Title III Information:REGULATED AS A TOXIC CHEMICAL UNDER SECTION
313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION
ACT OF 1986 AND 40 CFR PART 372. RELEVANT HAZARD CATEGORIES: ACUTE,
CHRONIC, FIRE, CERCLA, AND 313.

=====
===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular
situation.