View NSN Online: https://aerobasegroup.de/nsn/6810-00-958-9970

UNION CARBIDE CORP LINDE DIV -- MONOETHANOLAMINE -- 6810-00-958-9970

Product ID:MONOETHANOLAMINE MSDS Date:11/15/1994 FSC:6810 NIIN:00-958-9970 MSDS Number: BYXVQ === Responsible Party === Company Name: UNION CARBIDE CORP LINDE DIV Address:39 OLD RIDGEBURY RD **Box:NONE** City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:203-744-3487 **Emergency Phone Num:2** 03-744-3487 CAGE:36346 === Contractor Identification === Company Name: UNION CARBIDE CORP LINDE DIV Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06817-0001 Country:US Phone:800-822-4357; 304-744-3487 CAGE:36346 **Company Name: VENUS LABORATORIES INC** Address:15571 COMMERCE LANE Box:City:HUNTINGTON BEACH State:CA ZIP:92649 Country:US Phone:714-881-3100 CAGE:0N140

Ingred Name:ETHANOLAMINE CAS:141-43-5 RTECS #:KJ577500 0 Fraction by Wt: >99% Other REC Limits:NONE SPECIFIED OSHA PEL:3 PPM/6 STEL ACGIH TLV:3 PPM/6 STEL; 9192

LD50 LC50 Mixture: PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE-CAUSES SEVERE IRRITATION & BURNS TO BODY TISSUES. MAY BE ABSORBED THROUGH SKIN IN TOXIC AMOUNTS. CHRONIC-KI DNEY & LIVER DAMAGE. Explanation of Carcinogenicity: MANUFACTURER GAVE NO INFORMATION ABOUT CARCINOGENICITY. HMIS FOUND NO LISTING & DOES NOT EXPECT IT TO BE CARCINOGENIC. Effects of Overexposure:EYE:SEVERE IRRITATION, PAIN, TEARING, REDNESS, SWELLING, BURNS. SKIN:PAIN, REDNESS, SWELLING, ULCERATION, BLEEDING, ABSORPTION OF TOXIC AMOUNT. IHALATION: SEVERE RESPIRATORY IRRITATION, NASAL DISCHARGE, COUGHING, CHEST PAIN. INGESTED: SEVERE IRRITATION ORBURNS TO MOUTH & G/I TRACT, NAUSEA, DI ARRHEA, VOMITING W/ASPIRATION, DIZZINESS.

Medical Cond Aggravated by Exposure:MAY AGGRAVATE AN EXISTING DERMATITIS, ASTHMA & INFLAMMATORY OR FIBROTIC PULMONARY DISEASE.

First Aid:**GET MEDICAL ATTENTION FOR ALL OVEREXPOSURES** EYE:FLUSH W/WATER FOR 15 MIN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY W/SOAP & WATER. LAUNDER CLOTHING BEFORE REUSE. INHALED:REMOVE FROM EXPO SURE. AID OR RESTORE BREATHING AS NEEDED.

INGESTED:DO NOT INDUCE VOMITING. GIVE 1-2 GLASSES OF MILK OR WATER TO DRINK. GET IMMEDIATE MEDICAL ATTENTION. NOTHING BY MOUTH IF UNCONSCIOUS.

Flash Point Method:PMCC

Flash Point:205F,96C

Extinguishing Media:LARGE FIRE:ALCOHOL-TYPE OR ALL-PURPOSE-TYPE FOAMS BY MANUFACTURER RECOMMENDED TECHNIQUES. SMALL FIRE:CO2 OR DRY CHEMICAL

Fire Fighting Procedures: USE NIOSH APPROVED SELF-CONTAINED BREATHING

APPARATUS, EYE PROTECTION & PROTECTIVE CLOTHING. WATER STREAM MAY CAUSE SPATTERING & SPREAD FIRE.

Unusual Fire/Explosion Hazard:OXIDES OF NITROGEN WILL BE EVOLVED.

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. AVOID CONTACT W/EYES & SKIN. COLLECT FOR DISPOSAL. AVOID RUNOFF TO SEWERS & WATERWAYS. Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

====== Handling and Storage ====

Handling and Storage Precautions:STORAGE-STORE IN A COOL,DRY & VENTILATED AREA AWAY FROM HEAT & FLAMES.KEEP CONTAINER CLOSED.
Other Precautions:DANGER! CAUSES EYE & SKIN BURNS. HARMFUL IF INHALED,ABSORBED THROUGH SKIN,SWALLOWED. COMBUSTIBLE. REPEATED EXPOSURE MAY CAUSE LIVER & KIDNEY DAMAGE. ASPIRATION CAUSES LUNG DAMAGE. DO NOT GET IN EYES, ON SKIN/CLOTHING. AVOID BREATHING

VAPOR.

======= Exposure Controls/Personal Protection ==========

Resp

iratory Protection:USE SELF-CONTAINED BREATHING APPARATUS IN HIGH VAPOR CONCENTRATIONS.
Ventilation:GENERAL(MECHANICAL) VENTILATION PLUS LOCAL EXHAUST WHERE VAPORS ARE EXPECTED TO ESCAPE TO THE WORKPLACE.
Protective Gloves:PVC-COATED OR RUBBER
Eye Protection:MONOGOGGLES
Other Protective Equipment:EYE BATH, SAFETY SHOWER & CHEMICAL APRON
Work Hygienic Practices:MFR:?. HMIS:USE GOOD CHEMICAL HYGIENE PRACTICES. AVOID CONTACT IF AT ALL POSSIBLE. WASH THOROUGHLY AFTER HANDLING.
Supple
mental Safety and Health USE W/ADEQUATE VENTILATION.

HCC:B2 NRC/State Lic Num:NONE Boiling Pt:=170.6C, 339.F Melt/Freeze Pt:=10.8C, 51.4F Vapor Pres:0.2 MM Vapor Density:2.1 Spec Gravity:1.018 Evaporation Rate & amp; Reference: