View NSN Online: https://aerobasegroup.de/nsn/8010-01-292-9618

DEFT INC CHEMICAL COATING DIV -- CAT MIL-C-85285B, 34095, TYPE II (04GN005CAT) 8010-01-292-9618

Product ID:CAT MIL-C-85285B, 34095, TYPE II (04GN005CAT) MSDS Date:11/11/1993 FSC:8010 NIIN:01-292-9618 Kit Part:Y MSDS Number: BYYDC === Responsible Party === Company Name: DEFT INC CHEMICAL COATING DIV Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92714-620 5 Country:US Info Phone Num:714-474-0400 Emergency Phone Num:714-474-0400/800-424-9300 CHEMTREC Preparer's Name:NORM GAUL CAGE:33461 === Contractor Identification === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Phone:949-474-0400 CAGE:33461

Ingred Name:ALIPHATIC ISOCYANATE CAS:4035-89-6 Fraction by Wt: 65% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT EST. ACGIH TLV:NOT EST

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)(VP = 15 @ 68F) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 25% Other REC Limits:NONE RECOMMENDED **OSHA PEL:50 PPM/STEL 75** ACGIH TLV:50 PPM/STEL 75 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: ETHYL 3-ETHOXYPROPIONATE (VP = 0.7 @ 68F) CAS:763-69-9 RTECS #:UF3325000 Fraction by Wt: 10% Other REC Limits:50 PPM/STEL 100 Ingred Name: HEXAMETHYLENE DIISOCYANATE (CERCLA) FREE MONOMER CONTENT 3-6 MO. FREE MONOMER MAY **RISE*** CAS:822-06-0 RTECS #:MO1740000 Other REC Limits: MILES - 0.02PPM CEIL OSHA PEL:NK *TO MAX 1.6%. ACGIH TLV:0.005 PPM; 9495 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:VOC = 355 G/L RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT EST. ACGIH TLV:NOT EST.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: VA PORS IRRIT EYES/NOSE/THROAT. INHAL: IRRIT, ACUTE NS DEPRESSION. CHRONIC: DEFATTING W/PROLONGED CONTACT. INGEST: IRRIT. POS CHEM PNEUMONITIS W/ASPIRATION RESULT OF PREVIOUS REPEATED OVEREXPOS/ SINGLE LG DOSE, SOME PEOPLE WILL DEVELOP ISOCYANATE SENSITIZATION, WHICH CAUSES THEM REACT TO LATER EXPOSURE OF **

Effects of Overexposure:INHAL: HEADACHE, DIZZINESS, STAGGERING GATE, CONFUSION, UNCONSC OR COMA, DIFFICULT BREATHING, ASTHMA. SKIN: SENSITIZATION, OTHER ALLERGIC RES

PONSES, SWELLING, REDNESS, RASH.

EYES: TEARING, REDNESS, SW ELLING W/STINGING SENSATION. Medical Cond Aggravated by Exposure:ASTHMA & ANY OTHER RESP DISORDERS. SKIN: ALLERGIES, EXCEMA, DERMATITIS. ISOCYANATE SENSITIZATION.

First Aid:INHAL: GET FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPICAL SYMPTOMS MAY DEVELOP, MAY BE IMMED OR DELAYED BY SEVERAL HRS. GET MED AID. SKIN: REMOVE CONTAM CLOTHES. WASH THOROUGHLY W /SOAP &

WATER. EYES: FLUSH W/CLEAN LUKE WARM WATER (LOW PRESSURE) AT LEAST 15 MIN, LIFTING LIDS. GET MED AID. INGEST: DON'T INDUCE VOMITING. DON'T GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON. GET MED AID.

Flash Point Method:TCC Flash Point:60.0F,15.6C Lower Limits:1.05 Upper Limits:8.0 Extinguishing Media:FOAM, ALCOHOL-FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG, WATER SPRAY. Fire Fighting Procedures:FULL FIRE FIGHT EQUIP W/SCBA, FULL PROTECT CLOTHES. USE H2O TO COOL CLOSED CNTNRS/PREVENT PRESSURE BUILD-UP/AUTOIGNITE/EXPLOSION. HDI/IRRIT VAPORS GENERATED. Unusual Fire/Explosion Hazard:KEEP CLOSED TIGHT. CLOSED CNTNR MAY EXPLODE W/EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. POS HEALTH HAZ W/OVEREXPOSURE DECOMP PRODS

Spill Release Procedures: EVACUATE NONESSENTIAL PERSONNEL. REMOVE ALL

IGNITION SOURCES. VENT. AREA. CONTAIN/REMOVE W/INERT ABSORBENT & NONSPARKING TOOLS.

Handling and Storage Precautions:STORE IN BUILDING COMPLYING W/OSHA 1910.106. AVOID STORING NEAR HI TEMP/FIRE/OPEN FLAME/SPARK SOURCES. STORE IN TIGHT CLOSED CNTNR/WELL VENTED AREA.

Other Precautions: KEEP CNTNR TIGHT/UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED BREATHING VAPOR/SPRAY MISTS. POS ALLERGIC REACTION W/PROLONG

ED OVEREXPOSURE. AVOID SKIN/EYE CONTACT. DON'T TAKE INTERNALLY. DON'T HANDLE TIL READ/UNDERSTAND MFG PRECAUTIONS.

Respiratory Protection:ORGANIC VAPOR RESPIRATR (AIR PURIFYING/FRESH AIR) OBSERVE OSHA REGS (RESPIRATR USE). PROVIDE VENT (KEEP EXPOSURE LEVELS