

DEL PAINT CORP. -- TT-E-2784 -- 8010-01-333-9813

===== Product Identification =====

Product ID:TT-E-2784  
MSDS Date:08/01/1995  
FSC:8010  
NIIN:01-333-9813  
MSDS Number: BYYKZ  
=== Responsible Party ===  
Company Name:DEL PAINT CORP.  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431/FAX 405-672-0804  
Emergency Phone Num:800-424-9300 24 HRS  
Preparer's Name:ONE  
Y FLEMING  
CAGE:JO954  
=== Contractor Identification ===  
Company Name:DEL PAINT CORP.  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431/FAX 405-672-0804  
CAGE:JO954  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL  
CAS:57-55-6  
RTECS #:TY2000000  
Fraction by Wt: 3.68%  
Other REC Limi

ts:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 3.39%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC

CAS:108-01-0

RTECS #:KK6125000

Fraction by Wt: 0.21%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE

CAS:26530-20-1

Fraction by Wt: 0.18%

Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS

Fraction by Wt: 95.54%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAN CAUSE IRRITATION OF RESPIRATORY  
PASSAGES.

Effects of Overexposure:INHALATION OF VAPOR/MIST CAN CAUSE HEADACHES,  
NAUSEA, IRRITATION OF NOSE/THROAT/LUNGS. EYES: CAN CAUSE SLIGHT  
IRRITATION. CHRONIC SKIN CONTACT CAN CAUSE SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure:PREEXISTING LUNG DISEASE MAY BE  
AGGRAVATED BY EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMTS WATER 15 MINUTES. CONSULT DR. IF  
IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP &  
WATER. INGESTION: GIVE 2 GLASSES WATER. CONSULT DR.

=====  
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>212F,>100C

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) & FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 212F/100C.  
POLYMER FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY.  
USE CARE TO AVOID FALLING. CONTAIN W/INERT

MAT'L (SAND/EARTH).

TRANSFER LIQ/SOLID DIKING MAT'L TO SEPARATE SUITABLE CONTAINERS FOR  
RECOVERY/DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING. DO NOT TAKE  
INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE  
SOLID AIRBORNE PARTICLES OF OVER-SPRAY D  
URING SPRAY APPLICATION.

Ventilation:NORMAL, SUCH AS FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:EYEWASH STATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:350F,177C

Vapor Pres:NONE

Vapor Density:>AIR

Spec Gravity:1.13

VOC Pounds/Gallon:190

pH:9 MAX

VOC Grams/Liter:1.58

Viscosit

y:77-95 KU

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: SLIGHT

Appearance and Odor: RED LIQUID, SLIGHT ODOR

Percent Volatiles by Volume: 60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE KNOWN

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: ACRYLIC MONOMERS

===== Disposal Considerations =====

Waste Disposal Methods: KEEP SPILLS/CLEANING RUN-OFF OUT  
OF SEWERS &

OPEN BODIES OF WATER. CONSULT FEDERAL/STATE/LOCAL AUTHORITIES FOR  
PROPER DISPOSAL PROCEDURES CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document

should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.