

DEL PAINT CORP. -- TT-E-2784 -- 8010-01-365-8840

===== Product Identification =====

Product ID:TT-E-2784
MSDS Date:08/01/1995
FSC:8010
NIIN:01-365-8840
MSDS Number: BYYSD
=== Responsible Party ===
Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Info Phone Num:405-672-1431/FAX 405-672-0804
Emergency Phone Num:800-424-9300 24 HRS
Preparer's Name:ONE
Y FLEMING
CAGE:JO954
=== Contractor Identification ===
Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431/FAX 405-672-0804
CAGE:JO954
Company Name:DEL PAINT MFG
Address:3105 EAST RENO
Box:City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL
CAS:57-55-6
RTECS #:TY2000000
Fraction by Wt: 3.48%
Other REC Limi

ts:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 3.14%
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC
CAS:108-01-0
RTECS #:KK6125000
Fraction by Wt: 0.19%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE
CAS:26530-20-1
Fraction by Wt: 0.18%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS
Fraction by Wt: 93.01%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CAN CAUSE IRRITATION OF RESPIRATORY
PASSAGES.
Effects of Overexposure:INHALATION OF VAPOR/MIST CAN CAUSE HEADACHES,
NAUSEA, IRRITATION OF NOSE/THROAT/LUNGS. EYES: CAN CAUSE SLIGHT
IRRITATION. CHRONIC SKIN CONTACT CAN CAUSE SLIGHT IRRITATION.
Medical Cond Aggravated by Exposure:PREEXISTING LUNG DISEASE MAY BE
AGGRAVATED BY EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMTS WATER 15 MINUTES. CONSULT DR. IF
IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP &
WATER. INGESTION: GIVE 2 GLASSES WATER. CONSULT DR.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>212F,>100C

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) & FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 212F/100C.
POLYMER FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY.
USE CARE TO AVOID FALLING. CONTAIN W/INERT

MAT'L (SAND/EARTH).

TRANSFER LIQ/SOLID DIKING MAT'L TO SEPARATE SUITABLE CONTAINERS FOR
RECOVERY/DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING. DO NOT TAKE
INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE
SOLID AIRBORNE PARTICLES OF OVER-SPRAY D
URING SPRAY APPLICATION.

Ventilation:NORMAL, SUCH AS FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:EYEWASH STATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:350F,177C

Vapor Pres:NONE

Vapor Density:>AIR

Spec Gravity:1.13

VOC Pounds/Gallon:179

pH:9 MAX

VOC Grams/Liter:1.49

Viscosity:77-95

KU

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: SLIGHT

Appearance and Odor: ORANGE LIQUID, SLIGHT ODOR

Percent Volatiles by Volume: 60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE KNOWN

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: ACRYLIC MONOMERS

===== Disposal Considerations =====

Waste Disposal Methods: KEEP SPILLS/CLEANING RUN-OFF OUT OF S
EWERS &

OPEN BODIES OF WATER. CONSULT FEDERAL/STATE/LOCAL AUTHORITIES FOR
PROPER DISPOSAL PROCEDURES CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document shou

ld seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.