

PIONEER/ECLIPSE CORP. -- STATEMENT HARD FLOOR SEALER (#403) -- 7930-01-380-8379

===== Product Identification =====

Product ID:STATEMENT HARD FLOOR SEALER (#403)

MSDS Date:03/15/1995

FSC:7930

NIIN:01-380-8379

MSDS Number: BYYWD

=== Responsible Party ===

Company Name:PIONEER/ECLIPSE CORP.

City:SPARTA

State:NC

ZIP:28675

Country:US

Info Phone Num:910-372-8080

Emergency Phone Num:800-424-9300 (CHEMTREC

)

Preparer's Name:JAMES B. MCCORMICK

CAGE:ONLMO

=== Contractor Identification ===

Company Name:CLEANING SOLUTIONS, INC.

Box:UNKNOWN

CAGE:0NY12

Company Name:PIONEER ECLIPSE CORPORATION

Address:CHEMICAL DIVISION

Box:City:SPARTA

State:NC

ZIP:28675

Country:US

Phone:919-372-8080

CAGE:0NLM0

Company Name:PIONEER/ECLIPSE CORP.

Address:ECLIPSE RD. & HWY. 21 S.

Box:1089

City:SPARTA

State:NC

ZIP:28675

Phone:(919) 372-8080

CAGE:ONLMO

===== Composition/Information on Ingredients =====

Ingr

ed Name:1, 2-PROPANOL (LD50 ORAL RAT 34 G/KG)

CAS:57-55-6

RTECS #:TY2000000

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2-PROPANOL, 1-(2-METHOXY-1-METHYLETHOXY) (SARA 313) (LD50 ORAL RAT 5.4 G/KG)

CAS:34590-94-8

RTECS #:JM1575000

Fraction by Wt: 5-8%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/STEL 150 PPM

ACGIH TLV:100 PPM/STEL 150 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YE

S

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: SLIGHTLY IRRITATING. SKIN:

IRRITATING ON REPEATED/PROLONGED CONTACT. INHALATION: VAPOR/MIST CAN CAUSE HEADACHE, NAUSEA & IRRITATE EYES, NOSE, THROAT, LUNGS.

INGESTION: IRRITATES MOUTH, ESOPHAGUS , STOMACH.

Medical Cond Aggravated by Exposure:PROLONGED/REPEATED CONTACT MAY CAUSE DRYING, DEFATTING, DERMATITIS TO SKIN.

===== First Aid Measures =====

F

irst Aid:EYES: FLUSH W/LARGE AMOUNTS WATER AT LEAST 15 MINUTES. SEE DR. IF IRRITATION PERSISTS. SKIN: WASH W/SOAP & WATER. INHALATION: GET FRESH AIR. INGESTION: DRINK SEVERAL GLASSES WATER, INDUCE VOMITING. GE T MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point:NONCOMBUSTIBLE

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NA

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:MATERIALS CAN SPLATTER ABOVE 212F. POLYMER FIL

M CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:SM: ABSORB ON INERT MATERIAL (E.G. SAND/EARTH). DISPOSE ACCORDING TO FED./STATE/LOCAL LAWS. LG: KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY, USE CARE. DIKE/CONTAIN W/INERT MATERIAL. TRANSFER LIQ/SOLID DIKING MATERIAL TO SEPARATE CONTAINERSFOR*

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE TEMP., MAX. 140F, MIN . 34F.

KEEP FROM FREEZING, PRODUCT MAY COAGULATE.

Other Precautions:NK *DISPOSAL/RECOVERY. KEEP SPILLS/CLEANING RUN-OFF OUT OF SEWERS/OPEN BODIES WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHEN PERMISSIBLE AIRBORNE CONCENTRATIONS NOT EXCEEDED. IN EMERGENCY, USE APPROVED POSITIVE PRESSURE SCBA.

Ventilation:MECHANICAL LOCAL EXHAUST AT POINT OF CONTAMINATION RELEASE.

Eye Protection:CHEM SPLASH GOGGLES (ANSI/EQUIVALENT)

Other Protective Equipment:AS REQUIRED BY EMPLOYER CODE.

Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:NOT EST.

Vapor Density: