View NSN Online: https://aerobasegroup.de/nsn/6750-01-416-1777

EASTMAN KODAK CO -- 832 0608 FLEXICOLOR DEVELOPER REPLENISHER LORR, PART C -- 6750-01-416-1777

============= Product Identification =================

Product ID:832 0608 FLEXICOLOR DEVELOPER REPLENISHER LORR, PART C

MSDS Date:09/26/1997

FSC:6750

NIIN:01-416-1777

Kit Part:Y

MSDS Number: BZBSX === Responsible Party ===

Company Name: EASTMAN KODAK CO

Address:343 STATE ST City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Info Phone Num:800-242-2424

Emergency Phone Num:716-722-5151/716-724-4501

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Composition/Info

rmation on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 50-55%

Other REC Limits: NONE RECOMMENDED

Ingred Name:4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE

SULFATE CAS:25646-77-9 RTECS #:KJ6477000 Fraction by Wt: 40-45%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SODIUM BISULFITE (SASA III) (CERCLA)

CAS:7631-90-5

RTECS #:VZ2000000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9495

EPA Rpt

Qty:5000 LBS

DOT Rpt Qty:5000 LBS

========= Hazards Identification ================

LD50 LC50 Mixture:ORAL LD50 (RAT): 25-50 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE KIDNEY DAMAGE BASED ON ANIMAL DATA. LIBERATES SULFUR DIOXIDE GAS WHICH IS IRRITATING TO RESPIRATORY TRACT. EYE CONTACT CAUSES IRRITATION. SKIN CONTACT CAUSES IRRITATION. MAY CAUSE AL


LERGIC S KIN REACTION. MAY BE FATAL

IF SWALLOWED.MAY CAUSE IRRITATION OF GASTRINTESTINAL TRACT. MAY CAUSE KIDNEY DAMAGE.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:KIDNEY DAMAGE, RESPIRATORY TRACT IRRITATION, EYE IRRITATION, SKIN IRRITATION, ALLERGIC SKIN REACTION, DEATH, GI TRACT IRRITATION, DIFFICULT BREATHING.

Medical Cond Aggravated by Ex



CONCENTRATIONS GREATER THATN EXPOSURE LIMITS. DO NOT GET IN EYES,

Other Precautions: KEEP FROM CONTACT WITH OXIDIZING MATERIALS. EXERCISE CAUTION IN HEATING, ESPECIALLY IN A CLOSED CONTAINER. KEEP AWAY

ON SKIN, ON CLOTHING. USE WITH ADEQUATE VENTILATION

FROM HEAT. STORE IN A COOL PLACE. KEEP AWAY FROM INCOMP

| ATIBLE SUBSTANCES. KEEP CONT AINER CLOSED. |
|--|
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR TYPE: ACID GAS. IF RESPIRATORS ARE USED, A PROGRAM SH OULD BE INSTITUTED. Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS. Pro |
| tective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE. |
| Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health KEY1:C2. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. |
| ====================================== |
| HCC:C2 Boiling Pt:>100.C, 212.F Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.18 pH:2.1 Viscosity:NOT GIVEN Evaporation Rate & Description of the company o |

Appearance and Odor:LIGHT YELLOW LIQUID, STRONG SULFUR DIOXIDE ODOR

======== Stability and Reactivity Data =========

Percent Volatiles by Volume:50-60%

Stability Indicator/Materials to Avoid:YES BASES, STRONG OXIDIZING AGENTS. Stability Condition to Avoid:AVOID TEMPER

ATURES ABOVE 158F.

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR.

====== Disposal Considerations ===========

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.