

SCHERING CORP (SCHERING-PLOUGH ANIMAL HEALTH) -- 0566-05 CELESTONE SOLUSPAN SUSP
-- 6505-00-904-2190

===== Product Identification =====

Product ID:0566-05 CELESTONE SOLUSPAN SUSP

MSDS Date:06/25/1993

FSC:6505

NIIN:00-904-2190

MSDS Number: BZFXW

=== Responsible Party ===

Company Name:SCHERING CORP (SCHERING-PLOUGH ANIMAL HEALTH)

Address:2000 GALLOPING HILL RD

City:KENILWORTH

State:NJ

ZIP:07033-5000

Country:US

Info Phone Num:800-932-0473/908-298-5044

Emergency Phone Num:908-820-6222/908-298-5044

CAGE:04542

=== Contractor Identification ===

Company Name:SCHERING CORP (SCHERING-PLOUGH ANIMAL HEALTH)

Address:2000 GALLOPING HILL RD

City:KENILWORTH

State:NJ

ZIP:07033-5000

Country:US

Phone:800-932-0473/908-298-5044

CAGE:04542

===== Composition/Information on Ingredients =====

Ingred Name:BETAMETHASONE ACETATE

CAS:987-24-6

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

In

Product Name: BETAMETHASONE SODIUM PHOSPHATE *96-2*
CAS: 151-37-5
RTECS #: TU4056500

===== Hazards Identification =====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: EYES: IRRITATION. SKIN: IRRITATION &
SENSITIZATION. CORTICOSTEROID EXPOSURE MAY LEAD TO
TUBERCULOSIS/TUBERCULIN REACTIVITY. CORTICOSTEROID EXPOSURE MAY
ADVERSELY AFFECT INDIVIDUAL W/ NON-SPECIFIC ULCERATIVE COLITIS,
DIVERTICULITIS, ULCERS, RENAL INSUFFICIENCIES, HYPERTENSION,
OSTEOPOROSIS/MYASTHENIA GRAVIS.
Explanation of Carcinogenicity: NONE
Effects of Overexposure: IRRITATION & SENSITIZATION
Medical Conditions Aggravated by Exposure: NON-SPECIFIC ULCERATIVE COLITIS,
DIVERTICULITIS, ULCERS, RENAL INSUFFICIENCIES, HYPERTENSION,
OSTEOPOROSIS/IMMUNIZATION PROCEDURES

===== First Aid Measures =====

First Aid: INHALATION: REMOVE FROM EXPOSURE. IF NOT BREATHING GIVE CPR.
SKIN: THOROUGHLY WASH EXPOSED AREA W/ SOAP & WATER. EYES: FLUSH W/ WATER FOR 15 MINS. INGESTION: GIVE COPIOUS AMOUNTS OF WATER & INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point: >200°F
Extinguishing Media: WATER, WATER SPRAY, CO2, DRY CHEMICAL
Fire Fighting Procedures: FIGHT FROM SAFE DISTANCE/PROTECTED LOCATION.
USE WATER SPRAY TO KEEP EXPOSED CONTAINERS & EQUIPMENT COOL.
L. WEAR FULL PROTECTIVE CLOTHING & SCBA.

===== Accidental Release Measures =====

Spill Release Procedures: MINIMIZE CONTACT W/ MATERIAL, EVACUATE AREA.
WEAR APPROPRIATE RESPIRATORY PROTECTION & PROTECTIVE CLOTHING.
USE SQUEEGIE, SCOOP, ABSORB/USE A VACUUM. CLEAN AREA W/ AN ALKALINE
CLEANER/DETERGENT.

===== Handling and Storage =====

Handling and Storage Precautions: PROTECT FROM LIGHT. STORE IN A COOL,
DRY, WELL VENTILATED AREA.

LATED AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HALF MASKED RESPIRATOR W/ORGANIC VAPOR/ACID
GAS/HIGH EFFICIENCY CARTRIDGES.

Ventilation:ADEQUATE LOCAL EXHUAUST

Protective Gloves:LATEX

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Work Hygienic Practices:WASH HANDS & FOREARMS AFTER EACH USE.

REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, STRONG ACIDS & BASES

Stability Condition to Avoid:OPEN FLAME & HIGH TEMPS

Hazardous Decomposition Products:CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United Stat

es of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.