

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- G641 SILICONE COMPOUND --  
6850-00-927-9461

===== Product Identification =====

Product ID:G641 SILICONE COMPOUND

MSDS Date:02/12/1993

FSC:6850

NIIN:00-927-9461

MSDS Number: BZLHY

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address:260 HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:5

18-237-3330/FAX 518-233-3795

Emergency Phone Num:518-237-3330

Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS, EPA METHOD 24,  
300F;SKIN/RESP (SUPP)

Explanati

on of Carcinogenicity:PER MSDS:NOT LISTED AS CARCINOGEN OR  
SUSPECTED CARCINOGEN BY NTP/IARC/OSHA.

Effects of Overexposure:MILD SKIN IRRITATION. MODERATE EYE IRRITATION.  
METAL FUME FEVER.

Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:INGEST:RINSE MOUTH W/WATER SEVERAL TIMES. SKIN:WASH  
W/SOAP/WATER. INHAL:MOVE PERSON TO FRESH AIR. EYE:IMMED FLUSH  
W/PLENTY OF WATER FOR @LEAST 15MINS.GET MED ATTN IF IR

RIT PERSISTS.

NOTE TO PHYSICIAN: NONE KNOWN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>500F,>260C

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures:NONE KNOWN.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WIPE/SCRAP/SOAK UP IN INERT MATL.PUT IN CNTNR  
FOR DISPOSAL.WASH WALKING SURFACES W

/DETERGETN & WATER TO REDUCE

SLIPPING HAZARD.WEAR PROPER PROTECTIVE EQMT AS SPECIFIED IN  
PROTECTIVE EQPMT SECTION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT W/EYES.

Other Precautions:PROD CONTAINS METHYLPOLYSILOXANES WHICH CAN GENERATE  
FORMALDEHYDE @ APRROX 300F/ABOVE IN ATM W/OXY.MSDS FOR FORMALDEHYDE  
AVAILABLE FROM GE SILICONES.

=====  
===== Exposure

Controls/Personal Protection =====

Respiratory Protection:NONE KNOWN.

Ventilation:NONE KNOWN.

Protective Gloves:CLOTH GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:EYEWASH STATIONS.

Work Hygienic Practices:WASH HANDS AFT HDNLG.

Supplemental Safety and Health

HEALTH HAZ:SENSITIZER,EYE/THROAT IRRIT,ACUTE TOXICANT,POT CANCER HAZ.

=====  
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>572F,>300C

Vapor Pres: