

LUBRICATING SPECIALTIES CO -- A9952;VV-L-800C AM1 -- 9150-00-281-2060

=====
Product Identification
=====

Product ID:A9952;VV-L-800C AM1

MSDS Date:05/26/1993

FSC:9150

NIIN:00-281-2060

MSDS Number: BZNHR

=== Responsible Party ===

Company Name:LUBRICATING SPECIALTIES CO

Address:8015 PARAMOUNT BLVD

City:PICO RIVERA

State:CA

ZIP:90660-4811

Country:US

Info Phone Num:213-928-3311

Emergency Phone Num:800

-424-9300

Preparer's Name:RICHARD J. EBERHARDT

CAGE:2X842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO

Address:8015 PARAMOUNT BLVD

Box:City:PICO RIVERA

State:CA

ZIP:90660-4811

Country:US

Phone:800-424-9300

CAGE:2X842

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

Company Name:NAUGHTON ENERGY CORP

Address:RT 940

Box:709

City:

POCONO PINES
State:PA
ZIP:18350-0709
Country:US
Phone:570-646-0422
CAGE:1DL10

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE
CAS:64742-46-7
RTECS #:JN9379645
Fraction by Wt: 302F,>150C
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER
FOG.
Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE WHEN HEATED ABOVE
FLASHPOINT;VAPORS MAY EXPLODE IN CONFINED SPACE IF IGNITED.

=====
Accidental Release Measures
=====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT
ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE
CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.
Neutralizing Agent:NOT APPLICABLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM
HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.
Other Precautions:AVOID EXCESSIVE MISTING;MAY CAUSE SLIPPERY FLOORS;USE
PROPER FOOTWEAR.DISCARD CONTAMINATED LEATHER GLOVES AND SHOES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.
Ventilation:USE GENERAL DILUTION VENTILATION.
Protective Gloves:IMPERVIOUS GLOVES

VES.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:CHEMICALLY RESISTANT BOOTS AND APRON.PROVIDE
A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET
CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK
AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>482F,>250C

Vapor Pres:1

Spec Gravity:0.878

Eva

poration Rate & Reference: