

EASTMAN KODAK COMPANY -- 815 8396 KODAK COLOREDGE BLACK TONER -- 6850-01-354-4322

===== Product Identification =====

Product ID:815 8396 KODAK COLOREDGE BLACK TONER

MSDS Date:01/19/1994

FSC:6850

NIIN:01-354-4322

MSDS Number: BZNWF

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800-  
242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on Ingredients =====

=====

Ingred Name:BENZYLDIMETHYLOCTADECYLAMMONIUM 3-NITRO-BENZENESULFONATE  
CAS:124088-59-1  
Fraction by Wt: 90-95%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9596

Ingred Name:POLYMER - CGH  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BENZYLDIMETHYLOCTADECYLAMMONIUM 3-NITRO-BENZENESULFONATE  
CAS:124088-59-1  
Fraction by Wt: 1-5%  
Oth  
er REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION-EXPECTED TO BE A LOW HAZARD  
FOR RECOMMENDED HANDLING. EYES-NO SPECIFIC HAZARD KNOWN. MAY CAUSE  
TRANSIENT IRRITATION. SKIN-EXPECTED TO BE A LOW HAZARD FOR  
RECOMMENDED HANDLING. INGESTION-  
EXP ECTED TO BE A LOW INGESTION  
HAZARD.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:OVEREXPOSURE TO CARBON BLACK DUST MAY RESULT IN  
IRRITATION OF THE RESPIRATORY TRACT AND BENIGN DEPOSITION OF CARBON  
BLACK IN THE LUNG.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION-IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL  
ATTENTION IF SYMPTOMS PERSISTS. EYES-ANY M

ATERIAL THAT CONTACT THE  
EYES SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL  
ATTENTION IF SYMPTOMS OCCUR. SKIN-WASH WITH SOAP & WATER. GET  
MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION-DRINK 1 OR 2 GLASSES  
OF WATER. SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL.  
Fire Fighting Procedures:NONE.  
Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE  
DUST-AIR MIXTURE.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT USE A VACUUM CLEANER TO CLEAN UP SPILLS  
OF POWDERED TONERS. THE VERY FINE PARTICLES CAN CAUSE A FIRE OR  
EXPLOSION. SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CARTON.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. KEEP FROM  
CONTACT  
WITH OXIDZING MATERIALS. MINIMIZE DUST GENERATION AND  
ACCUMULATION.  
Other Precautions:USE WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.  
Ventilation:GOOD VENTILATION (TYPICALLY 4-6 ROOM VOLUMES/HR) SHOULD BE  
USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS  
Protective Gloves:MINIMIZE SKIN CONTACT.  
Eye Protection:MINIMIZE EYE CONTACT.  
Other Protective Equipment:EYE BATH, WASHING FACILITI  
ES, SAFETY SHOWER.  
Work Hygienic Practices:GOOD INDUSTRIAL HYGIENE PRACTICES SHOULD BE  
FOLLOWED WHICH INCLUDE PREVENTING EYE CONTACT MINIMIZING SKIN  
CONTACT.  
Supplemental Safety and Health  
LOW HAZARD FOR RECOMMENDED HANDLING.

===== Physical/Chemical Properties =====

HCC:N1  
Melt/Freeze Pt:M.P/F.P Text:140F,60C  
Vapor Pres:NEGLIGIBLE  
Vapor Density:NEGLIGIBLE  
Spec Gravity:>1.00  
Evaporation Rate & Reference:NEGLIGIBLE  
Solubility in Water:NEGLIGIBLE  
Appearance

and Odor:SOLID (POWDER), BLACK, SLIGHT ODOR.  
Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:NONE.

===== Disposal Considerations =====

Waste Disposal Methods:CAN BE INCINERATED WHEN IN COMPLIANCE WITH LOCAL  
REGULATIONS. CONTRACT WITH A LICENSED  
DISPOSAL AGENCY. DISCHARGE,  
TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent profession  
al advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.