

MATSUSHITA ELECTRONICS CORP, LIGHT BUS GROUP -- EFD25LE.UHD PANASONIC ELECTRONIC LIGHT BULBS-TRICOLOR(SUPPL) -- 6240-01-381-4450

=====  
Product Identification  
=====

Product ID:EFD25LE.UHD PANASONIC ELECTRONIC LIGHT BULBS-TRICOLOR(SUPPL)

MSDS Date:01/01/1987

FSC:6240

NIIN:01-381-4450

MSDS Number: BZNX

=== Responsible Party ===

Company Name:MATSUSHITA ELECTRONICS CORP, LIGHT BUS GROUP

Address:TAKATS

UKI OSAKA, 569-11

City:OSAKA

Country:JP

Info Phone Num:201-348-5380 (JOHN CUNNINGHAM)

Emergency Phone Num:81-726-82-5521

CAGE:MATSH

=== Contractor Identification ===

Company Name:MATSUSHITA ELECTRIC INDUSTRIAL CO LTD

Address:9-1 HIRAIDE KOGYO DANCHI

Box:18

City:UTSUNOMIYA CITY, TOCHIGI PREF, 321-JAPAN

Country:US

Phone:0286-63-3221

CAGE:MATSH

Company Name:PANASONIC CO DIV OF MATSUSHITA

Address:DATA PROCESSING CENTER HQTRS - ONLY

Box:City:SECAUCUS

State:NJ

ZIP:07094

Country:US

Phone:201-348-9090 F

OR CUST SVC/MSDS...

CAGE:2M734

=====  
Composition/Information on Ingredients  
=====

Ingred Name:INERT INGRED (GLASS,SILICONE RESIN,PET,PLASATIC,BASE(BRASS COVERED W/NI),LEAD-WIRE,TUNGSTEN FILAMENT,INERT GAS)

Fraction by Wt: 99.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PHOSPHOR POWDER (SEE INGREDIENTS 3,4,5)

Fraction by Wt: 1.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:LAP POWDER COMPOSED MAINLY OF LANTHANUM PHOSPHATE AS BODY OF CRYSTAL,CHARACTERIZED BY BEING A

ACTIVATED BY CERIUM,TERBIUM.

Fraction by Wt: SEE #2%

Other REC Limits:NONE RECOMMENDED

Ingred Name:YOX POWDER COMPOSED MAINLY OF YITRIUM OXIDES AS BODY OF CRYSTAL CHARACTERIZED BY BEING ACTIVATED BY EUROPIUS.

Fraction by Wt: SEE #2%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SCA POWDER COMPOSE MAINLY OF SR,CA,BA HALOPHOSPHATE AS BODY OF CRYSTAL CHARACTERIZED BY BEING ACTIVATED BY EUROPIUM.

Fraction by Wt: SEE #2%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MERCURY (SARA 313) (CE RCLA)

CAS:7439-97-6

RTECS #:OV4550000

Fraction by Wt: 0.005%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C, 0.1 MG/M3; Z-2

ACGIH TLV:S,0.025 MG/M3; A4;96

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:BREAKAGE OF LAMP MAY RESULT IN SOME EXPO TO PHOSP

HOR POWDER DUST/& TO ELEMENTAL MERCURY VAP.PHOSPHORS

CONTAIN ALUMINATE,PHOSPHATES & AN OXIDE.NO ADVERSE AFFECTS EXPECTED FROM OCCASIONAL EXPO TO BROKEN LAMPS BUT AS MATTER OF GOOD PRACT PROL/FREQ EXPO SHOULD BE AVOID THRU USE OF ADEQ VENTI DURING DISPO OF LG LAMP QUANT.

Effects of Overexposure:NO ADVERSE AFFECTS EXPECTED FROM OCCASIONAL EXPO TO BROKEN LAMPS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

=====

First Aid:NORMAL FIRST AID PROCEDURE FOR GLASS CUTS IS SUCH OCCUR THROUGH LAMP BREAKAGE.

===== Fire Fighting Measures =====

Extinguishing Media:NONE SPECIFIED BY MANUFACTURER. HMIS:USE APPROPRIATE EXTINGUISHING MEDIA FOR SURROUNDING FIRE.  
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.  
Unusual Fire/Explosion Hazard:NOT APPLICABLE. UNDER EXTREME HEAT GLASS BULB MIGHT BE MELT OR CRACK.

===== Accidental Release Measures =====

Spill Release Procedures:NORMAL PRECAUTIONS SHOULD BE TAKEN FOR COLLECTION OF BROKEN GLASS. APPROPRIATE DUST MASK SHOULD BE USED IF LG VOL OF LAMPS ARE BEING BROKEN FOR DISPOSAL. APPRIPIATE HAND/EYE PROT SHOULD BE WORN WHEN DISPOSING OF LAMPS OR HDNLTG BROKEN GLASS.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS SHOULD BE TAKEN FOR COLLECTION OF BROKEN GLASS.  
Other Precautions:AVOID INHALATION OF ANY AIRBORNE DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROPRIATE DUST MAKS SHOULD BE USED IF LARGE VOLUME OF LAMPS ARE BEING BROKEN FOR DISPOSAL.  
Ventilation:PROVIDE LOCAL EXHAUST WHEN DISPOSING LARGE QUANTITY OF LAMPS.  
Protective Gloves:SEE OTHER PROT EQPT.  
Eye Protection:SEE OTHER PROT EQPT.  
Other Protective Equipment:HAND & EYE PROTECTION:APPROPRIATE HAND/EYE PROTECTION SHOULD BE WORN WHEN DISPOSING OF LAMPS/HNDLTG BROKEN GLASS.  
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.  
Supplemental Safety and Health  
EFD20LE.UHD, EFD15LE.UHD. ITEM IS AN ARTICLE.

===== Physical/Chemical Properties =====

HCC:N1  
Appearance and Odor:LIGHT BULB, 203CM LONG, UP TO 64MM IN DIAGONAL DEMENSIONS OF OUTER ENCLOSURE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
GLASS WILL REACT WITH HYDROFLUORIC AC

ID.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ANY APPLICABLE LOCAL,  
STATE AND FEDERAL REGULATIONS. PROVIDE LOC EXHAST WHEN DISPO LG  
QUANT OF LAMPS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Departme

nt

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.