

ALLOY RODS CORPORATION -- 8N12 MISCELLANEOUS ARCALOY HIGH ALLOY COVERED
ELECTRODES -- 3439-00-238-5667

===== Product Identification =====

Product ID:8N12 MISCELLANEOUS ARCALOY HIGH ALLOY COVERED ELECTRODES

MSDS Date:02/15/1988

FSC:3439

NIIN:00-238-5667

MSDS Number: BZPFS

=== Responsible Party ===

Company Name:ALLOY RODS CORPORATION

Address:WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Coun

try:US

Info Phone Num:717-637-8911

Emergency Phone Num:717-637-8911

CAGE:84021

=== Contractor Identification ===

Company Name:ESAB GROUP INC

Address:801 WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Country:US

Phone:717-637-8911 OR 800-933-7070

CAGE:84021

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM

CAS:7440-32-6

RTECS #:XR1700000

Other REC Limits:NONE RECOMMENDED

Ingred Name:NIOBIUM (ALSO CALLED COLUMBIUM)

CAS:7440-03-1

Other REC Limits:NO

NE RECOMMENDED

Ingred Name:FELDSPAR; (POTASSIUM FELDSPAR)

CAS:68476-25-5

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM METASILICATE

CAS:6834-92-0

RTECS #:VV9275000

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM TITANATE

CAS:12030-97-6

Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Other REC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1

5 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:CRYOLITE (SODIUM ALUMINUM FLUORIDE)

CAS:15096-52-3

RTECS #:WA9625000

Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:SODIUM TITANATE

CAS:12034-34-3

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:WELDING FUME 5MG/M3

(ACGIH).

Routes of Entry: Inhalation: YES Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: YES

Health Hazards Acute and Chronic: FUMES/GASES CAN BE DANGEROUS TO HEALTH. ARC RAYS CAN INJURE EYES/BURN SKIN. ELECTRIC SHOCK CAN KILL. ACUTE OVEREXPO TO WELDING

FUMES: DISCOMFORT, DIZZ, NAU, DRYNESS, IRRIT OF NOSE/THROAT/EYES. CHRONIC OVEREXPO MAY LEAD TO SIDEROSIS (IRON DEPOSITS IN LUNG), BELIEVED BY SOME INVESTIGATORS TO AFFECT PULM FUNCTION.

Explanation of Carcinogenicity:

PER MSDS: CARCINOGENICITY: NTP-NI, CR.

IARC-NI, CR. OSHA-CR. (IF INGREDIENTS CONTAIN THESE MATERIALS).

Effects of Overexposure: INJURY TO EYES, BURN TO SKIN. DEATH FROM

ELECTRIC SHOCK. DISCOMFORT, DIZZINESS, NAUSEA, DRYNESS, IRRITATION OF NOSE/THROAT/EYES. SIDEROSIS.

Medical Conditions Aggravated by Exposure: AGGRAVATION OF PRE-EXISTING

RESPIRATORY OR ALLERGIC CONDITIONS MAY OCCUR IN SOME WORKERS.

=====
===== First Aid Measures =====

First Aid: CALL FOR MEDICAL AID.

EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

=====
===== Fire Fighting Measures =====

Flash Point: NP

Autoignition Temp: Autoignition Temp Text: NP

Lower Limits: NP

Upper Limits: NP

Extinguishing Media: NON-FLAMMABLE.

Fire Fighting Procedures: NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard: WELDING ARC & SPARKS CAN IGNITE COMBUSTIBLES. SEE Z-49.1

=====
===== Handling and Storage =====

Handling and Storage Precautions:

MONITOR FUMES OF CR VI/NI/CU WHEN PRESENT IN INGREDIENTS. READ/UNDERSTAND MFG INSTRUCTIONS/PRECAUTION LABEL ON PRODUCT. REF: Z-49.1/OSHA 29CFR1910.

Other Precautions: ONE RECOMMENDED WAY TO DETERMINE COMP/QUANT OF FUMES/GASES WORKERS EXPOSED: TAKE AIR SAMPLE INSIDE WELDER'S HELMET/BREATH ZONE. SEE ANSI/AWS F1.1 FROM AMERICAN WELDING SOCIETY, PO BOX 351040, MIAMI, FL 33135. TRAIN WELDER NOT TO TOUCH LIVE ELECTRICAL PARTS/INSULATE FROM WORK/GROUND

=====
===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHASUT OR VNETILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:USE ENOUGH VENT/LOC EXHA @ARC/BOTH TO KEEP FUME/GAS BEL TLV IN WORKER BREATH ZONE/GEN AREA.TRAIN WELD KEEP HEAD OUT FUME

Protective Gloves:WELDERS GLOVES

Eye Protection:FCSHIELD W/FILT LEN,FLASH/SCREEN GOGG.

Other Protective Equipment:WEAR HELMET/HEAD/HAND/BODY PROT FRM RAD

IATION/SPARKS/ELECT SHOCK.ARM/SHOULDER PROT,APRONS,HATS,DARK SUBSTANTIAL CLOTH.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

DECOMPO:USED,COAT ON METAL,#OF WELDERS/VOL IN WORKAREA,QUAL/AMT OF VENTI,POSITION FO WLEDER HEAD W/RESPECT TO FUME PLUME,PRESENCE OF CONTAMIN IN ATM.ELECTRODE CONSUMED FUNE/GAS DECOMPO PROD DIFFERENT IN %/FORM FROM INGREDIENTS.REASONABLY EXPECT:FLUORIDES,COMPLEX OXIDES OF METALS IN PRODUCT,CO/CO2,OZONE,NITROGEN OXIDE

S.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NP

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:NP

Vapor Density:NP

Spec Gravity:NP

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NP

Solubility in Water:NP

Appearance and Odor:NP

Percent Volatiles by Volume:NP

Corrosion Rate:NP

===== Stability and Reactivity Data =====

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPEC

IFIED BY MANUFACTURER.

Hazardous Decomposition Products:WELDING FUMES CAN'T BE CLASSIFIED
SIMPLY.COPO/QUANT DEPENDENT UPON METAL BEING
WELDED/PROCESS/PROCEDURES/ELECTRODES(SUP)

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRO.DISCARD ANY PRODUCT RESIDUE/DISPOSABLE CNTNR/LINER IN ENVIRO
ACCEPTABLE MANNER IN FULL COMPLIANCE W/FED/STATE/LOC REGULATIONS.

Disclaimer (provided with this in
formation by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.