View NSN Online: https://aerobasegroup.de/nsn/5970-01-014-3480

MINNESOTA MINING AND MFG CO -- SCOTCHCAST BRAND ELECTRICAL RESIN 9 (5240), PART A -- 5970-01-014-3480

============= Product Identification ==================

Product ID:SCOTCHCAST BRAND ELECTRICAL RESIN 9 (5240), PART A

MSDS Date: 10/23/1989

FSC:5970

NIIN:01-014-3480

Kit Part:Y

MSDS Number: BZPJQ === Responsible Party ===

Company Name: MINNESOTA MINING AND MFG CO

Address:3M CTR 224-2S-25

City:ST. PAUL State:MN ZIP:55144

-1000

Country:US

Info Phone Num:612-733-1341/612-733-1110

Emergency Phone Num:612-733-1341

CAGE:76381

=== Contractor Identification ===

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

Company Name: MINNESOTA MINING AND MFG CO ELECTRICAL HANDLING/PROTECTION

Address:3M AUSTIN CTR

Box:City:AUSTIN

State:TX

ZIP:78769-1263 Country:US

Phone:512-733-1341

CAGE:20999 Compan y Name: SUMMIT ASSOCIATES

Address:10910-H SOUTHLAKE COURT

Box:City:RICHMOND

State:VA

ZIP:23236-3914 Country:US

Phone:804-794-1434

CAGE:9X866

======= Composition/Information on Ingredients ========

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOLYMER

CAS:25068-38-6 RTECS #:SL6475000 Fraction by Wt: 62-66%

Other REC Limits: NONE RECOMMENDED

Ingred Name:TALC (NON-ASBESTIFORM)

CAS:14807-96-6 RTECS #:MW2700000 Fraction by Wt: 15-20%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:0.2 FIBER/CC,A1;9596

Ingred Name:MICA - SILICATES (< 1% CRYSTALLINE SILICA)

CAS:12001-26-2 RTECS #:VV8760000 Fraction by Wt: 15-20%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:20 MPPCF; Z-3

ACGIH TLV:3 MG/M3 RDUST; 9596

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 0.1-1.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9596

Ingred Name: IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000 Fraction by Wt: 0.1-1.0%

Other REC Limits: NONE RECOM

MENDED OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5MG(FE)/M3FUME,B2;96
============ Hazards Identification =============
LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PART A:MAY BE EYE/SKIN IRRIT ON DIRECT CONTACT.MAY CAUSE SKIN SENS IN SOME SUSCEPTIBLE PEOPLE.PART B:CAUSES EYE IRRIT.MAY BE HARMFUL IF ABSORBED THRU SKIN.MAY CAUSE
SKIN SENS IN SOME SUSCEPTIBLE PEOPL E.MIXTURE:EYE/SKIN IRRIT.SKIN SENS IN SOME SUSCEPTIBLE PEOPLE.INHAL:RESP SYS IRRIT.RESP SENS IN SOME SUSCEPTIBLE (SUPPL) Explanation of Carcinogenicity:PER MSDS:IARC STATES AVAILABLE DATA ON CARBON BLACKS INADEQUATE TO PERMIT EVALUATION OF CARCINO TO EXPERIMENTAL ANIMALS. Effects of Overexposure:RESP SYS/EYE/SKIN DIGESTIVE SYSTEM IRRITATION. TISSUE OR DIGESTIVE SYS DMG. SKIN SENSITIZATION IN SOME SUSCEPTIBLE INDIVIDUALS. HARMFUL IF ABS ORBED THRU SKIN.
Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:EYE:IMMED FLUSH W/LG AMTS OF WATER.CONTINUE FOR @LEAST 10MINS.CALL PHYSICIAN. SKIN:WASH AFFECTED AREA THOROUGHLY W/ SOAP/WATER. INHAL:PROVIDE FRESH AIR.IF COUGHING/WHEEZING/SHORTNESS OF BREATH DEVELOP CALL PHYSICIAN. SWALLOWED:GIVE ONE TO TWO GLASS OF WATER. CALL PHYSICIAN.
======================================
Flash Point Method:SCC Flash Point:>350F,>177C Autoignition Temp:Autoignition Temp Text:ND Lower Limits:ND Upper Limits:ND Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMCIAL. Fire Fighting Procedures:FIREFIGHTERS SHOULD BE EQUIPPED W/SELF-

CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

======== Accidental Release Measures ===============

Spill Release Procedures: PART A OR PART B: OBSERVE PRECAUTIONARY INFO FROM OTHER SEC

TIONS.USE ABSORBENT MATL AS NEEDED & SWEEP UP.MIXTURE OF PART A/PART B:OBSERVE PRECAUTIONARY INFO FORM OTHER SECTIONS.CLEAN UP SPILL. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. =========== Handling and Storage ============================ Handling and Storage Precautions: AVOID EYE/SKIN CONTACT. WHEN HNDLG PROD WEAR SAF GOGG/PROT CLOTH/IMPERV GLOVES.USE IN WELL VENTILATED AREA.AVOID BREATH VAP. Other Precautions: DO NOT BREATH VAP OF HEATED MIXTURES. USE EXHAUST ENTI FOR MIX/POUR/CURE PROCESSES.COOL DOWN AREA SHOULD BE VENTILATED TO PREVENT VAP FROM ENTERING WORKAREA. EXPOSURE TO CARBON BLACK IS NOT EXPECTED IN USE/HNDLG OF PRODUCT. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: WHERE VENTILATION IS INSUFFICIENT USE NIOSH APPROVED RESP W/ORG VAP CARTRIDGES. Ventilation: USE EXHAUST VENTILATION FOR MIXING, POURING, CURING PROCESSES. Protective Gloves: IMPERVIOUS GLOVES. Eye Protection: SAFETY GOGG LES. Other Protective Equipment: PROTECTIVE CLOTHING. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health KEY1; V5. HEALTH HAZ: PEOPLE. INGEST: MAY IRRIT DIGESTIVE SYS. MAY CAUSE TISSUE OR DIGESTIVE SYS DMG. 2-PART KIT, PNIND:B FOR PART B. NOTE:1 MSDS SUBMITTED FOR PART A/B FRM MFG.

======== Physical/Chemical Properties ==========

HCC:B2
Boiling Pt:B.P. Text:NA
Melt/Freeze Pt:M.P/F.P Text:NP
Decomp Temp:Decomp Text:NP
Vapor Pres:NA
Vapor D

ensity:NA
Spec Gravity:1.45
pH:NA

Viscosity:900P Evaporation Rate & Deference: NA

Solubility in Water:NIL

Appearance and Odor:RED VISCOUS LIQUID.

Percent Volatiles by Volume:0

Corrosion Rate:NP

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:MAY INCLUDE CARBON MONOXIDE, CARBON DIOXIDE & OXIDES OF NITROGEN.

Disposal Considerations ==========

Waste Disposal Methods:PART A OR PART B:DISPO BY INCINERATIN OR SEND FULLY ADSORBED MATL FOR LANDFILL IAW LOC/STATE REGS.MIXTURE OF PART A/PART B:FULLY CURED MATL MAY BE LANDFILLED IAW LOC/STATE REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.