View NSN Online: https://aerobasegroup.de/nsn/1560-01-334-9850

SCHULLER INTL INC (FORMALLY MANVILLE SALES CORP) -- FIBER GLASS INSULATION (FIBER GLASS WOOL PRODUCT) -- 1560-01-334-9850

Product ID:FIBER GLASS INSULATION (FIBER GLASS WOOL PRODUCT) MSDS Date:09/13/1995 FSC:1560 NIIN:01-334-9850 MSDS Number: BZPMM === Responsible Party === Company Name:SCHULLER INTL INC (FORMALLY MANVILLE SALES CORP) Address:717 17TH ST Box:5108

City:LITTLETON (FORMALLY IN DENVER, CO) State:CO ZIP:80127 Country:US Info Phone Num:303-978-4900/-2000 Emergency Phone Num:800-424-9300(CHEMTREC) Preparer's Name: (MSDS #:1009-4.3) CAGE:GO563 === Contractor Identification === Company Name: BARTELS DIAGNOSTICS DIV OF BAXTER Address:2005 NW SAMMANISH RD STE 107 City:ISSAQUAH State:WA ZIP:98027 Country:US Phone:800-BARTELS CAGE:BARTE Company Name:SCHULLER INTERNATIONAL INC. Address:Box:5108 **City:DENVER** State:CO ZIP:80217-5108 Country:US Phone:303-9

78-4900 CAGE:75165 Company Name:SCHULLER INTL INC Address:717 17TH ST Box:5108 **City:DENVER** State:CO ZIP:80202-5000 Country:US Phone:303-978-4900 CAGE:GO563 Ingred Name: FIBERGLASS WOOL CAS:65997-17-3 Fraction by Wt: 50-98% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 RESP DUST ACGIH TLV:10 MG/M3 (177C/350F)MAY RELEASE GASES IRRIT EYE/NOSE/THROAT DURING INITIAL HEATUP.IN TIGHTLY CONFINED/POORLY VENTI AREA SUE AIR SUPPLIED RESP DURING 1ST HEATUP CYCLES.REPAIR /MAINT:USE PPE.VACUUM EQPMT BEF REPAIR. Respiratory Protection: NIOSH-APPROVED DUST/MIST RESP PROTECT AGAINST NUISANCE DUST/FIBERS.(EX:3M 9900, MOLDEX 2200 RESP).SAW/BLOW/TEAR OUT/SPRAY REQUIRE HIGHER LEVEL RESP PROT.EXPO EXCEED 10X EXTABLISHED EXPO LIMITS USE NIOS H APPROVED 1/2MASK RESP W/HEPA (SUPPLE) Ventilation:LOC EXHAU @CUTTING AREAS.GEN DIL VENTI.NEED FOR VENTI EVALUATED BY PROF INDUST HYG, DESIGN OF SPEC VENTI BY PROF ENGINEER Protective Gloves: LEATHER/COTTON GLVS, BARRIER CREAMS. Eye Protection: SAF GLASS W/SIDESHIELDS RECOMMENDED. Other Protective Equipment: PROT EPMT SHOULD BE PROVIDED AS NECESARY TO PREVENT IRRIT THROAT/EYE/SKIN/KEEP EXPO BEL APPLICABLE EXPO LIMITS.(SUPPLE) Work Hygienic Practices: WASH HANDS BEF EATING/USING RESTROOM. Supplemental Safety and Health APPEARANCE: OR W/O NON-WOVEN/VINYL FACINGS; NO SIGNIFICANT ODOR. 1S

TAID:W/SYMPTOMATIC TREATMENT AS NECESSARY. RESP:CARTRIDGES,SURVIVAIR 1/2MASK W/#1090-00 CARTRIDGES. PROT EQPT:LOOSE-FIT LONG SLEEV CLOT H.WASH CLOTH SEPARAETLY FROM OTHER.WASHER SHOULD BE RINSED THOROUGHLY-REDUCE FIBER GLASS TRANSF TO OTHER CLOTH.

HCC:N1 Boiling Pt:B.P. Text:ND Melt/Freeze Pt:M.P/F.P Text:>1299F,>704 Decomp Temp:Decomp Text:NP Vapor Pres:NA Vapor Density:NA Spec Gravity:VARIABLE pH:NA Viscosit y:NA Evaporation Rate & amp; Reference:NA (N-BUTYL ACETATE=1) Solubility in Water:NIL Appearance and Odor: GOLD-TO-YELLOW OR BLACK FIBROUS GLASS BLANKET, BOARD, FORMED SHAPES W/(SUPPLEMENT Percent Volatiles by Volume:0 **Corrosion Rate:NP**

Stability Indicator/Materials to Avoid:YES THIS PRODUCT IS NOT REACTIVE. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:PROD EXPECTED FROM ANY

ORG(CARBON-CONTAINING)MATL.MAINLY DERIVED FRM RESIN PYRO/BURN.CO2,CL,CARBON PART,HCHO,TRACES HCN.

Waste Disposal Methods:WASTES NOT HAZ PER RCRA.COMPLY W/STATE/LOCAL REG FOR DISPOSAL OF FIBER GLASS WOOL PRODUCTS.IF UNSURE OF REGS CONTACT LOCAL PUBLIC HEALTH DEPT/LOC OFC OF EPA.COMPLY W/STATE/LOC REG FOR DISPOSAL.NO CHEM REG BY SARA SEC 313,CERCLA,TXCA12(B).

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.