

PRAXAIR SURFACE TECHNOL INC SPECIALTY POWDERS BUSI -- 036022-10 NI-122 --
3439-01-426-3231

===== Product Identification =====

Product ID:036022-10 NI-122

MSDS Date:06/22/1994

FSC:3439

NIIN:01-426-3231

MSDS Number: BZXWR

=== Responsible Party ===

Company Name:PRAXAIR SURFACE TECHNOL INC SPECIALTY POWDERS BUSI

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Info Phone N

um:317-240-2650

Emergency Phone Num:317-240-2209

Preparer's Name:MICHELLE ALEXANDER

CAGE:GO132

=== Contractor Identification ===

Company Name:PRAXAIR SURFACE TECHNOL INC SPECIALTY POWDERS BUSI

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:GO132

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

===== Composition/Information o

n Ingredients =====

Ingred Name:NICKEL (SUSPECTED ANIMAL/HUMAN CARCINOGEN BY IARC GROUP 2B,
SUSPECTED CARCINOGEN BY NTP) *96-2*

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 50-75%

Other REC Limits:1 MG/CUM

OSHA PEL:1 MG/CUM

ACGIH TLV:0.05 MG/CUM IC

Ingred Name:CHROMIUM METAL, CHROMIUM, CHROME (KNOWN CARCINOGEN BY NTP;
IARC CARC - GROUP 3) *96-2*

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 5-20%

ACGIH TLV:0.5 MG/CUM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ALU

MINUM *96-2*

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 5-20%

OSHA PEL:15 MG/CUM

ACGIH TLV:10 MG/CUM (DUST)

Ingred Name:SILICON

CAS:7440-21-3

RTECS #:VW0400000

Fraction by Wt: 1-5%

ACGIH TLV:10 MG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SKIN: ALLERGIC DERMATITIS, PAPULAR
FORMATION IN SUSCEPTABLE INDIVIDUALS,

MAY CAUSE ULCERS. EYES:

IRRITATION W/REDNESS OF THE CONJUNCTIVA. INGESTION: CNS DEPRESSION/BURNING SENSATION. INHALATION: RESPIRATORY TRACT IRRITANT & SENSITIZATION, BURNING SENSATION, CNS DEPRESSION, INTERSTITIAL PNEUMONITIS. (SEE SUPP)

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:REDNESS, DRY/SCALY SKIN, IRRITATION, NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, BURNING SENSATION, CHEST PAIN, LESIONS, ITCHING, SORENESS

Medical Cond Aggravated b

y Exposure:ASTHMA & INFLAMMATORY/FIBROTIC PULMONARY DISEASE. EXISTING DERMATITIS.

=====
===== First Aid Measures =====

First Aid:INGESTION: GIVE 2 GLASSES OF MILK/WATER. INDUCE VOMITING IF CONSCIOUS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NECESSARY. EYES: FLUSH THOROUGHLY W/PLENTY OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES. NOTES TO PHYSICIAN: NO SPECIFIC ANTIDOTE. TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS & THE CLINICAL CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:DRY POWDER METAL EXTINGUISHING MATERIAL FOR METAL FIRES. USE APPROPRIATE EXTINGUISHER FOR COMBUSTIBLE MATERIALS.

Fire Fighting Procedures:USE NFPA51 OXYGEN-FUEL GAS SYSTEMS FOR WELDING & CUTTING & NFPA58 STANDARD FOR THE STORAGE & HANDLING OF LIQUIDIFIED PETROLEUM GASES.

Unusual Fire/Explosion Hazard:

AIRBORNE DUST PARTICLES; METAL DUST & ACCUMULATION SHOULD BE TREATED AS EXPLOSIVES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST HAZARDS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:WHEN THERMAL SPRAYING-ELECTRICITY CAN CAUSE FATAL SHOCK. DON'T TOUCH LIVE ELECTRICAL PARTS. WEAR RECOMMENDED EYE & BODY PROTECTION.

Other Precautions:

ions:ARC RAYS CAN BURN EYES. FUMES, GAS & DUST CAN HARM YOUR HEALTH. PROVIDE VENTILATION & WEAR RESPIRATOR IF REQUIRED. ALWAYS SPRAY W/ENOUGH VENTILATION. AREA & SPARKS DURING SPRAYING CAN BE A SOURCE OF IGNITION OF COMBUSTIBLE MATERIALS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF THERE IS DUSTINESS, WEAR RESPIRATOR SELECTED PER OSHA 1910.134 & OSHA 29 CFR 1910.252 & ANSI Z49.1.

Ventilation:LOCAL DUST PICK UP & VENTILATION RECOMMENDED.

Protective Gloves:NOT REQUIRED

Eye Protection:WHEN DUSTY, USE GOGGLES PER OSHA 1910.13

Supplemental Safety and Health

CHRONIC EXPOSURE CAN CAUSE CORNEAL DAMAGE, POLYCYTHEMIA, HYPERPLASIA OF THE THYROID GLAND & DAMAGE TO THE ALPHA CELLS OF THE PANCREAS.

REPEATED INHALATION MAY CAUSE EMPHYSEMA/PULMONARY FIBROTIC DISEASE.

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NONE

Appearance and Odor:DUSTY YELLOW GRAY POWDER

Percent

Volatiles by Volume:0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:ELECTRICAL PARTS/EQUIPMENT, ARC RAYS

Hazardous Decomposition Products:OXIDES, SUB-OXIDES & COMPLEX OXIDES OF MATERIALS

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.