

PRAXAIR SURFACE TECHNOL INC SPECIALTY POWDERS BUSI -- NI-365-3 -- 3439-01-426-5241
===== Product Identification =====

Product ID:NI-365-3

MSDS Date:01/27/1995

FSC:3439

NIIN:01-426-5241

MSDS Number: BZXWS

=== Responsible Party ===

Company Name:PRAXAIR SURFACE TECHNOL INC SPECIALTY POWDERS BUSI

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Info Phone Num:317-240-2650

Emergency Phone Num:317-240-2209

Preparer's Name:MICHELLE ALEXANDER

CAGE:GO132

=== Contractor Identification ===

Company Name:PRAXAIR SURFACE TECHNOL INC SPECIALTY POWDERS BUSI

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:GO132

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

===== Composition/Information on Ingredients =

=====

Ingred Name:NICKEL (SUSPECTED ANIMAL/HUMAN CARCINOGEN BY IARC GROUP 2B,
SUSPECTED CARCINOGEN BY NTP) *96-2*

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 50-75%

Other REC Limits:1 MG/CUM

OSHA PEL:1 MG/CUM

ACGIH TLV:0.05 MG/CUM IC

Ingred Name:COBALT (ANIMAL CARCINOGEN BY IARC - GROUP 2B) *96-2*

CAS:7440-48-4

RTECS #:GF8750000

Fraction by Wt: 5-20%

Other REC Limits:0.05 PPM

OSHA PEL:0.1 MG/CUM

ACGIH TLV:0.05 MG/CUM

Ingred Name:CHROMIUM METAL, CHROMIUM, CHROME (KNOWN CAR
CINOGEN BY NTP;

IARC CARC - GROUP 3) *96-2*

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 5-20%

ACGIH TLV:0.5 MG/CUM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TANTALUM

CAS:7440-25-7

RTECS #:WW5505000

Fraction by Wt: 5-20%

OSHA PEL:5 MG/CUM

ACGIH TLV:5 MG/CUM

Ingred Name:ALUMINUM *96-2*

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 5-20%

OSHA PEL:15 MG/CUM

ACGIH TLV:10 MG/CUM (DUST)

Ingred Name:TUNGSTEN (INSOLUBLE), WOLFRAM *96-2*

CAS:7440-33-7

RTECS #:YO7175000

Fraction by Wt:

1-5%
ACGIH TLV:5 MG/CUM

Ingred Name:RHENIUM
CAS:7440-15-5
Fraction by Wt: 1-5%

Ingred Name:MOLYBDENUM (SOLUBLE COMPOUND)
CAS:7439-98-7
RTECS #:QA4680000
Fraction by Wt: 1-5%
OSHA PEL:5 MG/CUM
ACGIH TLV:5 MG/CUM

Ingred Name:HAFNIUM
CAS:7440-58-6
RTECS #:MG4600000
Fraction by Wt: 1-5%
OSHA PEL:0.5 MG/CUM
ACGIH TLV:0.5 MG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:Y
ES OSHA:NO

Health Hazards Acute and Chronic:SKIN: ALLERGIC DERMATITIS W/PAPULAR
FORMATION IN SUSCEPTABLE INDIVIDUALS. EYES: IRRITATION & REDNESS OF
THE CONJUNCTIVA, CORNEAL DAMAGE BY OVEREXPOSURE. INHALATION:
RESPIRATORY TRACT IRRITANT. BURNING SENSATION, CNS DEPRESSION,
INTERSTITIAL PNEUMONITIS & SENSITIZATION. INGESTION: CNS DEPRESSION
& BURNING SENSATION.(SUP

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:REDNESS, DRY/SCALY SKIN, FEVER, IRRITATI
ON,

NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, BURNING SENSATION,
CHEST PAIN, POLYCYTHEMIA, HYPERPLASIA OF THE THYROID GLAND,
LESIONS, ITCHING, SORENESS

Medical Cond Aggravated by Exposure:ASTHMA & INFLAMMATORY/FIBROTIC
PULMONARY DISEASE. EXISTING DERMATITIS.

===== First Aid Measures =====

First Aid:INGESTION: GIVE 2 GLASSES OF MILK/WATER. INDUCE VOMITING IF
CONSCIOUS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE
TO FRE

SH AIR. GIVE CPR/OXYGEN IF NECESSARY. EYES: FLUSH THOROUGHLY
W/PLE NTY OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES. NO
SPECIFIC ANTIDOTE. TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF
SYMPTOMS & THE CLINICAL CONDITION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:NONE

Upper Limits:0

Extinguishing Media:DRY POWDER METAL EXTINGUISHING MATERIAL FOR METAL
FIRES. APPROPRIATE EXTINGUISHER FOR COMBUSTIBLE MATERIALS

Fire Fighti

ng Procedures:USE NFPA51 OXYGEN FUEL GAS SYSTEMS FOR WELDING
& CUTTING. NFPA58 STANDARD FOR THE STORAGE & HANDLING OF LIQUIFIED
PETROLEUM GASES.

Unusual Fire/Explosion Hazard:AIRBORNE DUST PARTICLES & ACCUMULATION
SHOULD BE TREATED AS EXPLOSIVES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST
HAZARDS & DISPOSE OF PER WASTE DISPOSAL METHOD.

=====
===== Handling and Storage ===
=====

Other Precautions:ELECTRICITY CAN CAUSE FATAL SHOCK. DON'T TOUCH LIVE
ELECTRICAL PARTS. ARC RAYS CAN BURN EYES/SKIN. FUMES/GAS/DUST CAN
HARM YOUR HEALTH. AREA & SPARKS DURING SPRAYING CAN BE A SOURCE OF
IGNITION OF COM BUSTIBLE MATERIALS. PREVENT FIRES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF THERE IS DUSTINESS, WEAR RESPIRATOR SELECTED
PER OSHA 1910.134, & OSHA 29 CFR 1910.252 & ANSI Z49.1.

Ventilation:

LOCAL DUST PICK UP & VENTILATION RECOMMENDED

Protective Gloves:NOT REQUIRED

Eye Protection:GOGGLES PER OSHA 1910.13.

Other Protective Equipment:ANSI Z49.1, ANSI Z87.1, ANSI Z88, FOR
HELMETS, FACE SHIELDS & GOGGLES.

Supplemental Safety and Health

OVEREXPOSURE MAY CAUSE SENSITIZATION IN SUSCEPTABLE INDIVIDUALS. CAN
CAUSE POLYCYTHEMIA, HYPERPLASIA OF THE THYROID GLAND & DAMAGE TO
THE ALPHA CELLS OF THE PANCREAS. REPEATED INHALATION CAN CAUSE EMP
HYSEMA/PULMONARY FIBROTIC DISEASE.

=

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NONE

Vapor Density:>1

Appearance and Odor:GRAY POWDER

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:ACCUMULATION OF DUST PARTICLES, ARC RAYS,
SPARKS & OTHER IGNITION SOURCES

Hazardous Decomposition Products:BY THERMAL SPRAYING: OXIDES,
SUB-OXIDES & COMPLEX OXIDES OF MATERIALS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing
this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.