

AMERICAN ABRASIVE METALS CO -- NON-SKID DECK COATING EPOXO 2000X -- 5610-00-006-1546
===== Product Identification =====

Product ID:NON-SKID DECK COATING EPOXO 2000X

MSDS Date:10/29/1986

FSC:5610

NIIN:00-006-1546

Kit Part:Y

MSDS Number: CBQBV

=== Responsible Party ===

Company Name:AMERICAN ABRASIVE METALS CO

Address:460 COIT STOCK AVE

City:IRVINGTON

State:NJ

ZIP:07111

Country:US

Info Phone Num:201

-373-7060

Emergency Phone Num:201-373-7060

CAGE:88444

=== Contractor Identification ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

Box:City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:973-403-2600

CAGE:88444

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOLYMER; (EPOXY RESINS)

CAS:25068-38-6

RTECS #:SL6475000

Fraction by Wt: 12+/-1%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:XYLENE

CAS:1330-20-7

RTEC

S #:ZE2100000
Fraction by Wt: 10+/-1%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-PROPANOL, 1-METHOXY-; (PROPYLENE GLYCOL MONOMETHYL ETHER)
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 1%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL

Ingred Name:SILICA, CRYSTALLINE - QUARTZ; (SILICON DIOXIDE,
CRYSTALLINE)
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 20%
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:0.1 MG/M3 RDUST

=====
Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION:DIZZINESS, UNCONSCIOUSNESS.
SKIN CONTACT:IRRITATION. EYE CONTACT:IRRITATION, EYE DAMAGE.
Explanation of Carcinogenicity:SILICA, CRYSTALLINE-QUARTZ:IARC
MONOGRAPHS, SUPP. VOL 7, PG 341, 1987:GROUP 2A. NTP 7TH ANNUAL RPT
ON CARCINS. (SUPDAT)
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES, SKIN
CONDITIONS, KIDNEY OR LIVER DISEASES.

=====
First Aid Measures =====

First Aid:INHALATION:FRESH AIR, OXYGEN, ARTIFICIAL RESPIRATION.
SKIN:WASH WITH SOAP AND WATER. EYES:FLUSH WITH LARGE AMOUNTS OF
WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION:DO
NOT INDUCE VOMITING. CALL PHYSICIAN.

=====
Fire Fighti

ng Measures =====

Flash Point Method:PMCC

Flash Point:81.0F,27.2C

Lower Limits:1%

Upper Limits:12%

Extinguishing Media:CHEMICAL FOAM OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR; MAY TRAVEL ALONG GROUND AND BE IGNITED BY FLAMES, SPARKS OR OTHER IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedur

es:ELIMINATE ALL IGNITION SOURCES (FLAMES, FLARES, PILOT LIGHTS, ELECTRICAL SPARKS).

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:WARNING! IRRITANT:DO NOT GET INTO EYES. AVOID CONTACT WITH SKIN AND CLOTHING. AVOID INHALATION OF VAPOR OR MIST. USE WITH ADEQUATE VENTILATION.

Other Precautions:AVOID EXTREME HEAT-KEEP AWAY FROM FLAMES. DO NOT EXCEED 110F IN STORAGE AREA.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV'S ARE EXCEEDED, NIOSH/MSHA APPROVED SELF CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST:SUFFICIENT TO MAINTAIN LEVEL BELOW TLV.

Protective Gloves:RUBBER OR BUNA N GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS(SUPDAT)

Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE SHOWER . TO PVNT RPTD/PRLNGD SKIN CONT, WEAR PROTECTIVE CLOTHING.

Work Hygienic Practices

:WASH THOROUGHLY AFTER HANDLING, AND BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAM CLTHG & WASH BEFORE RE-USE.

Supplemental Safety and Health

EXPLAN OF CARCIN:1994:ANTICIPATED TO BE CARCINOGEN. ANIMAL:LUNG. EYE PROT:AND FULL LENGTH FACE SHIELD .

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>240F,>116C

Vapor Pres:8 @ 68F

Vapor Density:3.7

Spec Gravity:2.1 (H*2O=1)

Evaporation Rate & Reference:0.7 (BUTYL ACETATE=1)

Solubility in Wa

ter:SLIGHT

Appearance and Odor:VISCIOUS PASTE, MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CO*2, CO, NO*X AND TOXIC FUMES WHEN BURNING.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS

. ABSORB ON SAND, CLAY OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINERS. DISPOSE BY CONTROLLED BURNING OR AUTHORIZED LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.