

ARCOS ALLOYS DIV HOSKINS MFG CO -- BARE-WIRE FILLER METALS, MS-2 -- 3439-01-050-1655

=====
Product Identification
=====

Product ID:BARE-WIRE FILLER METALS, MS-2

MSDS Date:05/01/1994

FSC:3439

NIIN:01-050-1655

MSDS Number: CBQPF

=== Responsible Party ===

Company Name:ARCOS ALLOYS DIV HOSKINS MFG CO

Address:1 ARCOS DR

City:MT CARMEL

State:PA

ZIP:17851

Country:US

Info Phone Num:717-339-5200

Emergency

Phone Num:800-424-9300(CHEMTREC)

CAGE:03805

=== Contractor Identification ===

Company Name:ARCOS ALLOYS DIV OF HOSKINS MFG CO

Address:#1 ARCOS DRIVE

Box:308

City:MTCARMEL

State:PA

ZIP:17851

Country:US

Phone:717-339-5200, CHEMTREC 800-424-9300

CAGE:03805

Company Name:ARCOS ALLOYS DIVISION OF HOSKINS MFG. CO.

Address:#1 ARCOS DRIVE

Box:City:MT CARMEL

State:PA

ZIP:17851

Country:US

Phone:570-339-5200; 717-339-5200

CAGE:19270

=====
Composition/Information on Ingredients
=====

Ingr

ed Name:IRON, ION (FE2+); (FE)
CAS:15438-31-0
Fraction by Wt: BALANCE
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5MG(FE)/M3FUME,B2;95

Ingred Name:CHROMIUM; (CR) (SARA 313) (CERCLA)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 0.1%
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9495
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MANGANESE; (MN) (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1.0%
OSHA PEL:C 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name:NICKEL; (NI) (SARA 313) (CERCLA)
CAS:744
0-02-0
RTECS #:QR5950000
Fraction by Wt: 0.1%
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9495

Ingred Name:SUPDAT:OXIDES OF THE METALS, CHROMATES & COMPLEX METALLICS.
GASEOUS RXN PRODS MAY INCL CARBON MONOXIDE, OZONE & (ING 6)
RTECS #:9999999ZZ

Ingred Name:ING 5:NITROGEN OXIDES. CHLORINATED SOLVS MAY BE DECOMPOSED
INTO TOXIC GASES SUCH AS PHOSGENE. WHEN THE ELECTRODES(ING 7)
RTECS #:9999999ZZ

Ingred Name:ING 6:ARE CONSUMED, THE FUME & GAS DECOMP PRODS GENERATED
ARE DIFFERENT IN FORM FROM

THE INGREDIENTS LISTED. (ING 8)
RTECS #:9999999ZZ

Ingred Name:ING 7:NEW COMPOUNDS MAY FORM INCLUDING:ALUMINUM FUMES, CARBON MONOXIDE, CHROMIUM, CHROMIUM (CHROMATES), (ING 9)
RTECS #:9999999ZZ

Ingred Name:ING 8:COBALT FUME (CO), COPPER FUME (CU), IRON OXIDE FUME (AS FE), MANGANESE FUME (MN), MOLYBDENUM (MO) (ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9:(SOLUBLE), NICKEL (NI) (SOLUBLE), TUNGSTEN (W) (SOLUBLE), NITROGEN DIOXIDE, OZONE, AND PHOSGENE.
RTECS #:9999999ZZ

Ingred Name:EFFECTS OF OXIDES
REASON:FORMING THE BASIS FOR THIS CLASSIFICATION
WERE FROM OPERATIONS OTHER THAN WELDING OF CHROMIUM (ING 12)
RTECS #:9999999ZZ

Ingred Name:ING 11:OR NICKEL. THERE IS CONSIDERABLE CONTROVERSY ON THE EXTENT OF THE RESPIRATORY CANCER PROBLEMS DUE TO NICKEL & (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12:CHROMIUM. NEVERTHELESS EXPOSURES MUST BE MAINTAINED BELOW THE LEVELS SPECIFIED IN INGREDIENTS & HAZARD DECOMPOSITION (ING 14)
RTECS #:9999999ZZ

Ingred Name:ING 13:PRODUCTION SECTIONS. ELECTRIC ARC RAYS CAN INJURE EYES AND BURN SKIN.
RTECS #:9999999ZZ

Ingred Name:MEDICAL CONDITIONS:WIDE VARIATION IN INDIVIDUAL SUSCEPTIBILITIES.
RTECS #:9999999ZZ

Ingred Name:RESPIRATORY PROTECTION:DETERMINING BREATHING ZONE TO DETERMINE IF A RESPIRATOR IS REQUIRED & THE TYPE NEEDED. USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.
RTECS #:9999999ZZ

Ingred Name:VENTILATION:KEEP EXPOSURE BELOW THE LIMITS SPECIFIED IN INGREDIENTS AND HAZARD DECOMPOSITION PRODUCTION SECTION.
RTECS #:9999999ZZ

Ingred Name:EYE PROTECTION:AND/OR FACE SHIELD WHEN CUTTING, GRINDING/WELDING. IN ADDITION, WEAR

EN HOT CUTTING/WELDING, WEAR WELDING (ING 19)

RTECS #:9999999ZZ

Ingred Name:ING 18:HELMET/FACE SHIELD W/FILTER LENS. SELECT WELDING
LENS SHADE FROM AMERICAN WELDING SOCIETY (AWS) PUBLICATION F2.2.

RTECS #:9999999ZZ

Ingred Name:OTHER PROT EQUIP:/WELDING. DO NOT EXPOSE SKIN TO RADIA WHEN
HOT CUTTING/WELDING. PROVIDE PROT SCREENS TO SHIELD OTHERS.

RTECS #:9999999ZZ

Ingred Name:EXPLAN OF CARCIN:GROUP 2B. NTP 7TH ANNUAL REPORT ON
CARCINOGENS, 1994: ANTICIPATED TO BE CARCINOGEN.

RTECS #

:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE: GASES OR DUST MAY RESULT IN
DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR
IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE
NOTED. ACUTE EXPOSURE CAN RESULT IN THE SAME SYMP

TOMS EXCEPT TO A

GREATER DEGREE AS WELL AS WATERY EYES, HEADACHE, BREATHING
DIFFICULTY, (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NICKEL:IARC MONOGRAPHS ON THE EVALUATION
OF CARCINOGENIC RISK OF CHEMICALS TO MAN: VOL 49, PG 257, 1990:
(ING 21)

Effects of Overexposure:HLTH HAZ:FREQUENT COUGHING &/CHEST PAINS. SOME
TOX GASES MAY CAUSE PULM EDEMA, ASPHYXIATION & EXCESSIVE EXPOS CAN
BE FATAL. CHRONIC:MAY RESULT IN NEUROLOGICAL DMG, LUNG FIBROSIS,
PNEUMOCONIOSIS & O

THE R LUNG DISEASES. NICKEL & CHROMIUM ARE
CONSIDERED POSS CARCINOGENS UNDER OSHA (29CFR 1910.1200). THE
STUDIES (ING 11)

Medical Cond Aggravated by Exposure:SOME WORKERS MAY EXPERIENCE
DISCOMFORT AT CONCENTRATIONS BELOW THE THRESHOLD LIMIT VALUES AND
OTHERS MAY BE AFFECTED BY A PRE-EXISTING CONDITION OR OTHER
OCCUPATIONAL ILLNESS BECAUSE OF THE (ING 15)

===== First Aid Measures =====

First Aid:IN CASE OF ELEC SHOCK, TURN OFF POWER PRIO

R TO REMOVAL FROM

EXPOS AREA & ADMIN OF FIRST AID. INHAL:REMOVE TO FRESH AIR. IF BRTHG IS DFCLT ADMINISTER OXYGEN. IF NOT BRTHG BEGIN ARTF RESP. IF NO DETECTA BLE PULSE BEGIN EXTERNAL HEART MASSAGE.SKIN:WASH AFFECTED AREA W/SOAP & H*2O. EYES:FLUSH W/LRG AMTS OF FRESH H*2O FOR AT LEAST 15 MIN. INGEST:SEEK MED ATTN. IN ALL CASES, SEEK MED ATTN FOR FIRST AID.

=====
Fire Fighting Measures
=====

Flash Point:NONFLAMMABLE

Extinguishing Media:M

EDIA SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONFLAMMABLE; HOWEVER, ARCS, SPARKS AND MOLTEN METAL CAN IGNITE FLAMMABLES AND COMBUSTIBLES OR CAUSE EXPLOSION.

=====
Accidental Release Measures
=====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DEPARTMENT OF TRANSPORTATION (DOT) APROVED CONTAINERS AN

D DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AV OID INHALATION AND SKIN EXPOSURE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING. PROVIDE PROTECTIVE SCREENS TO SHIEL

D

OTHERS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE WELD FUME RESP/AIR SUPPLIED RESP WHEN CUTTING, GRINDING/WELDING IN A CONFINED SPACE/WHERE LOC EXHAUST/GEN VENT DOES NOT KEEP EXPOS BELOW REC LIMS. MONITOR THE AIR QUALITY INSIDE THE WELDER'S HELME T, IF WORN, &/THE WORKER'S (ING 16)

Ventilation:USE ENOUGH VENT WHEN CUTTING, GRINDING/WELDING TO KEEP DUST, FUMES & GASES FROM WORKERS BRTHG ZONE & GEN AREA. (ING 17)

Protecti

ve Gloves:IMPERVIOUS GLOVES .

Eye Protection:USE OSHA APPRVD GOGGLES, GLASSES(ING 18)

Other Protective Equipment:ANSI APPRVD EMER EYE WASH & DELUGE SHOWER .

WEAR GLOVES & FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING (ING 20)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

HAZ DECOMP PROD:METAL BEING WELDED, THE PROCEDURES, PROCESSES & TYPE OF WIRE/ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THE PRESENCE OF CONTAMS IN THE ATM. DECOMP PR

ODS FROM THE WELDING/CUTTING OP

ERATION INCL THOSE FROM THE VOLATILIZATION, REACTION &/OXIDATION OF THE MATLS IN INGRED SECTION & MAY INCL (ING 5)

===== Physical/Chemical Properties =====

HCC:T6

Appearance and Odor:BARE FILLER METALS ARE SOLID WIRE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazard

ous Decomposition Products:WELDING & HOT CUTTING FUMES & GASES

CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION & QTY ARE DEPENDENT ON THE (SUPDAT)

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States o

f America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.