

IPS CORP -- WELD-ON 16 FOR ACRYLIC

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 01-197-6062
MSDS Date: 01/01/1994
MSDS Num: CBQTB
Product ID: WELD-ON 16 FOR ACRYLIC
MFN: 02
Responsible Party
Cage: EO483
Name: IPS CORP
Address: 17109 S MAIN ST
Box: 379
City: GARDENA CA 90248
Info Phone Number: 310-366-3300
Emergency Phone Number: 213-222-3212;800-424-9300(CHEMTREC)
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: EO483
Name: IPS CORP
Address: 17109 S MAIN
Box: 379
City: GARDENA CA 90248-5000
Phone: 213-321-6515/213484-5151
Cage: 17510
Name: IPS CORPORATION
Address: 17109 S. MAIN ST.,
Box: 379
City: GARDENA CA 90248
Phone: 310-898-3300

=====
Item Description Information
=====

Item Name: ACRYLIC

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFAC

TURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: NO

Effects of Exposure: CHLOROCARBON MATLS HAVE PRDCED SENSIT OF MYOCARDIUM TO EPINEPHRINE IN LAB ANIMALS & COULD HAVE A SIMILAR EFT IN HUMANS.

ADRENOMIMETICS (E.G. EPINEPHRINE) MAY BE CONTRAINDICATED EXCEPT FOR LIFE-SUSTAINING USES IN HUMANS ACUTELY OR CHRONICALLY EXPOSED TO CHLOROCARBONS (FP N). ACUTE:INHAL:EXPOS TO VAPS (EFTS OF OVEREXP)

Explanation Of Carcinogenic

ity: SEE "LR" VERSION ING 24 FOR ADDITIONAL INFORMATION (FP N).

Signs And Symptoms Of Overexposure: HLTH HAZ:MAY CAUSE RESP TRACT IRRIT, SIGNS OF NERV SYS DEPRESS (DROW, DIZZ, NAUS, HDCH & FATG), ARRHY (IRREGULAR HEART BEATS). EXPOS TO HIGH CONC MAY IMPAIR BLOOD'S ABILITY TO TRANSPORT OXYG. PRLNGD/R PTD EXPOS TO VAPS MAY CAUSE LIVER & KIDNEY DMG.

SKIN:RPTD/PRLNGD CONT MAY CAUSE IRRIT, DEFAT OF SKIN & DERM.

Medical Cond Aggravated By Exposure: INDIVIDUALS WITH PRE-EXISTING DISEASES OF

THE LIVER, KIDNEY, OR HEART MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

First Aid: INHAL:REMOVE PATIENT TO FRESH AIR. ADMIN ARTF RESP. CALL PHYS.

EYE:IMMED FLUSH W/PLENTY OF WATER FOR @ LEAST 15 MINS & GET MED ATTN.

SKIN:REMOVE CONTAMD CLTHG & SHOES. WASH W/SOAP & WATER. WASH CONTAM D CLTHG BEFORE REUSE. INGEST:DO NOT INDUCE VOMIT. GIVE WATER/MILK. CONT PHYS/POIS CENTER IMMED. NOTE TO PHYS:DO NOT ADMIN SYMPATHOMIMETIC DRUGS UNL

ESS ABSOLUTELY NECESSARY.

=====
Handling and Disposal
=====

Spill Release Procedures: EVACUATE AREA, VENTILATE & AVOID BRTHG VAPS. DIKE AREA TO CNTN SPILL. CLEAN UP AREA (WEAR PROT EQUIP) BY MOPPING OR W/ABSORB MATL & PLACE IN CLSD CNTNRS FOR DISP. AVOID CONTAM OF GROUND & SURF WATERS. DO NOT FLUSH TO SEWER. IF SPILL OCCURS

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Was

te Disposal Methods: RECOVERED LIQUIDS MAY BE SENT TO LICENSED RECLAIMER/INCIN FACILITY. CONTAMD MATERIAL MUST BE DISPOSED OF IN A PERMITTED WASTE MANAGEMENT FACILITY. CONSULT LOCAL, STATE AND FEDERAL AUTHORITIES FOR APPR OVED PROCEDURES.

Handling And Storage Precautions: STORE IN SHADE BETWEEN 40F-110F. KEEP AWAY FROM HEAT, SPKS, OPEN FLAME & OTHER SOURCES OF IGNIT. AVOID PRLNGD BRTHG OF VAPS. USE W/ADEQ VENT.

Other Precautions: NO SMOKING IN AREA OF USE. DO NOT USE IN GEN VICINIT Y OF ARC

WELDING, OPEN FLAMES OR HOT SURFACES. HEAT &/OR UV RADIA MAY CAUSE FORMATION OF HCL &/OR PHOSGENE (FP N).

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 21.0F,-6.1C

Lower Limits: 1.8%

Upper Limits: 11.5%

Extinguishing Media: DRY CHEMICAL, CO*2 OR FOAM. WATER MAY BE AN INEFFECTIVE EXTINGUISHING AGENT.

Fire Fighting Procedures: WEA

R NIOSH/MSHA APPRVD PRESS DEMAND SCBA & FULL PROT EQUIP (FP N). WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPS & COOLING CNTNRS EXPOS TO HEAT & FLAME. (SUPDAT)

Unusual Fire/Explosion Hazard: THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HCL & PHOSGENE (FP N). AVOID HOT SURFACES AND OTHER SOURCES OF IGNITION.

=====
Control Measures
=====

Respiratory Protection: ATM LEVS SHOULD BE

MAINTAINED BELOW ESTABLISHED EXPOS

LIMS CNTND IN INGRED SECTION. IF AIRBORNE CONC EXCEED THOSE LIMS, USE

NIOSH/MSHA SUPPLIED AIR RESP. DO NOT USE NIOSH/MSHA APPRVD CHEM CARTRIDGE RE SP. FOR EMER & OTHER CNDTNS

Ventilation: USE ONLY W/ADEQ VENT. PROVIDE SUFFICIENT VENT IN VOL & PATTERN TO KEEP CONTAMS BELOW APPLIC EXPOS LIMS SET FOR

Protective Gloves: PVA COATED OR LATEX - NITRILE RUBBER.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: IMPERV

IOUS APRON. ANSI APPRVD EMER EYE WASH & DELUGE SHOWER (FP N).

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: USER OF "L" VERSION OF SHOULD CONSULT "LR"

VERSION FOR ADDNL INFO (FP N). SPEC GRAV:TYPICAL 1.02+/-0.040 @ 73+/-2F. SOL

IN H*2O:SOLVENT SLIGHTLY MISCIBLE. RESIN PRECIPITATES. FIRE FIGHT PROC:AVOI D SPREADING BURNING LIQ W/WATER USED FOR COOLING PURPOSES.

=====
Physical/Chemical Properties

=====
B.P. Text: SEE ING 2
Vapor Pres: SEE ING 2
Vapor Density: SEE ING 2
Spec Gravity: SUPDAT
Evaporation Rate & Reference: SEE INGREDIENT 2
Solubility in Water: SUPP DATA
Appearance and Odor: CLEAR, THIN LIQUID, KETONE LIKE ODOR.
Percent Volatiles by Volume: 80-95
=====

Reactivity Data

=====
Stability Indicator: YES
Stability Condition To Avoid: STABLE UNDER NORM CNDTNS OF STOR & HNDLG. AVOID
CONT W/OPEN FLAME, ELEC ARCS, HOT SURFS WHICH CAN CAUSE THERM DECOMP.
Materials To Avoid: STRONG ALKALIES, OXYGEN, NITROGEN PEROXIDE, POTASSIUM &
REACTIVE METALS.
Hazardous Decomposition Products: THERM DECOMP MAY YIELD CARBON MONOXIDE,
CARBON DIOXIDE, PHOSGENE AND/OR HYDROGEN CHLORIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.
=====

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

=====
Responsible Party Code: EO483
Trans ID NO: 114398
Product ID: WELD-ON 16 FOR ACRYLIC
MSDS Prepared Date: 01/01/1994
Review Date: 11/22/1996
MFN: 2
Multiple KIT Number: 0
Review IND: Y
=====

De

tail DOT Information

=====
DOT PSN Code: GJJ
Symbols: G
DOT Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
Hazard Class: 3
UN ID Num: UN1993
DOT Packaging Group: II
Label: FLAMMABLE LIQUID
Special Provision: T8,T31
Non Bulk Pack: 202
Bulk Pack: 242
Max Qty Pass: 5L
Max Qty Cargo: 60 L
Vessel Stow Req: B
=====

Detail IMO Information

=====
IMO PSN
Code: HIN
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. o
IMDG Page Number: 3230
UN Number: 1993
UN Hazard Class: 3.2
IMO Packaging Group: I/II
Subsidiary Risk Label: -
EMS Number: 3-07
MED First Aid Guide NUM: T
=====

Detail IATA Information

=====
IATA PSN BV
IATA UN ID Num: 1993
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. *
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing
Group: II
Packing Note Passenger: 305
Max Quant Pass: 5L
Max Quant Cargo: 60L
Packaging Note Cargo: 307
=====

Detail AFI Information

=====
AFI PSN BV
AFI Symbols: *
AFI Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
AFI Hazard Class: 3
AFI UN ID NUM: UN1993
AFI Packing Group: II
Special Provisions: P5
Back Pack Reference: A7.3
=====

HAZCOM Label

=====

Product ID: WELD-ON 16 FOR ACRYLIC

Cage: EO483

Assigned IND: Y

Company Name: IPS CORP

Street: 17109 S MAIN

PO Box: 379

City: GARDENA CA

Zipcode: 90248-5000

Health Emergency Phone: 213-222-3212;800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 04/12/1996

Status Code: C

Label Date: 04/12/1996

Origination Code: G

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protection

IND: YES

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: EXTREMELY FLAMMABLE. ACUTE:INHALATION OF VAPORS MAY
CONTRIBUTE TO THE OCCURRENCE OF IRREGULAR HEARTBEAT (FP N). INHAL:RESPIRATORY
TRACT, IRRITATION, NERVOUS SYSTEM DEPRESSION. SKIN:IRRITATION, DEFATTI NG.
EYES:IRRITATION. INGESTION:IRRITATION, NERVOUS SYSTEM DEPRESSION.
CHRONIC:CANCER HAZARD. CONTAINS MATERIAL WHICH IS LISTED AS AN ANIMAL LUNG
CARCINOGEN (FP N). I

NHALATION:LIVER & KIDNEY DAMAGE. SK IN:DERMATITIS.

=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.