

MINNESOTA MINING AND MFG CO -- FC-203CF LIGHT WATER BRAND AQUEOUS FILM FORMING FOAM -- 4210-01-372-9251

===== Product Identification =====

Product ID:FC-203CF LIGHT WATER BRAND AQUEOUS FILM FORMING FOAM

MSDS Date:11/13/1995

FSC:4210

NIIN:01-372-9251

MSDS Number: CBSNC

=== Responsible Party ===

Company Name:MINNESOTA MINING AND MFG CO

Address:3M CTR

City:SAINT PAUL (FORMALLY IN DETROITT, MI)

State

:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1341/612-733-1110

Emergency Phone Num:612-733-1341

CAGE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

Company Name:MINNESOTA MINING AND MFG CO PERFORMANCE CHEM AND FLUIDS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737

-6501

CAGE:28112

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 69-71%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE GLYCOL MONOBUTYL ETHER

CAS:112-34-5

RTECS #:KJ9100000

Fraction by Wt: 19-21%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TRADE SECRET COMPONENT, ALKYL SULFATE SALT

Fraction by Wt: 4-6%

Other REC Limits:NONE RECOMMENDED

MIDE
DERIVATIVE

Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANOL, 2,2',2"-NITRILOTRI-; (TRIEETHANOLAMINE)
CAS:102-71-6
RTECS #:KL9275000
Fraction by Wt: 0.5-1.5%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:5 MG/M3

Ingred Name:TRADE SECRET COMPONENT-PERFLUOROALKYL SULFONATE SALT
Fraction by Wt: 0.5-1.5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:1H-BENZOTRIAZOLE,METHYL-
CAS:29385-43-1
Fraction by Wt: 0-0.1%
Other REC Limits:NONE RECOMMENDED

=====
= Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE-MODERATE EYE IRRITATION. SKIN-MILD
SKIN IRRITATION. INHALATION-SINGLE OVEREXPOSURE, ABOVE RECOMMENDED
GUIDELINES, MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION &
IRRITATION (UPPER RESPIRATORY), BLOOD DISORDERS, BONE MARROW
DEPRESSION, KIDNEY EFFECTS, LIVER EFFECTS, PULMONARY EDEMA.
SW

ALLOWED-NO LIKELY ROUTE EXPOSURE.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS
CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:EYE-REDNESS, SWELLING, PAIN, TEARING & HAZY
VISION. SKIN-REDNESS, SWELLING, & ITCHING. INHALATION-HEADACHE,
DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME,
SLURRED SPEECH, GIDDINESS & UNCONSCIOUSNESS. SORENESS OF THE NOSE
& THROAT, COUGHING AND SNEEZING.

Medical Cond Aggravated by Expo

sure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES.
GET MEDICAL ATTENTION. SKIN: FLUSH SKIN WITH LARGE AMOUNTS OF
WATER. INHALATION: REMOVE PERSON TO FRESH AIR. IF SYMPTOMS
CONTINUE, CALL A PHYSICIAN. INGESTION: DRINK TWO GLASSES OF WATER.
CALL A PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:

Flash Point: NONE

Extinguishing Media: PRODUCT IS A FIRE EXTINGUISHING AGENT. DLA-HMIS:

USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures: NOT APPLICABLE.

Unusual Fire/Explosion Hazard: SEE HAZARDOUS DECOMPOSITION PRODUCTS
SECTION FOR PRODUCTS OF COMBUSTION.

=====
Accidental Release Measures
=====

Spill Release Procedures: OBSERVE PRECAUTIONS FROM OTHER SECTION. COVER
WITH ABSORBENT MATERIAL. COLLECT SPILLED MATERIAL. CLEANUP RESIDUE

WITH WATER. PLACE IN U. S. DOT APPROVED CONTAINER AND SEAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions: STORE IN A COOL PLACE. STORE AWAY FROM
HEAT. STORE OUT OF DIRECT SUNLIGHT. KEEP CONTAINER DRY. KEEP
CONTAINER IN WELL- VENTILATED AREA.

Other Precautions: KEEP CONTAINER TIGHTLY CLOSED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:

AVOID BREATHING OF VAPORS, MISTS OR SPRAY.

SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON
AIRBORNE CONCENTRATION OF CONTAMINANTS: HALF MASK ORGANIC VAPOR
RESPIRATOR WITH DUST.MIST PRE FILTER.

Ventilation: USE WITH ADEQUATE DILUTION VENTILATION.

Protective Gloves: BUTYL RUBBER GLOVES RECOMMENDED.

Eye Protection: WEAR VENTED GOGGLES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH EXPOSED AREAS THOROUGHLY WITH SOAP &
WATER

. WASH HANDS AFTER HANDLING & BEFORE EATING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17

Vapor Density:0.77

Spec Gravity:1

pH:8.50

Evaporation Rate & Reference: