View NSN Online: https://aerobasegroup.de/nsn/6750-01-379-1679

IMATION ENTERPRISES CORP (A 3M SPIN OFF COMPANY) -- 3M NEGATIVE COLOR PROOFING FILM MACHINE REPLENISHER (SUPPLE) -- 6750-01-379-1679

============= Product Identification =================

Product ID:3M NEGATIVE COLOR PROOFING FILM MACHINE REPLENISHER (SUPPLE)

MSDS Date: 08/23/1996

FSC:6750

NIIN:01-379-1679

MSDS Number: CBSNV === Responsible Party ===

Company Name: IMATION ENTERPRISES CORP (A 3M SPIN OFF COMPANY)

Addres

s:1 IMATION PLACE

City:OAKDALE

State:MN

ZIP:55128-3414

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:EO130

=== Contractor Identification ===

Company Name: IMATION CORP (A 3M SPIN OFF COMPANY)

Address:1 IMATION PL Box:City:SAINT PAUL

State:MN ZIP:55128 Country:US

Phone:612-733-1341

CAGE:06ZQ1

Company Name: IMATION ENTERPRISES CORPORATION

Address:1 IMATION PLACE

Box:City:SAINT PAUL

State:MN

ZIP:55128-1110

Country:US

Phone:612-733-1110

CAGE:EO130

Company Name: MINNESOT

A MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381
======= Composition/Information on Ingredients ========
Ingred Name:N-PROPYL ALCOHOL CAS:71-23-8 RTECS #:UH8225000 Fraction by Wt: 90-100% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:S,200PPM/250STEL; 96
============ Hazards Identification =============
LD50 LC50 Mixture:NONE SPECIFIE D BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE:MODERATE IRRIT. SKIN:MODERATE IRRIT(AFT PROL/REP CONTACT).MAY BE ABSORBED THRU SKIN,PRODUCE EFFECTS SIMILAR TO THOSE CAUSED BY INHAL &/OR INGEST. INHAL:CNS DEPRESSION,UPPER RESP IRRIT. INGEST:IRRI T OF GI TISSUES,LIVER EFFECTS,CNS DEPRESS. Effects of Overexposure:EYE:RED,SWELL,PAIN,TEAR,HAZY VISION.SKIN:RED,SWELL ,ITCH,DRY.INHAL:HEAD,DIZZ,DROWS,INCOORD,SLOW RX TIME,SLUR SPEECH,GIDDINESS,UNCONSC.NOSE/THROAT
SORE COUGH SNEEZ INGEST: PAIN VOMIT ABD TENDERNESS NAU B LOOD IN

VOMITUS, BLOOD IN FECES.LIVER: YELLOW SKIN(JAUNDICE), TENDERNESS OF UPPER ABD.MUSCULAR WEAK,FTG,TREMORS,CONVULSIONS

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE:IMMED FLUSH W/LG AMTS OF WATER FOR @LEAST 15MINS.GET IM

MED MED ATTN.SKIN:FLUSH W/LG AMTS OF WATER.IRRIT PERSIST GET MED ATTN.INHAL:REMOVE PERSON TO FRESH AIR.NOT BREATH GIVE ART RESP.DIFFI BREATH GET IMMED MED ATTN.INGEST:DO NOT INDUCEVOMIT.DRINK 2 GLASSES OF WATER.CALL PHYSICIAN.

Flash Point Method:TCC Flash Point:74.0F.23.3C Autoignition Temp: Autoignition Temp Text: N/DETE Lower Limits: 2.50 Upper Limits:N/DETERMINE Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, F Fire Fighting Procedures: WEAR FULL PROT CLOTH INCLUDE HELMET, SELF-CONTAIN POSIT PRESS/PRESS DEMAND BREATH APPARATUS, BUNKER COAT, PANTS, BAND AROUND ARMS/WAIST/LEGS, FCMASK, PORT COVER(SUPP) Unusual Fire/Explosion Hazard: NONE KNOWN. CLASS IC FLAMMABLE LIQUID. =========== Accidental Release Measures ================ Spill Release Procedures: REFER TO OTHER SEC OF MSDS FOR HAZ/VENTI/PPE.CALL 612-733-1110/612-733-6100 FOR ASSISTANCE.VENIT AREA.EXTINGUISH ALL IGN SOUR CES.CONTAIN SPILL.COVER W/ABSORBENT MATL.COLLECT SPILL MATL.CLEAN UP RESIDU E.PLACE IN DOT-APPROVED CNTNR. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============ Handling and Storage =========================== Handling and Storage Precautions: STORE IN COOL PLACE. KEEP CNTNR CLSD WHEN NOT IN USE.KEEP OUT OF REACH OF CHILDREN. Other Precautions: KEEP CNTNR TIGHTLY CLSD.FLAMM LIQ/VAP.KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, OTHER SOURCES OF IGN. GROUND CONTNRS SECURELY

WHEN TRANSFERRING CONTENTS.WEAR LOW STATIC/PROPERLY GROUNDED

====== Exposure Controls/Personal Protection ========

SHOES, VAP MAY IGN EXPLOSIVELY.

Respiratory Protection: AVOID BREATH OF VAP. SELECT 1 OF FOLLOWING NIOSH APPROVED RESP BASED ON AIRBORNE CONC OF CONTAMINANTS & IAW OSHA REGS:HALF-MASK ORG VAP RESP, FULL-FACE ORG VAP RESP.

Ventilation: USE W/APPROP LOC EXHAU VENTI. PROVIDE SUFFICIENT VENTI TO MAINTAIN EMISSIONS BELOW RECOMMENDED EXPO LIMITS. EXHAU (SUPPLE

WASTE#:D001(IGN).

Disclaimer (provided with this inform

ation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.