View NSN Online: https://aerobasegroup.de/nsn/8030-01-395-2726

COURTAULDS AEROSPACE, INC -- PRO-SEAL 870C-12 MAGNESE DIOXIDE DISPERSION, #0870C1 -- 8030-01-395-2726

Product ID: PRO-SEAL 870C-12 MAGNESE DIOXIDE DISPERSION, #0870C1 MSDS Date:06/03/1994 FSC:8030 NIIN:01-395-2726 Kit Part:Y MSDS Number: CBVDC === Responsible Party === Company Name: COURTAULDS AEROSPACE, INC Address:5430 SAN FERNANDO RD. Box:1800 City:GLENDALE Stat e:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 **City:GLENDALE** State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

======= Composition/Information on Ingredients ==========

Ingred Name:HYDROGENATED TERPHENYLS (VP = 1.0) CAS:61788-32-7 RTECS #:WZ6535000 Fraction by Wt: 35.0% Oth er REC Limits:NONE RECOMMENDED OSHA PEL:0.5 PPM ACGIH TLV:0.5 PPM

Ingred Name:MANGANESE DIOXIDE (SARA 313) CAS:1313-13-9 RTECS #:OP0350000 Fraction by Wt: 40.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 CEILING ACGIH TLV:5 MG/M3 (AS MN)

Ingred Name:MAGNESIUM CHROMATE (SARA 313) CAS:13423-61-5 Fraction by Wt: 25.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 AS CR ACGIH TLV:0.05 MG/M3 AS CR

Ingred Name:DIPHENYL GUANIDINE CAS:102-06-7 Fraction by Wt: 200F,>93C Extinguishing Me dia:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER. Fire Fighting Procedures:USE AIR-SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF

Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF MAGNESE DIOXIDE RESULTING IN OXIDATION & POSSIBLE IGNITION OF HYDROCARBON VEHICLE.

Spill Release Procedures: SCOOP INTO CONTAINERS. CLEAN UP RESIDUE W/SUITABLE SOLVENT.

====== Handli ng and Storage ========= Handli

Handling and Storage Precautions: WASH THOROUGHLY AFTER HANDLING & BEFORE SMOKING OR EATING. AVOID INGESTION.

Respiratory Protection:NOT REQUIRED. Ventilation:GENERAL VENTILATION. Protective Gloves:SOLVENT RESISTANT GLOVES Eye Protection:SAFETY GLASSES Supplemental Safety and Health NK

Boiling Pt:B.P. Text:644F,340

C Vapor Density:NONVOLATIL Spec Gravity:1.801 Evaporation Rate & amp; Reference:NON VOLATILE Appearance and Odor:BLACK PASTE Percent Volatiles by Volume:0.0

Stability Indicator/Materials to Avoid:YES EASILY OXIDIZABLE MATERIALS. Hazardous Decomposition Products:OXIDES OF CARBON & NITROGEN, MANGANESE & CHROMIUM COMPOUNDS.

Waste Disposal Methods:EPA #D-007 HAZARDOUS WASTE. DISPOSE OF IN COMPLIANCE W/FEDERAL & STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume respo

nsibility for the suitability of this information to their particular situation.