

P-T TECHNOLOGIES, INC. -- PF ELECTRICAL CLEANER #PF14AC -- 7930-01-398-1026

=====
Product Identification
=====

Product ID:PF ELECTRICAL CLEANER #PF14AC

MSDS Date:12/08/1993

FSC:7930

NIIN:01-398-1026

MSDS Number: CBVDL

=== Responsible Party ===

Company Name:P-T TECHNOLOGIES, INC.

Address:108 4TH AVE. S.

City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Info Phone Num:800-441-7874

Emergency Phone Num

:800-441-7874

CAGE:0JVH6

=== Contractor Identification ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

Box:City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Phone:813-726-4644

CAGE:0JVH6

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBONS

Fraction by Wt: 3.4G/KG/ORAL RAT=>5G/K

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:

POSSIBLE

IRRITATION/TEARING/REDNESS. SKIN: CHRONIC CONTACT MAY CAUSE
DEFATTING/DRYNESS/EVENTUALLY DERMATITIS. EXCESSIVE INHAL CAN CAUSE
IRRIT TO RESP TRACT/NAUSEA/DIZZINESS/HEADACHE. INGESTION: LOW
ORDER ACUTE ORAL TOXICITY, BUT LG AMTS MAY CAUSE NAUSEA/VOMITING/GI
IRRIT. MAY CAUSE INJURY IF ASPIRATED INTO LUNGS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/WATER 15 MIN. IF IRRIT PERSISTS CALL DR. SKIN:
WASH THOROUGHLY W/

SOAP & WATER. REMOVE CONTAM CLOTHES. INHALATION:
IF AFFECTED BY VAPORS GET FRESH AIR. IF TROUBLE BREATHING SEE DR.
INGESTION: DO NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBONS.
CONSULT DR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:144F,62C
Autoignition Temp:Autoignition Temp Text: 410F
Lower Limits:1.3*
Upper Limits:8.9*
Extinguishing Media:CO2, FOAM, DRY CHEMICAL *ESTIMATED AT 77F.
Fire Fighting Procedures:CLASS
B FIRE PROCEDURES. COOL EXPOSED
CONTAINERS W/WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID. CAN FORM COMBUSTIBLE
MIXTURES AT OR >FLASH POINT. AEROSOL CANS CAN RUPTURE & EXPLODE
UNDER FIRE CONDITIONS DUE TO PRESSURE/VAPOR BUILD-UP.

=====
===== Accidental Release Measures =====

Spill Release Procedures:LAND SPILL: REMOVE IGNIT SOURCES. CONTAIN
SPILL. RECOVER FREE PRODUCT. ABSORB W/SUITABLE CHEM ABSORBENT FOR
DISPOSAL VIA INCINERATION/BURIAL IN APPROVED LANDFILL. OBSERVE
LOCAL/STATE/FED REGS. WATER: REMOVE BY SKIMMING OR USE SUITABLE
ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT SOURCES/OPEN
FLAMES/OTHER IGNIT SOURCES. DON'T PUNCTURE/INCINERATE AEROSOL CANS.
STORAGE TEMP AMBIENT.
Other Precautions:USE PROPER GROUNDING PROCEDURES. KEEP OUT OF REACH OF
CHILDREN.

=====
===== Exposure Controls/Personal Protection =====
=====

Ventilation:NORMAL ROOM VENTILATION ADEQUATE. USE FANS OR OTHER
MECHANICAL VENTILATION IN ENCLOSED AREAS WHERE LARGE AMTS ARE USED.
Protective Gloves:SOLVENT RESISTANT W/PROLONGED EXPOSURE.
Eye Protection:SAFETY GLASSES RECOMMENDED
Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:380 TO 430F
Vapor Pres:1 (AIR=1)
Spec Gravity:0.76
pH:NA
Evaporation Rate & Reference:3.2 BUAC
Solubility in Water:NONSOLUBLE

Appearance and Odor:COLORLESS LIQUID, FAINT CITRUS ODOR
Percent Volatiles by Volume:100.00

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.