

CRAWFORD LABORATORIES INC -- MIL-C-22750 17925 WHITE, PART A M1-051 -- 8010-01-419-1159  
===== Product Identification =====

Product ID:MIL-C-22750 17925 WHITE, PART A M1-051

MSDS Date:03/07/1996

FSC:8010

NIIN:01-419-1159

Kit Part:Y

MSDS Number: CBVKF

=== Responsible Party ===

Company Name:CRAWFORD LABORATORIES INC

Address:4165 S EMERALD AVE

City:CHICAGO

State:IL

ZIP:60609-2646

Country:US

Info Phone

Num:312-376-7132

Emergency Phone Num:312-376-7132

Preparer's Name:DAVID SCHMETTERER

CAGE:DO165

=== Contractor Identification ===

Company Name:CRAWFORD LABORATIES, INC

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Phone:800-424-9300 CHEMTREC

CAGE:DO165

Company Name:CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL

ZIP:60609

Country:US

Phone:312-376-7132

CAGE:5V430

===== Composition/Information on Ingredients =====

Ingre

d Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) (VP =  
71.2 MMHG)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 12.0%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 8.0%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:EPOXY RESIN  
CAS:25085-99-8  
Fraction by Wt: 19.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:N  
APHTHA, LIGHT AROMATIC (VP = 9.0 MMHG)  
CAS:64742-95-6  
Fraction by Wt: 1.2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:50 PPM 9091

Ingred Name:SILICA, CRYSTALLINE - QUARTZ (MAY BE RELEASED BY SANDING  
DRIED PAINT FILM)  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: 7.20%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.  
ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred Name:VOC = 298.0 GPL  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:REPEATED/PROLONGED OCCUPATIONAL

OVEREXPOSURE TO SOLVENTS ASSOCIATED W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. PROLONGED OVEREXPOSURE (INHAL)MAY CAUSE DELAYED LUNG DISEASE.

Explanation of Carci

nogenicity:FROM INITIAL LIMITED TESTS/STUDIES IARC

CONCLUDES IS LIMITED EVIDANCE OF CARCINOGENICITY FROM CRYSTALLINE SILICA.

Effects of Overexposure:OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS. ACUTE TOXICITY (HEADACHE, DIZZINESS, NAUSEA, LOSS CONSCIOUSNESS. SEVERE EYE IRRITATION POSSIBLY RESULTING PERMANENT DAMAGE. IRRITATED MUCOUS MEMBRANES. VOMITING FROM INGESTION. SKIN DEFATTING/DRYING. SENSITIZATION AFTER REPEATED CONTACT.

===== First Aid Measures =  
=====

First Aid:EYE: FLUSH W/PLENTY CLEAN H2O 15 MIN, LIFTING LIDS, GET MED ATTN. INHAL: GET FRESH AIR, PROVIDE OXYGEN IF BREATH DIFFICULT. GIVE ARTIF RESP IF NOT BREATHING. GET MED ATTN. KEEP VICTIM WARM/QUIET. NEVER GIVE UNCONS PERSON LIQ. INGEST: CALL DR. IMMED. DON'T INDUCE VOMIT. IF VOMIT SPONTANEOUSLY, KEEP HEAD BELOW HIPS. SKIN: FLUSH W/H2O WHILE REMOVING CONTAM CLOTHES/SHOES. IF IRRIT PERSIST, GET MED AID

===== Fire Fighting Me  
asures =====

Flash Point Method:SCC

Flash Point:22.0F,-5.6C

Lower Limits:1.4

Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS COOL & KEEP FLAMMABLE STRUCTURE WETDON'T ENTER FIRE AREA WITHOUT PROPER PROTECTION, HAZARDOUS DECOMP MAY BE PRESENT

Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVER HEATED.

===== Accidental R

Release Measures =====

Spill Release Procedures:WARNING - FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH ABSORBENT & PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:TREAT AS A HAZARDOUS-FLAMMABLE MATERIAL. KNOW APPLICABLE D.O.T. REG. BEFORE ATTEMPTING TO TRANSPORT THIS MATERIAL.

Other Precautions:WARNING: HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED W/AIR. IGNITION MAY OCCUR @ TEMPS BELOW THOSE PUBLISHED AS AUTOIGNITION/IGNITION TEMPS. IGNITION TEMPS DECREASE W/INCREASING VAPOR\*

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IMPORTANT-MUST PROVIDE ADEQUATE VENT TO MAINTAIN VAPOR CONCENTRATION BELOW ESTABLISHED TLV LIMIT AS GIVEN BY OSHA. IN MORE CO

UNFINED AREAS A NIOSH/MSHA APPROVED RESPIRATOR EQUIPPED WITH ORGANIC VAPOR CARTRIDGE SHOULD BE WORN.

Ventilation:MUST PROVIDE ADEQUATE VENTILATION, SEE PARAGRAPH ABOVE.

Protective Gloves:USE RUBBER GLOVES

Eye Protection:APPROVED SAFETY GOGGLES &/OR FACE SHIELD

Other Protective Equipment:HAVE EYE BATH & SAFETY SHOWER AVAILABLE.

Supplemental Safety and Health

KEY1:F3. \*VOLUME AND VAPOR/AIR CONTACT TIME AND ARE INFLUENCED BY PRESSURE CHANGES. IGNITION MAY OCCUR AT TYPICAL ELEVATED TEMPERATURES

UNDER UNUSUAL CONDITIONS, ESPECIALLY IN PROCESS OPERATING UNDER VACUUM IF SUBJECTED TO SUDDEN INGRESS OF AIR, OUTSIDE PROCESS EQUIPMENT OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS/MIST.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 344F

Vapor Density:>AIR

Spec Gravity:1.35

pH:NA

Viscosity:73 KU

Evaporation Rate & Reference:3.5 X N-BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:WHITE, SOLVENT ODOR

Percent

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS & STRONG ALKALIES. NOT CORROSIVE TO METAL.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, STRONG  
ALKALIES, & OXIDIZING AGENTS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION OR PRODUCTS LIKE  
THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC  
GASES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT  
LOCAL, STATE & FEDERAL REG. CONTACT AN APPROVED DISPOSAL FACILITY

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.