

GE SILICONES -- DBT STANNANE, DIBUTYL BIS(1-OXODODECYL) -- 6850-01-119-1932

=====
Product Identification
=====

Product ID:DBT STANNANE, DIBUTYL BIS(1-OXODODECYL)

MSDS Date:08/22/1995

FSC:6850

NIIN:01-119-1932

Kit Part:Y

MSDS Number: CCBGH

=== Responsible Party ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER RD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergen

cy Phone Num:518-237-3330

Preparer's Name:CE HANNIGAN

CAGE:GESIL

=== Contractor Identification ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330

CAGE:GESIL

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

=====
Composition/Information on Ingredients
=====

Ingred Name:S

TANNANE, DIBUTYLBIS(LAUROYLOXY)-; (DIBUTYL TIN DILAURATE)

CAS:77-58-7

RTECS #:WH7000000

Fraction by Wt: 80-99%

OSHA PEL:0.1 MG SN/M3 SKIN

ACGIH TLV:0.1 MG SN/M3

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50:(ORAL,RAT) 1,470 MG/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INGESTION:HARMFUL IF SWALLOWED.

SKIN CONTACT:CAUSES MODERATE SKIN IRRIT

ATION. HARMFUL IF ABSORBED

THRU SKIN. INHALATION:VAPORS GIVEN OFF BY HEATED PRODUCT MAY BE

HARMFUL. EYE:CAUSES SEVERE EYE IRRITATION. CHRONIC:TARGET ORGAN

EFFECTS:CENTRAL NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:CENTRAL NERVOUS SYSTEM DISORDERS.

=====
===== First Aid Measures =====

First Aid:INGEST:DO NOT INDUCE VOMIT. SLOWLY DILUTE WITH 1-2 GL

ASSES OF

WATER/MILK & SEEK MED ATTN. NEVER GIVE ANYTHING BY MOUTH TO UNCON

PERSON. SKIN:REMOVE CONTAMD CLTHG & LAUNDRER BEFORE REUSE. WASH

W/SOAP & WATER. GET MED ATTN IF IRRIT PERSISTS. INHAL:MOVE PERSON

TO FRESH AIR. EYES:IN CASE OF CONT/SUSPECTED CONTACT, IMMEDI FLUSH

W/PLENTY OF WATER FOR AT LEAST 15 MINS & GET MED ATTN IMMEDI AFTER

FLUSHING.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:455F,235C

Extinguishing

Media:ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures:NONE KNOWN. USE NIOSH/MSHA APPROVED SCBA &

FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:SENSITIVITY TO STATIC DISCHARGE IS NOT

EXPECTED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL &

PUT IN A CNTNR FOR DISPOSAL. WEAR PROPER PROT EQUIP AS SPECIFIED IN

THE PROTECTIVE EQUIPMENT SECTION. WARN OTHER WORKERS OF SPI

LL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
AVOID CONTACT WITH SKIN AND EYES.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE KNOWN. NIOSH/MSHA APPROVED RESPIRATOR
APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:USE ONLY IN WELL VENTILATED AREA.
Protective Gloves:RUBBER GLOVES.
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .
Other Protective Equipment:RUBBER APRON. ANSI APPRVD EMERGENCY EYE WASH
& DELUGE SHOWER .
Work Hygienic Practices:WASH HANDS BEFORE EATING AND SMOKING.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====
Physical/Chemical Properties
=====

HCC:F4
Boiling Pt:B.P. Text:400F,204C
Vapor Pres:NEGLIGIBLE
Vapor Density:21.8
Spec Gravity:1.035 (WATER=1)
VOC Pounds
/Gallon:27
Evaporation Rate & Reference: