

PATTEN CO INC -- LIFT RAFT,INFLATABLE -- 4220-00-563-3567

=====
Product Identification
=====

Product ID:LIFT RAFT,INFLATABLE

MSDS Date:01/01/1987

FSC:4220

NIIN:00-563-3567

Kit Part:Y

MSDS Number: CCCBM

=== Responsible Party ===

Company Name:PATTEN CO INC

Address:1803 MADRID AVE

City:LAKE WORTH

State:FL

ZIP:33461-3315

Country:US

Info Phone Num:407-588-8500

Emergency Phone Num:407-588-8500

Preparer

's Name:NONE

CAGE:6M638

=== Contractor Identification ===

Company Name:PATTEN CO INC

Address:1803 MADRID AVE

Box:City:LAKE WORTH

State:FL

ZIP:33461

Country:US

Phone:407-588-8500

CAGE:6M638

=====
Composition/Information on Ingredients
=====

Ingred Name:INFLATABLE LIFE RAFT. A LIGHT WEIGHT WATERCRAFT OF BUOYANT
TUBE(S) CONSTRUCTION. RUBBER COATED NYLON MATERIAL.

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes o

f Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE.
Explanation of Carcinogenicity:NONE

=====
First Aid Measures
=====

First Aid:NONE NORMALLY REQUIRED.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:NORMAL PROCEDURES APPROPRIATE FOR FIGHTING

SURROUNDING FIRE.
Unusual Fire/Explosion Hazard:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN ENVIRONMENT SUITABLE FOR
RUBBER COATED NYLON MATERIAL.
Other Precautions:DO NOT MECHANICALLY DAMAGE INFLATABLE LIFE RAFT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:NORMAL WORK PLACE VENTILATION IS ADEQUATE.
Protective Gloves:NONE REQUIRED.

Eye Protection:NONE REQUIRED.
Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:NORMAL WORK PLACE HYGENIC PRACTICES ARE
ADEQUATE.

Supplemental Safety and Health

KEY1:N1. THIS ENTRY DESCRIBES PART 1 (INFLATABLE LIFE RAFT) OF TWO PART
KIT.SEE THIS SAME NSN, P/N IND B, FOR PART 2 (CARBON DIOXIDE
CYLINDER) DATA. INFLATABLE LIFE RAFT IS STOWED AS A COMPACT ITEM AN
D RENDERED BUOYANT PRIOR TO USE. PADDLES, SAIL RIGGING, CANOPY, AND
AN OUTBOARD MOTOR MOUNTING BRACKET M

AY BE INCLUDED.

===== Physical/Chemical Properties =====

HCC:G3

Solubility in Water:NOT SOLUBLE

Appearance and Odor:LIGHT WEIGHT INFLATABLE WATERCRAFT OF BUOYANT
TUBE(S) CONSTRUCTION.

Percent Volatiles by Volume:0.0

Corrosion Rate:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MATERIALS HARMFUL TO RUBBER COATED NYLON MATERIAL.

Stability Condition to Avoid:CONDITIONS HARMFUL TO RUBBER COATED N
YLON

MATERIAL.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS SCRAP RUBBER COATED NYLON WHEN
LIFE RAFT IS DICARDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be
accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.