

KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS -- NITROGEN -- 1680-00-831-1629

=====  
Product Identification  
=====

Product ID:NITROGEN

MSDS Date:05/20/1986

FSC:1680

NIIN:00-831-1629

Kit Part:Y

MSDS Number: CCCCCD

=== Responsible Party ===

Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

City:WILSON

State:NC

ZIP:27893-9604

Country:US

Info Phone Num:307-744-5487

Emergency P

hone Num:919-237-7004

CAGE:61423

=== Contractor Identification ===

Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

Box:City:WILSON

State:NC

ZIP:27893-9604

Country:US

Phone:252-237-7004

CAGE:61423

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:ASPHYXIAN; 9596

=====  
Hazards Identification  
=====

=====

LD50 LC50 Mixture:LD50 ORAL RAT IS NOT APPLICABLE.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NITROGEN IS A SIMPLE ASPHYXIANT.

NITROGEN UNDER HIGH PRESSURE CAN PRODUCE NARCOSIS.LIQUID MAY CAUSE FROSTBITE.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALATION:

HEADACHE,DROWSINESS,D

IZZINESS,EXCITATION,EXCESS

SALIVATION,VOMITING,UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:UNLIKELY TO AGGRIVATE EXISTING MEDICAL CONDITIONS UNDER NORMAL CONDITIONS OF USE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH WATER NO HOTTER THAN 105F.FOR MASSIVE EXPOSURE,TAKE A WARM SHOWER..EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:UNLIKELY ROUTE OF EXPOSURE.THIS ITEM IS A GAS.

===== Fire Fighting Measures =====

Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:EVACUATE PERSONNEL. IMMEDIATELY DELUGE CONTAINERS WITH WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL, THEN MOVE CONTAINERS AWAY FROM FIRE AREA IF WITHOUT RISK.

Unusual Fire/Explosion Hazard:CONTAINER MAY RUPTURE DUE TO HEAT OF FIRE. M

OST CONTAINERS ARE DESIGNED TO VENT CONTENTS WHEN THEY ARE EXPOSED TO ELEVATED TEMPERATURES.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL. USE SELF-CONTAINED BREATHING APPARATUS WHERE NEEDED. SHUT OFF LEAK IF WITHOUT RISK. VENTILATE OR MOVE LEAKING CONTAINER TO WELL-VENTILATED AREA. TEST AREA, ESPECIALLY CONFINED AREA S, FOR OXYGEN CONTENT PRIOR TO PERMITTING REENTRY.

===== Handling and Sto

rage =====

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED AREAS.  
CONTAINS NITROGEN AT EXTREMELY HIGH PRESSURE. CLOSE VALVE WHEN NOT  
IN USE AND WHEN EMPTY.

Other Precautions:NEVER MIX GASES;AN UNEXPECTED REACTION MAY OCCUR.DO  
NOT ATTEMPT WORK ON A PRESSURIZED SYSTEM.IF THERE IS A LEAK,CLOSE  
THE CYLINDER VALVE;BLOW DOWN THE SYSTEM BY VENTING TO A SAFE  
PLACE,THEN REPAIR THE LEAK.

===== Exposure Controls/Personal Protection =====

==

Respiratory Protection:USE SCBA IN OXYGEN-DEFICIENT ATMOSPHERES.  
CAUTION! RESPIRATORS WILL NOT FUNCTION. USE MAY RESULT IN  
ASPHYXIATION.

Ventilation:MECHANICAL (GENERAL) VENTILATION AND/OR LOCAL EXHAUST AS  
NECESSARY.

Protective Gloves:LEATHER WORK GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:OXYGEN MONITORING EQUIPMENT TO TEST FOR  
OXYGEN DEFICIENT ATMOSPHERES. METATORSAL SHOES FOR CYLINDER  
HANDLING.

Work Hygienic Practices:GOOD HYGENIC PRACTICES.

Supp

lemental Safety and Health

KEY1;G3.THIS RECORD GOES WITH PNIND-B UNDER THIS NSN/CAGE.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-319F,-195C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Pres:GAS

Vapor Density:0.967

Spec Gravity:1.2506

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS, ODORLESS GAS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

UNDER CERTAIN CONDITION

S NITROGEN CAN REACT VIOLENTLY WITH LITHIUM,  
NEODYMIUM, TITANIUM, OZONE.

Stability Condition to Avoid:HIGH HEAT ABOVE 125F

Hazardous Decomposition Products:MANUFACTURER STATES NONE.

===== Disposal Considerations =====

Waste Disposal Methods:VENT NITROGEN GAS SLOWLY TO A WELL VENTILATED  
OUTDOOR LOCATION REMOTE FROM WORK AREAS. DISCARD ANY PRODUCT,  
RESIDUE, DISPOSABLE CONTAINER IN FULL COMPLIANCE WITH FEDERAL,  
STATE AND LOCAL REGULATIONS.

Discla

imer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.