

ACCUMETRIC INC. -- SILICONE ELASTOMER PRIMER -- 8040-01-010-8758

=====
Product Identification
=====

Product ID:SILICONE ELASTOMER PRIMER

MSDS Date:05/11/1995

FSC:8040

NIIN:01-010-8758

Kit Part:Y

MSDS Number: CCCCW

=== Responsible Party ===

Company Name:ACCUMETRIC INC.

Address:350 RING ROAD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385

Emergency Phone Num:800

-424-9300 CHEMTREC

Preparer's Name:GARY HARTLEDGE

CAGE:58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Q

ty:1000 LBS

Ingred Name:2-METHOXYETHANOL (METHYL CELLOSOLVE) (SARA 313)

CAS:109-86-4

RTECS #:KL5775000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9596

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TETRABUTYL TITANATE

CAS:5593-70-4

RTECS #:XR1585000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VM & P NAPHTHA (LIGHT ALIPHATIC PETROLEUM SOLVENT NAPHTHA)

CAS:64742-89-8

Fraction by Wt: 85%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TETRA (2-METHOXYETHOXY) SILANE (METHYL CELLOSOLVE
ORTHOSILICATE)

CAS:2157-45-1

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP

:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY CAUSE SKIN & EYE IRRITATION. INHALATION MAY CAUSE DROWSINESS, RESPIRATORY IRRITATION; CAUSE INJURY TO BLOOD, LUNGS, LIVER, KIDNEYS, CNS, BRAIN. INGESTION NOT A MAJOR HEALTH RISK; AS PIRATION INTO LUNGS MAY CAUSE SERIOUS INJURY. CHRONIC: PROLONGED/REPEATED EXPOSURE MAY CAUSE INJURY TO LIVER, CNS, LUNGS

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:EYES-IRRITATION, SWELLING, REDNESS, CORNEAL INJURY. SKIN-IRRITATION, MAY BURN MILDLY. INHALED-DROWSINESS, IRRITATION OF NOSE, THROAT. INGESTED-ASPIRATION/LUNG INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES. GET MEDIAL ATTENTION. SKIN-WIPE OFF & FLUSH WITH WATER. INHALED-REMOVE TO FRESH AIR. INGESTED-NO FIRST AID SHOULD BE NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:63.0F,17.2C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR, MAY TRAVEL TO A DISTANT IGNITION SOURCE AND FLASHBACK. STATIC ELECTRICITY MAY ACCUMULATE AND IGNITE VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. USE NON-SPARKING TOOLS & EQUIPMENT. MOP UP OR WIPE UP OR SOAK UP WITH ABSORBENT & CONTAIN FOR SALVAGE OR DISPOSAL. CLEAN ANY REMAINING SLIPPERY SURFACES. LOCAL, STATE AND FEDERAL REPORTING REQUIREMENTS MAYAPPLY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Sto

rage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED & AWAY FROM HEAT, SPARKS AND OPOEN FLAME. KEEP AWAY FROM WATER OR MOISTURE.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS

REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE ADEQUATE GENERAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:SILVER SHIELD.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:DLA-HMIS: EYE WASH STATION.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health
KEY1=F3. PART OF A 2 PART KIT.

=====

== Physical/Chemical Properties =====

HCC:F2

Spec Gravity:0.76

Viscosity:1 CST

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS LIQUID; SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS CAN CAUSE A REACTION.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:CARBON OXIDES, TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS.

Conditions to Avoid Polymeri

zation:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.