

DEL PAINT CORP -- S-9970 -- 8010-00-530-8380

===== Product Identification =====

Product ID:S-9970
MSDS Date:11/14/1994
FSC:8010
NIIN:00-530-8380
MSDS Number: CCGFY
=== Responsible Party ===
Company Name:DEL PAINT CORP
Address:3105 E RENO AVE
City:OKLAHOMA CITY
State:OK
ZIP:73117-6699
Country:US
Info Phone Num:405-672-1431/800-866-6823
Emergency Phone Num:800-866-6823/405-672-1431

Preparer's Name:
ONEY FLEMING
CAGE:EO523
=== Contractor Identification ===
Company Name:DEL PAINT CORP
Address:3105 E RENO AVE
City:OKLAHOMA CITY
State:OK
ZIP:73117-6699
Country:US
Phone:405-672-1431/800-866-6823
CAGE:EO523
Company Name:DEL PAINT MFG
Address:3105 EAST RENO
Box:City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE
CAS:64742-89-8
Fraction by

Wt: 32.06%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:HEXONE, METHYL ISOBUTYL KETONE (MIBK), 4-METHYL-2-PENTANONE
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 2.34%
Other REC Limits:50 PPM
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 2.24%
Other REC Limits:50 PPM
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: CAN CAUSE
MODERATE IRRITATION & DERMATITIS. INHALATION: NASAL & RESPIRATORY
IRRITATION. INGESTION: CAN CAUSE GI IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:REDNESS, PAIN, LABORED BREATHING, DULLNESS,
DROWSINESS, ABDOMINAL PAIN, NAUSEA, IR
RITATION, TEARING, BLURRED
VISION, DEFATTING, DIZZINESS, HEADACHE, VOMITING.
Medical Cond Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: WASH
W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF
NECESSARY. INGESTION: KEEP WARM & QUIET. DON'T INDUCE VOMITING.
OBTAIN MEDI CAL ATTENTION IN ALL CASES.

===== F

Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:52F

Autoignition Temp:Autoignition Temp Text:540F

Lower Limits:1

Upper Limits:6

Extinguishing Media:CO2, DRY CHEMICAL/FOAM. WATER MAY SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS.

Fire Fighting Procedures:WEAR PRESSURE DEMAND MSHA/NIOSH APPROVED/EQUIVALENT SCBA & FULL PROTECTIVE GEAR. WATER SPRAY MAY BE USED FOR COOLING CONTAINERS.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & TRAVEL

ALONG THE GROUND/MOVED BY VENTILATION & IGNITE BY IGNITION SOURCES. AUTOIGNITION TEMP: 540F.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE THE AREA. COVER W/INERT ABSORBENT MATERIAL & SHOVEL W/NON-SPARKING TOOLS INTO CONTAINER. REMOVE CONTAINER TO A SAFE AREA & SEAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY FROM SPARKS

, FIRE & REMOTE IGNITION SOURCES. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:KEEP AWAY FROM CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED TO REDUCE STATIC ELECTRICITY HAZARD. USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, USE A RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH APPROVED). ENGINEERING/MANAGEMENT CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:LOCAL EXHAUST, SUFFICIENT TO KEEP AIRBORNE VAPOR CONCENTRATIONS BELOW THE TLV LIMIT.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:EYEWASH & BATH STATION, IMPERVIOUS CLOTHING.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:244-284F

Decomp Temp:Decomp Text:752F

Vapor Pres:2.58

Vapor Density:>1

Spe

c Gravity:1.39
Viscosity:77-89KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:INSOLUBLE
Appearance and Odor:BLACK LIQUID W/SLIGHT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT SURFACES, OPEN FLAMES/IGNITION
SOURCES.
Hazardous Decomposition Products:THERMAL: CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS. FLAMMABLE UN1263.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.