

SCOT INC. -- 6028200 INITIATOR,EXPLOSIVE MECHANICALLY ACTUATED -- 1377-01-166-4265
===== Product Identification =====

Product ID:6028200 INITIATOR,EXPLOSIVE MECHANICALLY ACTUATED

MSDS Date:12/15/1992

FSC:1377

NIIN:01-166-4265

MSDS Number: CCGKY

=== Responsible Party ===

Company Name:SCOT INC.

Address:2525 CURTISS ST

City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Info Phone Num:708-969-0620

Emergency Phone Num:800-535-5053

Preparer's Name:NICHOLAS F TURCIC

CAGE:MO896

=== Contractor Identification ===

Company Name:SCOT INC

Address:2525 CURTISS ST

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Phone:630-969-0620

CAGE:93455

Company Name:SCOT INC.

Address:2525 CURTISS ST

City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Phone:708-969-0620

CAGE:MO896

===== Composition/Information on Ingredients =====

Ingred Name:HNS HEXANITROSTILBENE

Fraction by Wt: 60

%

Ingred Name:LEAD AZIDE

CAS:13424-46-9

RTECS #:OF8650000

Fraction by Wt: 40%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE

=====
===== First Aid Measures =====

First Aid:OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Extinguishing Med

ia:WATER ONLY, NO DRY CHEMICAL, CO2/HALON

Fire Fighting Procedures:MOVE CONTAINERS FROM AREA W/O RISK. APPLY
WATER TOSIDES OF EXPOSED CONTAINERS. MASSIVE FIRE IN CARGO AREA,
USE UNMANNED HOSE HOLDER/MONITOR NOZZLES.

Unusual Fire/Explosion Hazard:USE FLOODING QUANTITIES OF WATER AS FOG.
COOL CONTAINERS W/FLOODING WATER, APPLY FROM A FAR DISTANCE.
EVACUATE TO RADIUS OF 1500 FT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KE

EP FIRE AWAY. USE CAUTION IN

HANDLING. ACTUATED DEVICE SURFACE TEMP MAY BE 200F. INITIATE BY
REMOTELY EXTRACTING THE SEAR.

Other Precautions:THE INITIATOR SHOULD BE CONTAINED TO PREVENT HAZARDS
OF SHRAPNEL.

=====
===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

INITIATOR HAS A REDUNDANT ACTUATION SYSTEM. A DUAL FIRING MECHANISM
FIRES DUAL PRIMERS WHICH ACTUATE DUAL DETONATORS. ACTUATION OF DUAL
SEARS WHICH COCK INDEPENDENT SPRINGS

WHICH WILL IMPART SUFFICIENT ENERGY TO FIRE DUAL PRIMERS INTO DUAL DETONATORS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: HEAT, FLAME, IMPACT. IF INITIATOR IS INITIATED SOME LIGHT METALLIC FRAGMENTATION WOULD OCCUR W/HOT DISCHARGE.

Hazardous Decomposition Products: MINIMAL NOXIOUS GASES LIBERATED IF HERMETIC SEAL SHOULD RUPTURE.

===== Disposal Considerations =====
=====

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. UN0173.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.