

TEXACO REFINING AND MARKETING INC. -- CAPELLA WF 68,01562 -- 9150-00-598-2911

===== Product Identification =====

Product ID:CAPELLA WF 68,01562

MSDS Date:06/15/1994

FSC:9150

NIIN:00-598-2911

MSDS Number: CCHTL

=== Responsible Party ===

Company Name:TEXACO REFINING AND MARKETING INC.

Address:1111 RUSK STREET

City:HOUSTON

State:TX

ZIP:77002-3310

Country:US

Info Phone Num:800-782-7852

Emergency Phon

e Num:914-831-3400/800-424-9300(CHEMTREC)

CAGE:2R503

=== Contractor Identification ===

Company Name:EMULTEC INDUSTRIAL PRODUCTS INC

Address:1150 HAYDEN DR SUITE 100

Box:City:CHARROLLTON

State:TX

ZIP:75006

Country:US

Phone:972-417-1288

CAGE:0WA27

Company Name:SUPERIOR FUELS INC

Box:UNKNOW

CAGE:4X847

Company Name:TEXACO INC CORPORATE HQ

Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY

ZIP:10604

Country:US

Phone:914-253-4000

CAGE:59595

Company Name:TEXACO REFINING AND MARKETING INC

Address:1

111 RUSK ST
Box:City:HOUSTON
State:TX
ZIP:77002-3310
Country:US
Phone:713-650-5206
CAGE:2R503

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC
CAS:64742-18-3
RTECS #:PY8032000
Fraction by Wt: 80 - 90%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL/LIGHT NAPHTHENIC HYDROTREATED PETROELUM
DISTILLATE
CAS:64742-53-6
RTECS #:PY8036000
Fraction by Wt: 10 - 20%
Other REC Limit
s:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS >5000 MG/KG.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY
TRACT. ACUTE- MAY CAUSE MINIMAL EYE IRRITATION. PROLONGED/REPEATED
SKIN CONTACT MAY CAUSE DEFATTING. INHALATION OF V
APORS/OIL MIST MAY
CAUSE IRRITATION OF NOSE & T HROAT, HEADACHE, DROWSINESS. INGESTION
OF SEVERAL MOUTHFULS MAY CAUSE ABDOMINAL DISCOMFORT. CHRONIC- NONE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, HEADACHE,
DROWSINESS, COUGH, ABDOMINAL DISCOMFORT, TEARING, DEFATTING
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
First Aid
=====

Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:IF MORE THAN SEVERAL MOUTHFULS OF THIS MATERIAL ARE SWALLOWED, DRINK TWO GLASSES OF WATER. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:355F,179C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM/DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. RECOVER FREE OIL IF POSSIBLE. ABSORB SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH & SHOVELD INTO CONTAINERS FOR LATER DISPOSAL. PREVENT RUN-OFF TO ENTER WATERWAYS, SEWERS. ALL RESPONSE ACTIVITIES MUST COMPLY WITH HAZWOPER.
Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT, FLAME & STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.
G. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDRER BEFORE RE-USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.
Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD

(S).

Protective Gloves:NITRILE OR NEOPRENE RECOMMENDED

Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Spec Gravity:0.895

Viscosity:64.6C

ST @104F

Appearance and Odor:CLEAR YELLOW LIQUID - BLAND ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:MAY PRODUCE FUMES, SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES AND KETONES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN COMPLIANCE WITH ALL

A

APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS. RCRA

EMERGENCY NUMBER: 800-424-9346. DO NOT CONTAMINATE ANY LAKES, STREAMS OR UNDERGROUND WATER SUPPLY . INCINERATION IS RECOMMENDED. NOT HAZARDOUS WASTE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

d

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.