View NSN Online: https://aerobasegroup.de/nsn/6140-01-041-0262

ENERGIZER POWER SYSTEM, DIV OF EVEREADY BATTERY -- NICKEL CADMIUM BATTERY -- 6140-01-041-0262

Product ID:NICKEL CADMIUM BATTERY MSDS Date:08/03/1995 FSC:6140 NIIN:01-041-0262 MSDS Number: CCHXG === Responsible Party === Company Name: ENERGIZER POWER SYSTEM, DIV OF EVEREADY BATTERY Address: US HIGHWAY 441N City:ALACHUA State:FL ZIP:32615 Country:US Info Phone Num:21 6-835-7368 Emergency Phone Num:216-835-7368 CAGE:EO263 === Contractor Identification === **Company Name: BALKAMP INC** Address:2601 S HOLT ROAD Box:City:INDIANAPOLIS State:IN ZIP:46241 Country:US Phone:317-244-7241 CAGE:70842 Company Name: ENERGIZER POWER SYSTEM, DIV. OF EVEREADY BATTERY Address: US HIGHWAY 441N Box:City:ALACHUA State:FL ZIP:32615 Country:US Phone:440-835-7368 CAGE:EO263 Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE Address:ONE LINCOLN WAY Box:City:ST. LOUIS State:MO ZIP:63120-15

78 Country:US Phone:414-255-5520 CAGE:050Q3 Box:UNKNOW CAGE:ENER1

Ingred Name:CADMIUM (SARA 313) (CERCLA) CAS:7440-43-9 RTECS #:EU9800000 Fraction by Wt: 13-22% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 MG/M3 DUST; Z-2 ACGIH TLV:0.01 MG/M3 DUST;9596 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM OXIDE (SARA 302/313) (CERCLA) CAS:1306-19-0 RTECS #:EV1925000 Fraction by Wt: 13-22% Other REC Limits:NONE RECOMMEN DED OSHA PEL:0.2 MG (CD)/M3 DUST ACGIH TLV:0.01 MG(CD)/M3; 9596

Ingred Name:CADMIUM HYDROXIDE CAS:21041-95-2 Fraction by Wt: 13-22% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.05 MG CD/M3 ACGIH TLV:0.05 MG CD/M3

Ingred Name:COBALT (SARA 313) CAS:7440-48-4 RTECS #:GF8750000 Fraction by Wt: 0.5-2% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.02 MG/M3; A3; 9596

Ingred Name:COBALT (2+) OXIDE CAS:1307-96-6 RTECS #:GG2800000 Fraction by Wt: 0.5-2% Other REC Limits:NONE RECOMMEN DED

Ingred Name:COBALT (II) HYDROXIDE CAS:21041-93-0 RTECS #:GG0904500 Fraction by Wt: 0.5-2% Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM HYDROXIDE CAS:1310-65-2 RTECS #:OJ6307070 Fraction by Wt: 0-4% Other REC Limits:NONE RECOMMENDED

Ingred Name:NICKEL (SARA 313) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 20-32% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9596

Ingred Name:NICKEL OXIDE CAS:1313-99-1 RTECS #:QR8400000 Fraction by Wt: 20-32% Ot her REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 AS NI ACGIH TLV:1 MG/M3 AS NI

Ingred Name:NICKEL HYDROXIDE (SARA 313) (CERCLA) CAS:12054-48-7 RTECS #:QR7040000 Fraction by Wt: 20-32% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG(NI)/M3 ACGIH TLV:0.1 MG(NI)/M3; 9596 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (CERCLA) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 0-4% Other REC Limits:NONE RECOMMENDED OSHA PEL:C 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9596 EPA Rpt Qty:1000 L BS DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM HYDROXIDE (CERCLA) CAS:1310-73-2 RTECS #:WB4900000 Fraction by Wt: 0-4% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:C 2 MG/M3; 9596 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT RELEVANT. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chroni c:TARGET ORGANS:NONE. ACUTE- UNDER NORMAL CONDITIONS OF USE, NO EXPOSURE TO HAZARDOUS COMPONENTS. IF INCINERATED, INHALATION OF FUMES MAY CAUSE RESPIRATORY SYSTEMS IRRITATION. FUMES WILL ALSO IRRITATE E YE TISSUE. IF BROKEN, MAY CAUSE SKIN BURNS. SWALLOWING IS HARMFUL. CHRONIC- MAY CAUSE KIDNEY **DYSFUNCTION & LUNG INJURY.** Explanation of Carcinogenicity: CONTAINS CADMIUM [7440-43-9] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. CONTAINS NICKEL. Е ffects of Overexposure:NONE UNDER NORMAL CONDITIONS OF USE. IF LEAKING OR INCINERATED: IRRITATION OF RESPIRATORY TRACT AND EYES, SKIN BURNS, CHEST PAIN, COUGHING, SWEATING, CHILLS, SHORTNESS OF BREATH, WEAKNESS Medical Cond Aggravated by Exposure: IF INCINERATED: RESPIRATORY DISORDERS, PROSTATE DISORDERS, LIVER AND KIDNEY DISORDERS, VISION

PROBLEM

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMO

VE TO FRESH

AIR. CALL PHYSICIAN. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SEE PHYSICIAN. SKIN:WASH WITH SOAP & WATER. ORAL:IF BATTERY/ OPEN BATTERY IS INGESTED, DO NOT INDUCEVOMITING OR GIVE FOOD/DRINK. SEEK IMMEDIATE MEDICAL ATTENTION. CALL NATIONAL BATTERY INGESTION HOTLINE FOR ADVICE & FOLLOWUP (202-625-3333) COLLECT, DAY/NIGHT.

Flash Point:NONE Extinguishing Media:WATER SPRAY, CARBO N DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CADMIUM AND NICKEL FUMES ARE TOXIC AND CAN CAUSE DEATH.

Spill Release Procedures:BATTERY AND CELL CASES WILL NORMALLY CONTAIN MATERIALS OF CONCERN. USE INDUSTRIAL ABSORBENT TO COLLECT POTASSIUM HYDROXIDE. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. AVOID BREAKING, CRUSHING OR OTHERWISE DESTROYING THE PHYSICAL INTEGRITY OF THE CELL OR BATTERY.
Other Precautions:DO NOT INCINERATE. DO NOT TOUCH BROKEN BATTERIES. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING FUMES OR DUST. KEEP OUT OF REACH OF SMALL CHILDREN.

Respiratory Protection:USE NIOSH APPROVED MIST OR DUST MASK WHEN HANDLING BROKEN BATTERIES. Ventilation:ADEQUATE Protective Gloves:NEOPRENE, NITRILE FOR BROKEN BATTERIES Eye Protection:SAFETY GOGGLES RECOMMENDED Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING.

Supplemental

Safety and Health

THE MANUFACTURER STATES THIS BATTERY IS AN ARTICLE AND, AS SUCH, IS NOT SUBJECT TO OSHA HAZARD COMMUNICATION STANDARD REQUIREMENT FOR PREPARATION OF A MATERIAL SAFETY DATA SHEET.

HCC:Z5

Appearance and Odor: FIVE AA BATTERIES CONNECTED IN SERIES, NO ODOR

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:EXCESSI VE HEAT, FIRE Hazardous Decomposition Products:TOXIC FUMES OF CADMIUM OXIDE AND NICKEL OXIDE.

Waste Disposal Methods:CELLS AND BATTERIES MAY BE RETURNED AT SENDERS EXPENSE TO A PERMITTED TREATMENT, STORAGE, DISPOSAL FACILITY (TSDF). DISPOSAL MUST BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAW S AND REGULATIONS. EPA/RCRA#-D006 (CD) MAY APPLY.

Disclaimer (provided with this informati

on by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.