

ALLIED SIGNAL INC., AIRCRAFT LANDING SYSTEM -- CHROMIUM PLATED AIRCRAFT PART,2609930
-- 1630-01-411-7523

===== Product Identification =====

Product ID:CHROMIUM PLATED AIRCRAFT PART,2609930

MSDS Date:12/01/1993

FSC:1630

NIIN:01-411-7523

MSDS Number: CCJHX

=== Responsible Party ===

Company Name:ALLIED SIGNAL INC., AIRCRAFT LANDING SYSTEM

Address:3520 WESTMOOR STREET

City:SOUTH BEND

State:IN

ZIP:4662

8

Country:US

Info Phone Num:219-231-2302

Emergency Phone Num:219-231-2000

CAGE:55284

=== Contractor Identification ===

Company Name:HONEYWELL INTL INC, AIRCRAFT LANDING SYSTEM ALS

Address:3520 WESTMOOR STREET

Box:City:SOUTH BEND

State:IN

ZIP:46628-1373

Country:US

Phone:219-231-2201

CAGE:55284

===== Composition/Information on Ingredients =====

Ingred Name:CHROMIUM (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: TRACE

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9596
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT RELEVANT.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, LUNG, KIDNEY,
LIVER. PRODUCT IS NOT HAZARDOUS. HEALTH HAZARDS ARE DUE TO
DUSTS/FUMES CREATED DURING MACHINING. ACUTE- EYE:MAY CAUSE
USE
IRRITATION. SKIN:MAY CAUSE SENSITIVITY. INH ALE:CAN CAUSE METAL
FUME FEVER. ORAL:MAY CAUSE GI IRRITATION. CHRONIC- LUNG & THROAT
CANCER, LIVER & KIDNEY EFFECTS.
Explanation of Carcinogenicity:CONTAINS CHROMIUM.
Effects of Overexposure:IRRITATION, SHORTNESS OF BREATH, CHEST PAIN,
WEAKNESS, HEADACHE, CHILLS AND MUSCULAR PAIN, NAUSEA, VOMITING,
DIARRHEA, SORE THROAT, SWEATING, FEVER, LUNG ALLERGY, SKIN
ULCERATION, DERMATITIS, ECZEMA
Medical Cond Aggravated by Exposure:IN
DIVIDUALS WITH PRE-EXISTING
DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, LIVER, KIDNEYS, CNS
MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE
EXPOSURES.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. EYE:FLUSH WITH WATER FOR
15 MINUTES. HOLD EYELIDS OPEN. SKIN:REMOVE CONTAMINATED CLOTHING.
WASH SKIN WITH SOAP/MILD DETERGENT & LARGE AMOUNT OF WATER.
INHALED:REMOVE TO FRESH AIR. PROVIDE CPR
/OXYGEN IF NEEDED.
ORAL:TREATMENT MUST BE ADMINISTERED BY MEDICAL PERSONNEL. NOTE TO
PHYSICIAN:TREAT ACCORDING TO SYMPTOMS PRESENT.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:DRY SAND, DRY DOLOMITE, DRY GRAPHITE OR SODIUM
CHLORIDE
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CHROMIUM DUST CREATED DURING MACHINING
MAY PRESEN

T A MODERATE EXPLOSION HAZARD WHEN EXPOSED TO FLAME. DUST AND STRONG OXIDIZERS MAY CAUSE FIRE OR EXPLOSION.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VACUUM OR SWEEP UP SPILLAGE. AVOID CREATING DUST. PLACE SPILLAGE IN APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AREA. SPILLS AND RELEASES MAY HAVE TO BE REPORTED TO FEDERAL AND/OR LOCAL AUTHORITIES.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:AVOID CREATING DUST. AVOID CONTACT TO EYES AND SKIN. AVOID INHALATION OF DUST. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. OBEY HAZARD WARNING LABEL. USE WITH ADEQUATE VENTILATION. MAY CAUSE LUNG AND THROAT CANCER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED SUPPLIED-AIR RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO KEEP DUST AND FUME LEVELS BELOW TLV.

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, PROTECTIVE CLOTHING AND/OR UNIFORM

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

THIS METAL AIRCRAFT PART IS PLATED WITH CHROMIUM. THE PART ITSELF IS NOT HAZARDOUS. HAZARDS ARE ASSOCIATED WITH THE CHROMIUM DUSTS AND FUMES THAT MAY BE GENERATED IF THE PART IS MACHINED DURING MAINTENANCE ACTIVITIES.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT

Solubility in Water:NO

T RELEVANT

Appearance and Odor:SOLID, MATTED TEXTURE METALLIC TO POLISHED METAL
FINISH - ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG BASES
Stability Condition to Avoid:STABLE UNDER NORMAL CONDITIONS.
Hazardous Decomposition Products:NOT RELEVANT

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULATIONS. RECYCLE IF POSSIBLE. RCRA NUMBER: D007.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.