View NSN Online: https://aerobasegroup.de/nsn/8010-00-261-4160

## T&R CHEMICALS -- GUM TERPENTINE -- 8010-00-261-4160

Product ID:GUM TERPENTINE

MSDS Date:06/24/1986

FSC:8010

NIIN:00-261-4160

MSDS Number: CCJSB === Responsible Party ===

Company Name: T&R CHEMICALS

Box:330 City:CLINT State:TX ZIP:79836 Country:US

Info Phone Num:915-851-2761

Emergency Phone Num:915-851-2761 FOR ADDITIONAL INFO

CAGE:KO922

=== Contractor Identificati

on ===

Company Name: CHEMICAL SPECIALISTS & DEVELOPMENT

Box:UNKNOW CAGE:5W443

Company Name:STARTEX (409-539-6244)

Box:UNKNOW CAGE:NO735

Company Name: T&R CHEMICALS

Box:330 City:CLINT State:TX ZIP:79836 Country:US

Phone:915-851-2761

CAGE:KO922

Company Name:TRI-CHEM CORP

Box:City:SOUTHFIELD

State:MI

ZIP:48037-0448 Country:US

Phone:800-456-6255

CAGE:TRCHE

======= Composition/Information on Ingredients ========

Ingred Name: TURPENTINE

CAS:8006-64-2

RTECS #:YO8400000 Other REC Limits:NONE RECOMMENDED ACGIH TLV:100 PPM

========= Hazards Identification =============== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: MODERATELY IRRITATING. MAY BE ALLERGENIC TO SOME WORKERS. ABOVE AVERAGE EXPOSURE MAY CAUSE DERMATITIS, CHRONIC: SAME AS ABOVE EXCEPT MILD BOTH AS IRRITANT & ALLERGENIC. EXPOSURE OVER LONG TIME PERIOD MAY RESULT IN SERIOUS KIDNEY IR RITATION. INGEST: LARGE OVEREXPOSURE, HEAVY BREATHING/COLLAPSE/COMA. Effects of Overexposure: INHALATION: CHARACTERISTIC ODOR ON BREATH. GIDDINESS/RESTLESSNESS/EXCITABLE/INTOXICATION/NAUSEA. SKIN/EYES: DIALATES. IRRITATES SKIN. ABSORPTION: ATAXIA/INSOMNIA/ALBUMINURIA/CYANOSIS/DILERIUM. Medical Cond Aggravated by Exposure: CONTINUED EXPOSURE TO FUMES/VAPORS IN EXCESS OF 100 PPM WOULD CONSTITUTE OVEREXPOSURE & COULD CAUSE KIDNEY DAMAGE. ====== First Aid Meas ures =========== First Aid:EYES: FLUSH WELL W/WARM WATER, CALL DR, SKIN: REMOVE CONTAM CLOTHES. WASH SKIN W/LARGE AMTS LUKE WARM WATER USING BLAND SOAP SOLUTION. INHALATION: GET TO FRESH AIR. KEEP WARM. INGESTION: GIVE LAVAGE O R EMETIC & COPIOUS AMTS WATER. CONSULT DR IMMEDIATELY. ============ Fire Fighting Measures ========================= Flash Point Method:TCC Flash Point: 105F,41C Autoignition Temp: Autoignition Temp Text: 488F Lower Limits:0.8 Extinguishing Media:CO2, FOAM, DRY CHEMICAL. Fire Fighting Procedures: AVOID IMPREGNATION OF ANY LEAKAGE W/OXIDANTS OR COMBUSTIBLES. Unusual Fire/Explosion Hazard: EMITS ACRID FUMES WHEN HEATED ALONG W/COMBUSTIBLE VAPORS. ======== Accidental Release Measures ============ Spill Release Procedures: STOP SPILL PROMPTLY. REMOVE IGNIT SOURCES. CONTAIN SPILL W/DIKE ETC. CONTAINMENT REQUIRED. PUMP TO TANK FOR

CONTAINMENT, SALVAGE/CONTROL DISPOSAL AS NECESSARY.

= Handling and Storage =========== Handling and Storage Precautions: AS MAY BE SPECIFIED FOR HEALTH & SAFETY. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USBM TYPE N CANISTER OR EQUAL AS APPROVAL FOR CONCERNED PRODUCT. Ventilation: ADEQUATE EXHAUST TO PREVENT BUILD-UP VAPOR/FUMES/IGNITABLE MATERIAL. Protective Gloves: NEOPRENE RUBBER Eye Protection: SAFETY GOGGLES/FACE SHIELDS (OSHA) Other Protective Equipment: OVERALLS & APRON S - NEOPRENE. Work Hygienic Practices: WASHING & SHOWER FACILITIES READILY AVAILABLE. Supplemental Safety and Health PROTECTIVE MEASURES DURING MAINTAINANCE OF CONTAMINATED EQUIPMENT AS MAY BE REQUIRED TO MEET STATE, FEDERAL, LOCAL REGULATIONS. ========= Physical/Chemical Properties =========== Boiling Pt:B.P. Text:307F,153C Melt/Freeze Pt:M.P/F.P Text:LIQ@AMBIENT Vapor Pres:760 Vapor Density:4.84 Spec Gravity: 0.864 @ 25C Evaporation Rate & Description Rate & Reference: 1.0 (BUAC=1) Solub ility in Water:NEGLIGIBLE Appearance and Odor: COLORLESS TO LIGHT AMBER, TERPENE AROMA ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS. Stability Condition to Avoid: UNCONTROLLED EXPOSURE TO HEAT/FLAME. KEEP COOL. Hazardous Decomposition Products: OVERHEATED ACRID FUMES/DEGREDATION TERPENES RELEASED.COMBUS PRODS INCLUDE DECOMPOSED

HYDROCARBONS/CARBON MONOXIDE/CO2.

Conditions to Avoid Polymerization: AVOI

D ALL CONTACT W/STRONG MINERAL ACIDS & LEWIS ACIDS (BORON TRIFLUORIDE/SUBSTANCES CAPABLE OF RELEASING PROTON MATTER)

======= Disposal Considerations ===========

Waste Disposal Methods:AVOID DIRECT CONTACT W/LIQUID/VAPOR/SPRAY/MIST BY WEARING PROTECTIVE CLOTHES/SAFETY GOGGLES/SAFETY SHIELDS/USING RESP PROTECTION AS NECESSARY. FOLLOW REQ OF RCRA 1976 & ADDENDA OF US FOR INFO ON LEGAL DISPOSAL OF HAZARDOUS SOLIDS. COMPLY W/APPLIC LAW

## Disclaimer (

provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.