View NSN Online: https://aerobasegroup.de/nsn/5970-01-386-6169 VARFLEX CORPORATION -- VARGLAS SILICONE RESIN 500 -- 5970-01-386-6169 Product ID: VARGLAS SILICONE RESIN 500 MSDS Date:07/23/1993 FSC:5970 NIIN:01-386-6169 MSDS Number: CCKPZ === Responsible Party === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET City:ROME State:NY ZIP:13440 Country:US Info Phone Num:315-336-4400 Emergency Phone Num:315-336-4400 C AGE:79074 === Contractor Identification === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET Box:City:ROME State:NY ZIP:13440 Country:US Phone:315-336-4400 CAGE:79074 ======= Composition/Information on Ingredients ======== Ingred Name:FIBROUS GLASS Other REC Limits: NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST

Ingred Name:SILICONE COATING--METHYL, PHENYL

Other REC Limits: NONE RECOMMENDED

======= Hazards Identification ========

========

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. ACUTE- THE FIBERS FROM THIS PRODUCT ARE MECHANICAL IRRITANTS AND MAY CAUSE TRANSITORY IRRITATION TO EXPOSED AREAS SUCH AS EYES, SKIN AND UPPER RESPIRATORY TRACTS. ORAL:UNLIKELY TO OCCUR. CHRONIC- NONE.

Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION

Medical Cond

Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS OR EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. DO NOT RUB OR SCRATCH IRRITATED AREAS. INHALED:REMOVE TO FRESH AIR. PROV IDE OXYGEN/CPR IF NEEDED. OR AL:UNLIKELYTO OCCUR.

============ Fire Fighting Measures ==============

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

========= Accidental Release Measures ================

Spill Release Procedures:WEAR APPROVED RESPIRATOR AND CHEMICALLY COMPATIBLE GLOVES IF NEEDED. FOR DUST AND FIBERS GENER ATED DURING

FABRICATION, VACUUM OR SWEEP UP. AVOID CREATING DUST. PLACE IN APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AREA AND WASH SPILL SITE.

Neutralizing Agent: NOT RELEVANT

Handling and Storage Precautions:STORE AWAY FROM DIRECT SUNLIGHT, AT A RELATIVE HUMIDITY OF 30-60%. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:AVOID INHALATION OF FIBERS. AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGH

Disclaimer (provided with this information by the compiling agencies): This information is formulated

LY AFTER HANDLING MATERIAL.

for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.