

ASPEN PAINTS -- STAIN, OIL TYPE, WOOD INTERIOR -- 8010-00-165-8627

===== Product Identification =====

Product ID:STAIN, OIL TYPE, WOOD INTERIOR

MSDS Date:12/01/1994

FSC:8010

NIIN:00-165-8627

MSDS Number: CCKWQ

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergency Phone Num:800-424-9300

(CHEMTREC)

Preparer's Name:D KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

===== Composition/Information on Ingredients =====

Ingred Name:SK SOLVENT (MINERAL SPIRITS MIXT

URE) SOLVENT 390
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 67.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:525 MG/M3
ACGIH TLV:100 PPM

Ingred Name:VOC: 594 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:RAT:ORAL >8 ML/KG. INHAL +71400 PPM/4HR*
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE; INHA
L: NASAL & RESP IRRIT,
DIZZY, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUS,
ASPHYXIATION. EYE: SEVERE IRRIT, RED, TEAR, BLURRED VISION. INGEST:
GI IRRIT, NAUSEA, VOMIT, DIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE
CHEMICAL PNEUMONITIS (CAN BE FATAL). SKIN: CHRONIC: DEFATING,
DRYING (IRRIT & DERMITITIS).
Effects of Overexposure:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENT WITH PERMANENT BRAIN AND NS
DAMAGE. CONCENTRATING AND INH
ALING CONTENTS MAY BE HARMFUL OR
FATAL.

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR AND RESTORE BREATHING IF REQUIRED.
EYE: FLUSH W/WATER FOR >15 MINUTES, HOLDING EYELIDS OPEN. SKIN:
WASH W/MILD SOAP & WATER. INGESTION: DONT INDUCE VOMITING. GET MED
AID IMM EDIATELY. NOTE: THE MAIN HAZATD FOLLOWING ACCIDENTAL
INGESTION IS ASPIRATION OF LIQUID INTO LUNGS PRODUCING CHEMICAL
PNEUMONITIS. CARDIAC ARRYTGMI AS HAVE
BEEN REPORTED W/SOLVENT
EXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:112F,44C
Lower Limits:0.8
Upper Limits:5.0
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, AND WATER FOG
Fire Fighting Procedures:FLAMMABLE. DONT ENTER CONFINED FIRE SPACE W/O
PROTECTIVE CLOTH & POS PRESSURE SCBA. EXCLUDE AIR. DONT USE WATER
EXCEPT AS FOG (USE TO COOL FIRE EXPOSED CNTNRS)
Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLA

MES AND ALL

IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNIT SOURCE. VENT AREA. ABSORB SPILL W/ABSORBENT (SAWDUST, SAND, VERMICULITE), PLACE IN CLOSD CNTNR. LARGE: DIKE AREA TO PREVENT MATERIAL FROM ENTERING WATER SYSTEMS/SEWERS. WEAR PROTECTIVE CLOTHES. NOTIFY ENVIRONMNTL AGENCIES IF >220 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE LIQUID. STORE IN COOL, DRY, WELL-VENTED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED/REPEATED CONTACT WITH SKIN. AVOID BREATHING
Other Precautions:WASH CONTAM CLOTHES PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE. GROUND CNTNR WHEN POURING & LIMIT FREE FALL (MINIMIZE STATIC BLDUP). EMPTY CNTNRS HAZARDOUS FROM RESIDUES. DONT TAKE INTERNALLY. CLOSE CN TNR AFTER USE. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPOR OR SPRAY MISTS WHEN TLV PEL IS EXCEEDED.
Ventilation:GENERAL VENT REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED TO KEEP EXPOSURE LEVEL BELOW LIMITS.
Protective Gloves:CHEM RESIST NITRILE, NEOPRENE, RUBBER
Eye Protection:WEAR FACE SHIELDS OR CHEMICAL GOGGLES
Other Protective Equipment:WEAR EAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.
Supplemental Safety and Health
*DERMAL 74 ML/KG. BENZENE RAT ORAL >5600 ML/KG. INHAL: 13700 PPM 4 HR.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:301 TO 402F
Vapor Pres:>7.0 @ 38C
Vapor Density:4.8
Spec Gravity:0.87 (WATER=1)
pH:NA
Evaporation Rate & Reference:SLOWER THAN N-BUTYL AC
Solubility in Water:NEGLIGIBLE
Appearance and Odor:M

AHOGANY THIN LIQUID, MAHOGANY, MILD ODOR
Percent Volatiles by Volume:65-69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE ARE
PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:IF NOT POSSIBLE TO RECLAIM, TREAT AS HAZARDOUS
WASTE (EPA WASTE #D001) BASED ON IGNITABILITY. ALL DISPOSAL
PROCEDURES MUST COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.